

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST

PRESSURE WASHER

SITE AND BLDG #: PA168

**MECHANIC
SIGNATURE:**
DATE:
LOCATION/RM #: **WO#** 4628 **ASSET #** 6756

START TIME:
FINISH TIME:

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
SPECIAL INSTRUCTIONS				
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.			
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.			
3	Turn off gas and electricity before servicing. Turn back on after completion			
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	Clean the strainer screen, in the hose connection at the float tank.			
2	Check the oil level. Change the oil after 50 hours of operation, and thereafter every 500 hours. Use SAE 30 weight non detergent oil.			
3	Use teflon tape or approved sealer on the plumbing connections when reassembling to prevent leakage.			
4	Deliming coils: Periodic flushing of the coils is recommended to extend coil life and prevent lime buildup. Clean coils as needed.			

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed discription of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes: