

CERTIFICATION OF WORK  
(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: Pr053

Date of Visit: 7/17/19

Contractor Personnel on Site:

1. Tony Cozans
2. Jim Geertgens
3. Scott Wenz

4. \_\_\_\_\_
5. \_\_\_\_\_
6. \_\_\_\_\_

**Work Performed:**

**Preventive Maintenance** - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)

1. 9913
2. 9947
3. \_\_\_\_\_
4. \_\_\_\_\_

**CERTIFICATION OF WORK**

To be signed by the Contractor:

Print Name: Jim Geertgens Date: 7-17-19

Signed: 

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: Paul N. Overbeck GOS Date: 17 July 19

Signed: 

E-Mail: Paul.n.overbeck.civil@mail.mil

OTHER RECURRING SERVICES CERTIFICATION OF WORK  
(To be completed by the Contractor and saved in the Contractor's CMMS)

FacID/Building: Pro 83

Date of Visit: 7/17/19

Contractor Personnel on Site:

1. Tony Grimes  
2. Scott Berry  
3. Jim Geertgens

4. \_\_\_\_\_  
5. \_\_\_\_\_  
6. \_\_\_\_\_

Work Performed:

Other Recurring Services

1. 9828  
2. \_\_\_\_\_  
3. \_\_\_\_\_  
4. \_\_\_\_\_

**CERTIFICATION OF WORK**

To be signed by the Contractor:

Print Name: Jim Geertgens Date: 7-17-19

Signed: Jim Geertgens

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: Paul N. Ondrejek 6509 Date: 7/17/19

Signed: Paul N. Ondrejek

E-Mail:

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
GATES, FENCES, SECURITY AND ACCESS

SITE AND BLDG #:

P-053-01

LOCATION/RM #:

MGP

WO# 2913

ASSET # 7528

MECHANIC  
SIGNATURE:  


DATE:

2/12/19

START TIME:

8:00

FINISH TIME:

8:15

CHECK ITEM	DESCRIPTION	WORK COMPLETED YES (Y) NO (N)	NOTES/ACTUATIONS	
			HE GATE/DOOR WAS REFERRED TO PROVIDE INFORMATION	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.			
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.			
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>				
<b>GATES</b>				
1	Inspect all pivot points, hinges, latches, etc. Apply lubricant where needed, wiping off excess.			
2	Check all locking devices. Lubricate as required.			
3	Inspect center gate support rollers and lubricate as required.			
4	Clean roller track of any debris.			
5	Check bolts, fasteners, and mounting hardware. Tighten or adjust as necessary.			
6	Check for any obstructions that retard full swing or movement of the gate.			
7	Check that shrubs and trees are pruned clear of gate.			
8	Check hold open devices for proper operation. Lubricate as required.			
<b>FENCES</b>				
1	Check posts and corner posts, support guys, and horizontal bars between each support post.			
2	Check wire and anchor point; re-stretch and re-anchor if necessary.			
3	Inspect fence anchors along the bottom of the fence and at the point where the fence is connected to the post.			
4	Treat with galvanized protectant where rust has developed.			
5	If approved, apply weed control along entire base of fence. Consult the Safety Data Sheets (SDS) for hazardous ingredients and proper personal protective equipment (PPE).			
6	Check that shrubs and trees are pruned clear of fencing.			

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.  
To be performed by: General Maintenance Worker  
Additional Notes:

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
**POWER OPERATED OVERHEAD DOOR**

ACTIVITY AND BLDG #: *Pa 053-01*

LOCATION: *Storage 6004 9913* *psud 17624*

MECHANIC  
SIGNATURE: *Anthony*

DATE: *2/12/18*

START TIME: *815*

FINISH TIME: *825*

CHECK POINT	CHECKPOINT DESCRIPTION	SPECIAL INSTRUCTIONS	TASK COMPLETED		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO. PROVIDE EXPLANATION)
			YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.				
2	Review manufacturer's instructions.		✓		
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.		✓		
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>					
1	Inspect general arrangement of door and mechanism, mountings, standards, wind locks, anchor bolts, counterbalances, weather stripping, door sweeps etc. Clean, tighten, and adjust repair as required.				
2	Operate with power from stop to stop and at intermediate positions. Observe performance of various components, such as brake, limit switches, door operating speed, motor, gear box, etc. Clean and adjust as needed.		✓		
3	Check operation of safety edges, stops, electric eye, treadle, or other operating devices. Clean and make required adjustments or repairs.		✓		
4	Check manual operation. Note brake release, motor disengagement, functioning of hand pulls, chains sprockets, clutch, etc.		✓		
5	Examine all wiring, motor, starter, push button, etc., blow out or vacuum if needed.		✓		
6	Inspect gear box, change or add oil as required.		✓		
7	Perform required lubrication. Remove old or excess lubricant.		✓		
8	Clean unit and mechanism thoroughly. Touch up paint where required.		✓		
9	Clean up and remove all debris.		✓		

Note: The Contractor shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence.  
 Checklist compiled in accordance with:

- General Services Administration (GSA) Public Building Service. 2012. *Public Buildings Maintenance Standards Final*. October 1.
- Original equipment manufacturers (OEM) documentation for exact or similar assets, which can be located at ([Provide Link to OEM Manual/Asset Library](#))


Additional Notes:

*10x20*

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
**POWER OPERATED OVERHEAD DOOR**

ACTIVITY AND BLDG #: PA 053-0

LOCATION: DRILL WEF 9913 Asset # 2219

MECHANIC  
SIGNATURE: 

DATE: 2/12/10

START TIME: 8:15

FINISH TIME: 8:30

CHECK POINT	CHECKPOINT DESCRIPTION	SPECIAL INSTRUCTIONS	TASK COMPLETE		NOTES/ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
			YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.		<input checked="" type="checkbox"/>		
2	Review manufacturer's instructions.		<input checked="" type="checkbox"/>		
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.		<input checked="" type="checkbox"/>		
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>					
1	Inspect general arrangement of door and mechanism, mountings, standards, wind locks, anchor bolts, counterbalances, weather stripping, door sweeps etc. Clean, tighten, and adjust repair as required.		<input checked="" type="checkbox"/>		
2	Operate with power from stop to stop and at intermediate positions. Observe performance of various components, such as brake, limit switches, door operating speed, motor, gear box, etc. Clean and adjust as needed.		<input checked="" type="checkbox"/>		
3	Check operation of safety edges, stops, electric eye, treadle, or other operating devices. Clean and make required adjustments or repairs.		<input checked="" type="checkbox"/>		
4	Check manual operation. Note brake release, motor disengagement, functioning or hand pulls, chains sprockets, clutch, etc.		<input checked="" type="checkbox"/>		
5	Examine all wiring, motor, starter, push button, etc., blow out or vacuum if needed.		<input checked="" type="checkbox"/>		
6	Inspect gear box, change or add oil as required.		<input checked="" type="checkbox"/>		
7	Perform required lubrication. Remove old or excess lubricant.		<input checked="" type="checkbox"/>		
8	Clean unit and mechanism thoroughly. Touch up paint where required.		<input checked="" type="checkbox"/>		
9	Clean up and remove all debris.		<input checked="" type="checkbox"/>		

Note: The Contractor shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence.  
 Checklist compiled in accordance with:

- General Services Administration (GSA) Public Building Service, 2012. *Public Buildings Maintenance Standards Final*, October 1.

- Original equipment manufacturers (OEM) documentation for exact or similar assets, which can be located at ([Provide Link to OEM Manual/Asset Library](#))

Additional Notes:

14 X 14

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
**MANUAL/AUTOMATIC ROLL-UP DOORS**

ACTIVITY AND BLDG #:

PA 053 - 01

LOCATION: DRIVE DOOR 9813 ASSET # 2985

MECHANIC  
SIGNATURE:

DATE:

7/12/18

START TIME:

8:35

FINISH TIME:

8:45

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETED YES <input type="checkbox"/> NO <input type="checkbox"/>	SPECIAL INSTRUCTIONS		NOTES/ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
			1	2	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.	<input type="checkbox"/>		<input type="checkbox"/>	
2	Review manufacturer's instructions.	<input type="checkbox"/>		<input type="checkbox"/>	
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	<input type="checkbox"/>		<input type="checkbox"/>	
TO BE PERFORMED AT EACH INSPECTION SERVICE					
1	Check with door operating personnel for any known deficiencies.	<input type="checkbox"/>			
2	Inspect general arrangement of door and mechanism, mountings, standards, wind locks, anchor bolts, counterbalances, weather stripping, door sweeps etc. Clean, tighten, and adjust repair as required.	<input type="checkbox"/>			
3	If applicable, operate with power from start to stop and at intermediate positions. Observe performance of various components, such as brake, limit switches, door operating speed, motor, gear box, etc. Clean and adjust as needed.	<input type="checkbox"/>		<i>NA</i>	
4	Check operation of safety edges, stops, electric eye, treadle, or other operating devices. Clean and make required adjustments or repairs.	<input type="checkbox"/>		<i>NP</i>	
5	Check manual operation. Note brake release, motor disengagement, functioning or hand pulls, chains sprockets, clutch, etc.	<input type="checkbox"/>			
6	If applicable, examine all wiring, motor, starter, push button, etc., blow out or vacuum if needed.	<input type="checkbox"/>		<i>NP</i>	
7	If applicable, inspect gear box, change or add oil as required.	<input type="checkbox"/>			
8	Perform required lubrication. Remove old or excess lubricant.	<input type="checkbox"/>			
9	Clean unit and mechanism thoroughly. Touch up paint where required.	<input type="checkbox"/>			
10	Clean up and remove all debris.	<input type="checkbox"/>			

Note: The Contractor shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence.  
 Checklist compiled in accordance with:

- Original equipment manufacturers (OEM) documentation for exact or similar assets, which can be located at ([Provide Link to OEM Manual/Asset Library](#))  
 Additional Notes:

10K 3

Rullen, Foss, Shuford