

CERTIFICATION OF WORK
(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: Pr 079

Date of Visit: 7/22/19

Contractor Personnel on Site:

1. Tony Gerecus
2. Jim Goetges
3. _____
4. _____
5. _____
6. _____

Work Performed:

Preventive Maintenance - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)

1. 9906
2. 9734
3. 9963
4. _____

CERTIFICATION OF WORK

To be signed by the Contractor:

Print Name: Jim Goetges Date: 7-22-19

Signed: 

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: Josh Sutton / GS-11 Date: 22 Jul 19

Signed: 

E-Mail:

OTHER RECURRING SERVICES CERTIFICATION OF WORK
(To be completed by the Contractor and saved in the Contractor's CMMS)

FacID/Building: Pr 079-01 Date of Visit: 7/22/19

Contractor Personnel on Site:

1. Tony Czerwos
2. Scott Werry
3. _____
4. _____
5. _____
6. _____


Work Performed:

Other Recurring Services

1. 9810
2. _____
3. _____
4. _____


CERTIFICATION OF WORK

To be signed by the Contractor:

Print Name: Tim Czerwos Date: 7-22-19
Signed: 

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: Josh Sutton/GS-11 Date: 22 Jul 19
Signed: 

E-Mail: joshua.e.sutton2.civ@mail.mil

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
GATES, FENCES, SECURITY AND ACCESS

SITE AND BLDG #: *Pr 078-01*LOCATION/RM #: *POU* WO# *9906*ASSET # *7806*MECHANIC
SIGNATURE: *Jewell*DATE: *7/22/19*START TIME: *7:30*FINISH TIME: *7:40*

CHECK#	DESCRIPTION	WORK COMPLETED		NOTES/INSTRUCTIONS
		YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.			
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.			
TO BE PERFORMED AT EACH INSPECTION SERVICE				
GATES				
1	Inspect all pivot points, hinges, latches, etc. Apply lubricant where needed, wiping off excess.			
2	Check all locking devices. Lubricate as required.			
3	Inspect center gate support rollers and lubricate as required.			
4	Clean roller track of any debris.			
5	Check bolts, fasteners, and mounting hardware. Tighten or adjust as necessary.			
6	Check for any obstructions that retard full swing or movement of the gate.			
7	Check that shrubs and trees are pruned clear of gate.			
8	Check hold open devices for proper operation. Lubricate as required.			
FENCES				
1	Check posts and corner posts, support guys, and horizontal bars between each support post.			
2	Check wire and anchor point; re-stretch and re-anchor if necessary.			
3	Inspect fence anchors along the bottom of the fence and at the point where the fence is connected to the post.			
4	Treat with galvanized protectant where rust has developed.			
5	If approved, apply weed control along entire base of fence. Consult the Safety Data Sheets (SDS) for hazardous ingredients and proper personal protective equipment (PPE).			
6	Check that shrubs and trees are pruned clear of fencing			

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes:

JK

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
GATES, FENCES, SECURITY AND ACCESS

SITE AND BLDG #: *Pr 079-01*LOCATION/RM #: *POV* WO# *9906*ASSET # *7527*MECHANIC
SIGNATURE: *[Signature]*DATE: *7/22/18*START TIME: *7:30*FINISH TIME: *7:40*

CHECK LIST	ITEM/POINT DESCRIPTION	WORK COND/EQUIP YES / NO	NOTES/ACTIONS	
			SPECIAL INSTRUCTIONS	THE BULK OF THIS FORM IS DEDICATED TO PREPARATION AND NOTES
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.			
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.			
TO BE PERFORMED AT EACH INSPECTION SERVICE				
GATES				
1	Inspect all pivot points, hinges, latches, etc. Apply lubricant where needed, wiping off excess.			
2	Check all locking devices. Lubricate as required.			
3	Inspect center gate support rollers and lubricate as required.			
4	Clean roller track of any debris.			
5	Check bolts, fasteners, and mounting hardware. Tighten or adjust as necessary.			
6	Check for any obstructions that retard full swing or movement of the gate.			
7	Check that shrubs and trees are pruned clear of gate.			
8	Check hold open devices for proper operation. Lubricate as required.			
FENCES				
1	Check posts and corner posts, support guys, and horizontal bars between each support post.	<i>NP</i>		
2	Check wire and anchor point; re-stretch and re-anchor if necessary.	<i>NP</i>		
3	Inspect fence anchors along the bottom of the fence and at the point where the fence is connected to the post.	<i>NP</i>		
4	Treat with galvanized protectant where rust has developed.	<i>NP</i>		
5	If approved, apply weed control along entire base of fence. Consult the Safety Data Sheets (SDS) for hazardous ingredients and proper personal protective equipment (PPE).	<i>NP</i>		
6	Check that shrubs and trees are pruned clear of fencing	<i>NP</i>		

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes:

[Signature]

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
GATES, FENCES, SECURITY AND ACCESS

SITE AND BLDG #: *Pr 079-01*LOCATION/RM #: *MEL* WO# *9906*ASSET # *7548*MECHANIC
SIGNATURE: *John M. Johnson*DATE: *7/22/19*START TIME: *740*FINISH TIME: *745*

CHECK LIST	DESCRIPTION	LAST COMPLETED	YRS. (NO.)	NOTES/EXCLUSIONS	
				SPECIAL INSTRUCTIONS	THE BULK OF THE MAINTENANCE IS PERFORMED BY PROVIDER/EXCUSE
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.			/	
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.			/	
TO BE PERFORMED AT EACH INSPECTION SERVICE					
GATES					
1	Inspect all pivot points, hinges, latches, etc. Apply lubricant where needed, wiping off excess.			/	
2	Check all locking devices. Lubricate as required.			/	
3	Inspect center gate support rollers and lubricate as required.			/	
4	Clean roller track of any debris.			/	
5	Check bolts, fasteners, and mounting hardware. Tighten or adjust as necessary.			/	
6	Check for any obstructions that retard full swing or movement of the gate.			/	
7	Check that shrubs and trees are pruned clear of gate.			/	
8	Check hold open devices for proper operation. Lubricate as required.			/	
FENCE					
1	Check posts and corner posts, support guys, and horizontal bars between each support post.			/	
2	Check wire and anchor point; re-stretch and re-anchor if necessary.			/	
3	Inspect fence anchors along the bottom of the fence and at the point where the fence is connected to the post.			/	
4	Treat with galvanized protectant where rust has developed.			/	
5	If approved, apply weed control along entire base of fence. Consult the Safety Data Sheets (SDS) for hazardous ingredients and proper personal protective equipment (PPE).			/	
6	Check that shrubs and trees are pruned clear of fencing			/	

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes:

JK

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
GATES, FENCES, SECURITY AND ACCESS

SITE AND BLDG #: *Pr 079-a1*LOCATION/RM #: *MEP*WO# *9906*ASSET # *7549*MECHANIC
SIGNATURE: *[Signature]*DATE: *7/22/18*START TIME: *740*FINISH TIME: *750*

CHECK ITEM	DESCRIPTION/INSTRUCTION	PARK COMPLETION		NOTES/EXCLUSIONS (IF ANY)
		YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.			
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.			
TO BE PERFORMED AT EACH INSPECTION SERVICE				
GATES				
1	Inspect all pivot points, hinges, latches, etc. Apply lubricant where needed, wiping off excess.			
2	Check all locking devices. Lubricate as required.			
3	Inspect center gate support rollers and lubricate as required.			
4	Clean roller track of any debris.			
5	Check bolts, fasteners, and mounting hardware. Tighten or adjust as necessary.			
6	Check for any obstructions that retard full swing or movement of the gate.			
7	Check that shrubs and trees are pruned clear of gate.			
8	Check hold open devices for proper operation. Lubricate as required.			
FENCES				
1	Check posts and corner posts, support guys, and horizontal bars between each support post.			
2	Check wire and anchor point; re-stretch and re-anchor if necessary.			
3	Inspect fence anchors along the bottom of the fence and at the point where the fence is connected to the post.			
4	Treat with galvanized protectant where rust has developed.			
5	If approved, apply weed control along entire base of fence. Consult the Safety Data Sheets (SDS) for hazardous ingredients and proper personal protective equipment (PPE).			
6	Check that shrubs and trees are pruned clear of fencing			

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes:

b/c

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
POWER OPERATED OVERHEAD DOOR

ACTIVITY AND BLDG #:

P1079-01

LOCATION: DRILL WELD 9806 Asset # 7702

MECHANIC
SIGNATURE:

DATE:

7/22/11

START TIME:

750

FINISH TIME:

800

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ACTIONS (IF TASK COMPLETE IS CHECKED NO PROVIDE EXPLANATION)
		YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.			
2	Review manufacturer's instructions.	✓	✗	
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.		✓	
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	Inspect general arrangement of door and mechanism, mountings, standards, wind locks, anchor bolts, counterbalances, weather stripping, door sweeps etc. Clean, tighten, and adjust repair as required.	✓		
2	Operate with power from stop to stop and at intermediate positions. Observe performance of various components, such as brake, limit switches, door operating speed, motor, gear box, etc. Clean and adjust as needed.	✓		
3	Check operation of safety edges, stops, electric eye, treadle, or other operating devices. Clean and make required adjustments or repairs.	✓		
4	Check manual operation. Note brake release, motor disengagement, functioning of hand pulls, chains sprockets, clutch, etc.	✓		
5	Examine all wiring, motor, starter, push button, etc., blow out or vacuum if needed.	✓		
6	Inspect gear box, change or add oil as required.	✓		
7	Perform required lubrication. Remove old or excess lubricant.	✓		
8	Clean unit and mechanism thoroughly. Touch up paint where required.	✓		
9	Clean up and remove all debris.	✓		

Note: The Contractor shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence.

Checklist compiled in accordance with:

- General Services Administration (GSA) Public Building Service. 2012. *Public Buildings Maintenance Standards Final*. October 1.

- Original equipment manufacturers (OEM) documentation for exact or similar assets, which can be located at ([Provide Link to OEM Manual/Asset Library](#))

Additional Notes:

13 X 12

DOOR NEEDS PAINTED

BK

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
MANUAL/AUTOMATIC ROLL-UP DOORS

ACTIVITY AND BLDG #: PA 079-01

LOCATION: Kitchen Ws# 9906 Asset # 8009

MECHANIC
SIGNATURE: *John*

DATE: 7/22/19

START TIME: 810

FINISH TIME: 815

CHECK POINT	CHECKPOINT DESCRIPTION	SPECIAL INSTRUCTIONS	TASK COMPLETED		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
			YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.				
2	Review manufacturer's instructions.				
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.				
TO BE PERFORMED AT EACH INSPECTION SERVICE					
1	Check with door operating personnel for any known deficiencies.				
2	Inspect general arrangement of door and mechanism, mountings, standards, wind locks, anchor bolts, counterbalances, weather stripping, door sweeps etc. Clean, tighten, and adjust repair as required.				
3	If applicable, operate with power from start to stop and at intermediate positions. Observe performance of various components, such as brake, limit switches, door operating speed, motor, gear box, etc. Clean and adjust as needed.				
4	Check operation of safety edges, stops, electric eye, treadle, or other operating devices. Clean and make required adjustments or repairs.				
5	Check manual operation. Note brake release, motor disengagement, functioning or hand pulls, chains sprockets, clutch, etc.				
6	If applicable, examine all wiring, motor, starter, push button, etc., blow out or vacuum if needed.				
7	If applicable, inspect gear box, change or add oil as required.				
8	Perform required lubrication. Remove old or excess lubricant.				
9	Clean unit and mechanism thoroughly. Touch up paint where required.				
10	Clean up and remove all debris.				

Note: The Contractor shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence.
 Checklist compiled in accordance with:

- Original equipment manufacturers (OEM) documentation for exact or similar assets, which can be located at ([Provide Link to OEM Manual/Asset Library](#))
 Additional Notes:

2 x 3
 Rolling Fire Shutter

BK

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
MANUAL/AUTOMATIC ROLL-UP DOORS

ACTIVITY AND BLDG #: Pp 079-01
 LOCATION: Kitchen wall 9906 Asset# 8012

MECHANIC SIGNATURE: Anthony DATE: 7/22/19
 START TIME: 8:15 FINISH TIME: 8:20

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETED		NOTES/ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
SPECIAL INSTRUCTIONS				
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.		-	
2	Review manufacturer's instructions.		-	
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.		-	
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	Check with door operating personnel for any known deficiencies.	-		
2	Inspect general arrangement of door and mechanism, mountings, standards, wind locks, anchor bolts, counterbalances, weather stripping, door sweeps etc. Clean, tighten, and adjust repair as required.	-		
3	If applicable, operate with power from start to stop and at intermediate positions. Observe performance of various components, such as brake, limit switches, door operating speed, motor, gear box, etc. Clean and adjust as needed.			
4	Check operation of safety edges, stops, electric eye, treadle, or other operating devices. Clean and make required adjustments or repairs.			NP
5	Check manual operation. Note brake release, motor disengagement, functioning or hand pulls, chains sprockets, clutch, etc.			N/A
6	If applicable, examine all wiring, motor, starter, push button, etc., blow out or vacuum if needed.	-		
7	If applicable, inspect gear box, change or add oil as required.			N/A
8	Perform required lubrication. Remove old or excess lubricant.	-		
9	Clean unit and mechanism thoroughly. Touch up paint where required.	-		
10	Clean up and remove all debris.			

Note: The Contractor shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence.
 Checklist compiled in accordance with:

- Original equipment manufacturers (OEM) documentation for exact or similar assets, which can be located at ([Provide Link to OEM Manual/Asset Library](#))

Additional Notes:

Ex 3

Rolling Fire Shutter

BL