

ATTACHMENT J-0200000-05  
FORMS

CERTIFICATION OF WORK  
(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: Pr 087

Date of Visit: 5/30/19

Contractor Personnel on Site:

1. Tony Lazarus
2. Jim Geertgas
3. SK Werry

- 4.
- 5.
- 6.

Work Performed:

**Preventive Maintenance** - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)

1. <u>8525</u>	<u>8687</u>
2. <u>8618</u>	<u>8735</u>
3. <u>8748</u>	
4. <u>8539</u>	

CERTIFICATION OF WORK

To be signed by the Contractor:

Print Name: Jim Geertgas Date: 5-30-19

Signed: 

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: WACFF JAMES T. 659 Date: 30 MAY 19

Signed: 

E-Mail: james.t.wacff.cust@mail.com

OTHER RECURRING SERVICES CERTIFICATION OF WORK  
(To be completed by the Contractor and saved in the Contractor's CMMS)

Facility/Building: Pp 087-01 Date of Visit: 5/7/18

Contractor Personnel on Site:

1. Tony Lazarus  
2. Jim Geertgens  
3. Scott Werry  
4.  
5.  
6.

Work Performed:

Other Recurring Services

1. 8584  
2.  
3.  
4.

CERTIFICATION OF WORK

To be signed by the Contractor:

Print Name: Jim Geertgens Date: 5-30-19

Signed: Jim Geertgens

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: \_\_\_\_\_ Date: \_\_\_\_\_

Signed: \_\_\_\_\_

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
AIR HANDLER

SITE AND BLDG #: PA 082-01  
LOCATION/RM #: 1st floor WO# 9748 ASSET # 3168

MECHANIC SIGNATURE: *Mark M. Dwyer* DATE: 5/30/18  
START TIME: 10:40 FINISH TIME: 11:00

ITEM	DESCRIPTION	LAST PERFORMED	NOTES/CAUTIONS	
			YES	NO
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.		✓	
2	Remove power at Drive or at Breaker Panel. Verify with tester or meter that power has been removed. Install lock out tag out if servicing alone or in confined space for safety precautions.		✓	
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>				
1	Check fan blades and moving parts for cracks and excessive wear.		✓	
2	Check running motor amperatures on all three phases (record in note column) noteate L1, L2, and L3 amp draws.		✓	L1 3.2 L2 3.3 L3 _____
3	Tighten all electrical connectors/lugs to proper torque.		✓	
4	If unit is a multi-zone air handler, then check each individual zone damper and associated controls.		✓	
5	Check bearing collar set screws on fan shaft to make sure they are tight.		✓	N/A
6	Check filters for dirt accumulations, replace as necessary. Check belt, repair or replace as necessary.		✓	
7	Check damper actuators and linkage for proper operation. Adjust linkage on dampers if out of alignment.		✓	N/A
8	Lubricate mechanical bearings and connections sparingly.		✓	
9	Clean coils by brushing, blowing, vacuuming, or pressure washing.		✓	
10	Check coils for leaking, tightness of fittings.		✓	
11	Use fin comb to straighten coil fins.		✓	
12	If applicable, clean strainer (annually).		✓	N/A
13	Flush and clean condensate pans and drains, remove all rust prepare metal and paint. Hose down coils and drain pans and wash with an appropriate EPA approved solution approved solution. Treat condensate pans with an EPA approved biocide.		✓	
14	Check belts for wear and cracks, adjust tension or alignment. Replace belts when necessary. Multi-belt drives shall only be replaced with matched sets.		✓	
15	Check rigid couplings for alignment on direct drives, and for tightness of assembly. Check flexible couplings for alignment and wear.		✓	
16	Check and test freezestat for proper operation		✓	
17	Vacuum interior of unit.		✓	
18	Check filter doors and access doors for proper gasketing and air leaks. Correct as necessary.		✓	
19	Lubricate fan shaft bearings while unit is running. Add grease slowly until slight bleeding is noted from the seals. Do not over lubricate. Remove old or excess lubricant.		✓	
20	Clean up work area.		✓	

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: HVAC Technician

Additional Notes:

AHU-1

b/w

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
AIR HANDLER

SITE AND BLDG #: PA 087 - G1  
LOCATION/RM #: DREC WO# 8748 ASSET # 3170

MECHANIC SIGNATURE: *Anton* DATE: 5/3/18  
START TIME: 1015 FINISH TIME: 1100

ITEM	DESCRIPTION	LAST COMPLETED		NOTES/REMARKS (INCLUDE REASON FOR EXEMPTION)
		YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.		/	
2	Remove power at Drive or at Breaker Panel. Verify with tester or meter that power has been removed. Install lock out tag out if servicing alone or in confined space for safety precautions.		/	
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>				
1	Check fan blades and moving parts for cracks and excessive wear.	/		
2	Check running motor amperages on all three phases (record in note column) notate L1, L2, and L3 amp draws.	/		L1 10.5 L2 10.6 L3
3	Tighten all electrical connectors/lugs to proper torque.	/		
4	If unit is a multi-zone air handler, then check each individual zone damper and associated controls.	/		
5	Check bearing collar set screws on fan shaft to make sure they are tight.	/		
6	Check filters for dirt accumulations, replace as necessary. Check belt, repair or replace as necessary.	/		
7	Check damper actuators and linkage for proper operation. Adjust linkage on dampers if out of alignment.	/		
8	Lubricate mechanical bearings and connections sparingly.	/		
9	Clean coils by brushing, blowing, vacuuming, or pressure washing.	/		
10	Check coils for leaking, tightness of fittings.	/		
11	Use fin comb to straighten coil fins.	/		
12	If applicable, clean strainer (annually).	/		
13	Flush and clean condensate pans and drains, remove all rust prepare metal and paint. Hose down coils and drain pans and wash with an appropriate EPA approved solution approved solution. Treat condensate pans with an EPA approved biocide.	/		
14	Check belts for wear and cracks, adjust tension or alignment. Replace belts when necessary. Multi-belt drives shall only be replaced with matched sets.	/		
15	Check rigid couplings for alignment on direct drives, and for tightness of assembly. Check flexible couplings for alignment and wear.	/		
16	Check and test freezestat for proper operation	/		
17	Vacuum interior of unit.	/		
18	Check filter doors and access doors for proper gasketing and air leaks. Correct as necessary.	/		
19	Lubricate fan shaft bearings while unit is running. Add grease slowly until slight bleeding is noted from the seals. Do not over lubricate. Remove old or excess lubricant.	/		
20	Clean up work area.	/		

No. e: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: HVAC Technician

Additional Notes:

A10U - 2

hC

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
**OUTDOOR CONDENSING UNIT**

SITE AND BLDG #:

P1 081-01

LOCATION/RM #:

WO# 5748

ASSET # 3301

MECHANIC  
SIGNATURE:

DATE:

5/3/13

START TIME:

645

FINISH TIME:

800

ITEM #	DESCRIPTION	SPECIAL INSTRUCTIONS		NOTES/ACHIEVEMENT
		YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.	/		
2	Schedule outage of unit with personnel in area the unit serves.	/		
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	/		
4	If disposal of the equipment is required, follow regulations concerning removal of refrigerants and disposal of the unit.	/		
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	Remove debris from air screen and clean underneath unit.	/		
2	Wash coil with coil cleaning solution - Rinse Thoroughly	/		
3	Straighten fin tubes with fin comb, as needed.	/		
4	Check electrical connections for tightness.	/		
5	Check mounting base for tightness.	/		
6	Inspect fans for bent blades, unbalance, excessive noise and vibrations.	/		
7	Inspect all piping for leaks and tighten loose connections.	/		
8	Check wires at condenser electrical fused safety switches for tightness and burned insulation. Repair as necessary.	/		
9	Check supply air temperature to ensure unit is operating properly. If possible record room temperature.	/		
10	Inspect unit for overall condition and recommend for replacement or other needed repairs.	/		
11	Clean up work area.	/		

Note. The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: HVAC Technician

Additional Notes:

ACCU - 1

b6

## PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST

## VAV BOX

SITE AND BLDG #: P1 087 - 01LOCATION/RM #: 113 WO# 8748 ASSET # 4725MECHANIC  
SIGNATURE: JohnDATE: 5/30/18START TIME: 800FINISH TIME: 805

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETED		NOTES/ACTIONS (IF TASK COMPLETED IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
SPECIAL INSTRUCTIONS				
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.		/	
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.		/	
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	If EMS system permits, check that the operating controls activate damper per design specifications.	/		
2	If required, check damper linkage for tightness and lightly lubricate.	/		
3	If required, inspect dampers for free movement.	/		
4	If required, inspect actuators for tightness to mounting brackets.	/		
5	As needed, tighten electrical connections to servo motor.	/		
6	Inspect unit for overall condition and recommend for replacement or other needed repairs.	/		

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: HVAC Technician

Additional Notes:

VAV - 10      15      INACTIVE, No Heat allowed  
                     15      Computer Room

1      PC

BC

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
VAV BOX

SITE AND BLDG #:

PA 081-41

MECHANIC  
SIGNATURE:

DATE:

130/19

LOCATION/RM #:

WO# 5798

ASSET # 4832

START TIME:

805

FINISH TIME:

800

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETED		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
<b>SPECIAL INSTRUCTIONS</b>				
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.		✓	
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.		✓	
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>				
1	If EMS system permits, check that the operating controls activate damper per design specifications.	✓		
2	If required, check damper linkage for tightness and lightly lubricate.	✓		
3	If required, inspect dampers for free movement.	✓		
4	If required, inspect actuators for tightness to mounting brackets.	✓		
5	As needed, tighten electrical connections to servo motor.	✓		
6	Inspect unit for overall condition and recommend for replacement or other needed repairs.	✓		

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: HVAC Technician

Additional Notes:

9

PC

101  
102  
104105  
106  
106

107

108

102

B16

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
**DEHUMIDIFIER**

SITE AND BLDG #: *P1 087-C1*

LOCATION/RM #:

WO# *8748*ASSET # *5049*MECHANIC  
SIGNATURE:*John*

DATE:

*5/20/13*

START TIME:

*900*

FINISH TIME:

*910*

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	

- 1 In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.
- 2 Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.
- 3 Check water inlet and outlet for any leaks, repair as needed.
- 4 Clean and/or replace filter as needed.
- 5 If applicable, check hours per usage, replace tanks as needed.

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes:

*BK*