

Over and Above Repair Work - Order Number and Description of Work Completed

looked at Fin Tube Radiator in office. found
to have very poor flow. Checked Boiler out
to find system low on water. 9 Psi. - BPS.
Tried to add water but Reducing Valve is bad.

Shut off feed until Replacement.

Also ordered cylinder for Boiler system Main Bldg.

CERTIFICATION OF WORK

To be signed by the Contractor:

Print Name: Justin Zavaacky Date: 2-8-19

Signed: _____

To be signed by Facility Manager:

I certify that the above named individuals representing the Contractor arrived on site and to the best of my knowledge, completed the stated work listed:

Print Name/Rank: Esther Date: 2-8-19

Signed: _____

E-Mail: jose.f.lacoste@marl.mil

EMERCOOL[®] NFE

Inhibited Ethylene Glycol

DANGER: HARMFUL OR FATAL IF SWALLOWED

HANDLING:

Wear protective clothing and equipment. Avoid eye and skin contact. Keep container closed when not in use. Wash thoroughly after handling.

IN CASE OF FIRE:

Use water spray, carbon dioxide, dry chemical or alcohol-type foam or universal-type foam.

FOR SPILL:

Contain spill by diking. Collect for disposal. Dispose of at approved waste disposal facility in accordance with applicable laws and regulations.

For further information, refer to MATERIAL SAFETY DATA SHEET. Contact employer for additional instructions.
IN CASE OF TRANSPORTATION EMERGENCY, CONTACT CHEMTREC (800) 424-9300

DISTRIBUTED BY:
M & P INDUSTRIES INC
P.O. Box 57, Lesage, WV 25702
PHONE: (304) 736-4046

HMIS

Health:	0
Flammability:	1
Physical Hazard:	0
Personal Protection:	B

FIRST AID:

EYE OR SKIN CONTACT: Immediately flush with water. Remove contaminated clothing and launder before reuse.

INHALATION: If affected, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical assistance.

IF SWALLOWED: Give two glasses of water and induce vomiting. Get immediate medical assistance.

NET VOLUME
55 gallons
35% GLYCOL

LOT#
227910-