

Additional Funding Request

NY0039	CSS# 20689 WO# 5729 Asset# NA			
Description of Repairs	Labor and materials to replace hot water shutoff valve broken and stuck in the closed position.			
Diagnosis: Initial Work Order	Found that the hot water shut off valve might be broke in the closed position and I would need to cut the pipe and valve out and replace the valve. There is a possibility that also might find the pipe restricted when I cut into it and I might have to replace the pipe from the valve to the shower.			
Diagnostic Fee	\$0			
Additional Labor Cost to Perform Repairs	\$ 640 TW Labor \$80/hr x 8			
Additional Cost	\$ 123.21			
	Valve and Pipe See parts detail attached	1	\$114.84	\$114.84
	Sales Tax	1		\$8.37
Total Cost of Repair	\$ 763.21			



WORK ESTIMATE

CSS #: 20689

Work Order #: 5729

Emergency ☐ Urgent ☐

Routine ☒

Company Name:	Tidewater, Inc.	Facility ID:	NY039
Contractor POC:	Adam Colopy		
Telephone No:	740-819-6207	Building/Location; (e.g., Classroom/Room #)	
E-Mail Address:	adam.colopy@tideh2o.net		
Assigned Technician(s):	PATRICK BROWN		

DESCRIPTION of WORK and EXPLANATION for REPAIRS or REPLACEMENT

Labor and materials to replace hot water shutoff valve broken and stuck in the closed position.

LABOR/MATERIAL		MATERIAL/ SUB UNIT DOLLAR AMOUNT	LBR/HR \$80	LINE ITEM TOTAL DOLLAR AMOUNT
ITEM	QUANTITY			
Labor			8	\$640.00
Valve and Pipe (See parts attachments)	1			\$114.84
Sales Tax				\$8.37
SUB-TOTAL COSTS:		Materials Total	\$123.21	Labor \$640.00
TOTAL			\$763.21	

Plumbing > Plumbing Valves > Shut-Off Valves > Ball Valves > Manual Ball Valves > Lead-Free Brass Push x Push Ball Valve, Lever, 1" Pipe Size >

Print

Email

SHARKBITE

Lead-Free Brass Push x Push Ball Valve, Lever, 1" Pipe Size

Item # 38EG54 Mfr. Model # 24737LF Catalog Page # N/A UNSPSC # 40141607



Web Price ⓘ
\$63.00 / each

☒ One Time Delivery

1

Add to Cart

+ Add to List |

☒ Shipping ☐ Pickup

Expected to arrive **Fri. Oct 11.**

Ship To **43085** [\(Change\)](#)

★★★★★ | 5.0 of 5 | 1 review | [Write a Review](#)

Shipping Weight 2.74 lbs.

Country of Origin China | *Country of Origin is subject to change.*

Note: Product availability is real-time updated and adjusted continuously. The product will be reserved for you when you complete your order. [More](#)

How can we improve our [Product Images?](#)

☐ Compare

Product Details

[View More](#) ▾

Technical Specs

Item	Ball Valve
Body Material	Lead-Free Brass
Body Style	Inline
General Connection Type	Push
Valve Structure	2-Piece
Pipe Size	1"
Tube Size	1"
Connection Type	Push x Push
Port	Full
Max. Pressure	200 psi CWP
Max. Steam Pressure	200 psi WSP
Temp. Range	32 Degrees to 200 Degrees F
Ball Material	Lead Free Brass

Seat Material	PTFE
Stem Type	Blowout Proof
Handle Type	Lever
Handle Material	Steel
Stem Material	Lead Free Brass
Body Seal Material	EPDM
Hose I.D.	1"
Features	Slip
Ball Valve Product Group	Manual
Valve Basic Body Material	Brass
Standards	UPC, IPC, cUPC, IAPMO

Plumbing > Pipe, Tubing and Fittings > Tubing > Copper Pipe and Tubing >
5 ft. Hard Straight Copper Tubing, 1-1/8" Outside Dia., 1.000" Inside Dia. >


Print

Email

MUELLER INDUSTRIES

5 ft. Hard Straight Copper Tubing, 1-1/8" Outside Dia., 1.000" Inside Dia.

Item # 4WTR1 Mfr. Model # KH10005 Catalog Page # 2847 UNSPSC # 31231302



Web Price ⓘ
\$32.70 / each

One Time Delivery

1

Add to Cart

+ Add to List |

Shipping

Pickup

Expected to arrive **Thu. Oct 10.**

Ship To **43085** [\(Change\)](#)

☆☆☆☆☆ Be the first to write a review

Shipping Weight **4.05 lbs.**

Country of Origin **USA** | *Country of Origin is subject to change.*
Note: Product availability is real-time updated and adjusted continuously. The product will be reserved for you when you complete your order. [More](#)

How can we [improve our Product Images?](#)

☐ Compare

Technical Specs

Item	Copper Tubing	Copper Tube Type	Type K
Tube Material	Copper	Copper Tube Shape	Straight
Tube Size	1"	Soft/Hard	Hard
Inside Dia.	1.000"	Application	Water
Outside Dia.	1-1/8"	Copper Tube Coating	None
Wall Thickness	0.065"	Temp. Range	100 Degrees to 400 Degrees F
Max. Pressure	655 psi	Standards	ASTM B88, ASTM B306, ASTM B280, ASTM B819
Tube Length	5 ft.		



