

**CERTIFICATION OF WORK  
PREVENTIVE MAINTENANCE**

(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: NY127 Date of Visit: 3/23/22

Contractor Personnel on Site:

1. Patrick Brown 3. \_\_\_\_\_  
2. \_\_\_\_\_ 4. \_\_\_\_\_

**Work Performed:**

**Preventive Maintenance** - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)


1. WO#'S , 16321 , 16592 , 16610 , 16322 , 16580 , 16593 ,
2. 16611 ,
3. ASSET#'S , 190917- , 605-614 , 634 , 635 , 643 , 617 , 628 ,
4. 629 , 655 , 691 , 695 , 698 , 705 , 706 , 724 , 697 , 692 , 693 ,
5. 694 ,

---

**CERTIFICATION OF WORK**

To be signed by the Contractor:

Print Name: Patrick Brown Date: 3/23/22

Signed: 

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: LARS LUFFMAN Date: 3/23/22

Signed: 

E-Mail: \_\_\_\_\_

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
**GREASE TRAP**

SITE AND BLDG #: **NY127 BLDG1**LOCATION/RM #: **outside BLDG1**WO# **16592** ASSET # **190917-643**MECHANIC  
SIGNATURE: DATE: **3/23/22**START TIME: **8am**FINISH TIME: **8:30am**

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
<b>SPECIAL INSTRUCTIONS</b>				
1	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
2	Insure proper grease disposal.-Tanks are pumped by local septic companies	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>				
1	Remove lid. If the trap is equipped with removable baffles, remove them.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
2	Make sure the flow restrictor on the inflow pipe is present.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	flow restrictor is present
3	If damages, missing parts, or cleaning is required, report them as needed to ensure proper working operation.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	no damaged or missing parts
4	Replace lid and baffles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	baffles and lids have been reinstalled
5	Record grease trap maintenance activities on your log or request a receipt from your grease hauler. Keep records for 3 years. -In Maximo under WO#	<input checked="" type="checkbox"/>	<input type="checkbox"/>	no grease hauler used

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Technician

Additional Notes: