

### CERTIFICATION OF WORK

(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: Rockville MDO21 Date of Visit: 6/21/19

Contractor Personnel on Site:

1. Patrick Donovan
2. \_\_\_\_\_

#### Work Performed:

**Preventive Maintenance** - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)

1. 8860, 8893, 8938, 8952, 8894, 8939, 8895

**Service Calls** – Service Call Number and Description

1. CSS# \_\_\_\_\_
2. CSS# \_\_\_\_\_
3. CSS# \_\_\_\_\_

### CERTIFICATION OF WORK

To be signed by the Contractor:

Print Name: Patrick Donovan Date: 6/21/19

Signed: [Signature]

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: James F. (Sign) SFC-E7 Date: 21 Jun 19

Signed: [Signature]

E-Mail: \_\_\_\_\_

# PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST EXHAUST FANS

SITE AND BLDG #: Rockville HPD21

MECHANIC SIGNATURE: [Signature]

DATE: 6/29/15

LOCATION/RM #: Thompson Bldg 1 WO# 8853 ASSET # Scot

START TIME: 1000

FINISH TIME: 2:30

CHECK POINT	CHECK POINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS
		YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
2	Schedule shutdown with operating personnel, as needed.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	Clean unit, especially fan blades.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	done
2	Inspect pulleys, belts, couplings, etc.; adjust tension and tighten mountings as necessary. Change badly worn belts. Multiple belts should be replaced with matched sets.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	good done
3	Perform required lubrication and remove old or excess lubricant.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	done
4	Clean motor with vacuum or low pressure dry air (less than 40 psig). Check for obstructions in motor cooling and air flow.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	done
5	Check structural members, vibration eliminators, and flexible connections. Check fan housing to ensure there is no damage and the housing is tight.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	all good done
6	Start unit and check for vibration and noise.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	done
7	Remove all trash and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	done

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes:

Asset # 1264 ✓

# 1266 ✓

# 1265 ✓

# 1267 ✓