PREVENTIVE MAINTENANCE CERTIFICATION OF WORK
(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: Rockville /MD021 Date of Visit: 8/29/18

Contractor Personnel on Site:

1. Damyan & G Hollian
2. Patrick Donovan
3.
4.
5.
6.

Work Performed:

Preventive Maintenance - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)

7. LIST WO# Chg Batty
8. Chg Combo on vault
9. Test motion
10. Test Vault door
11. Chek comunication

CERTIFICATION OF WORK

10 need to get key for hold up Button

To be signed by the Contractor:

Print Name: Damyan GHollian Date: 8/29/18

Signed:

To be signed by Facility Manager or Government Official

I certify that the above named individuals representing the Contractor arrived on site and to the best of my knowledge, completed the stated work listed:

Print Name/Rank: RIOS OSCAR GS9 Date: 20180829

Signed:

E-Mail: OSCAR.G.RIOS3.CIV@mail.mil

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
VAULT DOOR

SITE AND BLDG #: Rockville MD021

LOCATION/RM #: Rm 114 **WO#** PM-AM-127 **ASSET #** 127

MECHANIC SIGNATURE: [signature] **DATE:** 8/29/16

START TIME: 10:00 **FINISH TIME:** 11:00

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE YES	TASK COMPLETE NO	NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
	SPECIAL INSTRUCTIONS			
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.	✓		
2	Review manufacturer's instructions.	✓		
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	✓		
	TO BE PERFORMED AT EACH INSPECTION SERVICE			
1	Check alignment of dial ring with lock case; correct if necessary.	✓		
2	Check mounting screws of dial ring and lock case; tighten them, using a thread locking compound.	✓		
3	Look for corrosion or presence of any foreign matter that will in any manner affect the lock's proper operation.	✓		Changed Combinations
4	Look for any signs of malfunctioning or impending failure.	✓		
5	Look for any signs of tampering, forced, or covert entry; report this to the local Security and Law Enforcement Office.	✓		
6	Check Alignment of door with frame	✓		
7	Check for difficulty in opening, closing or locking the door.	✓		
8	Replace all defective hardware	✓		

Note: The technician shall perform any repairs identified during PM up to $250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding $250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed discription of the deficiency.

1. A qualified locksmith with expertise in GSA locks is required.
2. Prior Coordination with the facility must occur prior to scheduled work. (See suggested coordination questions below)

a. Access to Arms room is accompanied. Someone with unaccompanied access MUST be present at all times during scheduled work.
b. Coordination AND approval from the Facility Coordinator or Physical Security Officer or PIN Custodian for combination change.

Additional Notes:

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST
SECURITY SYSTEM (ARMS ROOM ONLY)

SITE AND BLDG #: Rockville MD021

LOCATION/RM #: Rm114/Vault **WO#** PM-AM-1270A **ASSET #** 1273

MECHANIC SIGNATURE:

DATE: 8/29/16

START TIME: 10:00

FINISH TIME: 11:00

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE YES	TASK COMPLETE NO	NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
	SPECIAL INSTRUCTIONS			
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.	✓		
2	Review manufacturer's instructions. SEE End User Handbook (Separate Attachment) for all DSC Panels	✓		
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	✓		Need holdup button key or replaced
	TO BE PERFORMED AT EACH INSPECTION SERVICE			
1	Test the control panels for communications to the monitoring center, sirens, tampers, cameras, and strobe lights. (SEE End User Handbook for testing procedures). Replace any faulty sensor, verify with Central Monitoring Station that it is fully functional.	✓		Changed Batteries
2	Inspect and test the operation of all detection devices	✓		Called out System + Checked
3	Check power supplies	✓		
4	Verify that no compromise to devices has occurred (compromise of devices could be from building alterations, partitions, furniture or other obstacles)	✓		Tested System - Checked Communications
5	Load test batteries and if needed recommend for replacement.	✓		

Note: The technician shall perform any repairs identified during PM up to $250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding $250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed discription of the deficiency.

1. A qualified alarm technician is a requirement. A minimum of 5 years experience with Intrusion Detection Systems is required.
2. Prior Coordination with the facility must occur prior to scheduled work. (See suggested coordination questions below)

a. Access to Arms room is accompanied. Someone with unaccompanied access MUST be present at all times during scheduled work.
b. All cages with motion sensors should be open. Multiple unit coordination may be necessary.
c. In the event that all sensors could not be tested due to accessability every attempt will be made to test the sensor and if unsucessful must be noted.
d. Ensure facility has access to Maintenance Key.

Additional Notes: