ATTACHMENT J-0200000-05
FORMS

CERTIFICATION OF WORK
(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID: _____

Building: Canton NY

Contractor Personnel on Site:

1. Keith Pearson
2. Scott Segit

Date of Visit: 7-16-20

CSS: 20293 EST- 1526

~~CMMS~~: WO-7689

Service Order: ☑

Corrective Maintenance: ☐

Service Order Work Performed:

Unit: Gate operator

Manufacturer: Viking

Model: L-3

Serial: 0516-L3UL-1146

Description: ~~Req~~ Diagnose Gate and Keypad not Working

Found missing fuse for motor. Spoke w TECH Support motor most likely Bad

Repairs: Need to order parts & return to install, Further Troubleshooting may be necessary

To be signed by the Contractor:

Print Name: Keith Pearson Date: 7-16-20

Signed: _____

To be signed by Facility Manager:

I certify that the above named individuals representing the Contractor arrived on site and to the best of my knowledge, completed the stated work listed:

Print Name/Rank: Michael McCarthy GS-09 Date: 16 July 2020

Signed: _____

E-Mail: Michael.c.mccarthy46.civ.mil


Open
Center
Re-Open
VIKING
MAINTENANCE
RECORD


BATTERY
POWER
RESET
OFF


Center

BATTERY
POWER
OFF
MANUAL
RELEASE


VIKING
MAINTENANCE-FREE SEALED LEAD ACID BATTERY
MODEL NUMBER:
DUBA12
12Vdc
Pb
MANUAL RELEASE
ALARM
RELEASE
ENGAGE
RESET
AC VOLTAGE INPUT
PROTECTION WORKING
AC VOLTAGE OUTPUT
Voltage Selector
AC Power
4 Amp Fuse
120VAC 3A Max
DANGER!!
HIGH VOLTAGE


+ DC -
Open Right
Open Left
EPS1
EPS2
EMI
N.C
COM
N.O
Magnetic Lock Relay
Check Motor
Battery Low
POWER
+28V
GND
+28V
Radio
GND
+28V
GND
UL
GND
Re-Open
ATG
C. Loop
GND
Exit
GND
Strike
GND
Fire
GND
Open
Stop
Close
GND
MS1
MS2
Class 2 Supply +28V
Fail Safe/Secure
Open Limit
Close Limit
Timer
ODS
Overlap
Speed
OFF
60
Min.
Max.
NORM
Radio
UL
Re-Open
ATG
C. Loop
Open
Stop
Close
Auto Open
Last Open
Pre-Warning
SYNC
EXT
Diagnose
Aux. Pwr
Siren
V.K
V.M
V.Exp
AUX


VIKING



VIKING
ACCESS SYSTEMS™

Vehicular Gate Operator
Model L-3

Class I
Class II
Class III
Class IV

SN# *0516-L3UL-1146*

Date: 5/18/20

Volts (VAC)	Freq (Hz)	Amps	Phase	Max Gate Weight (lbs)	Max Gate Length (ft)
120	50-60	6.00 *	1	1,600 1,200 (1)	60 40
240	50-60	1.5	1	1,600 1,200 (1)	60 40 (1)

* Includes 3 amp load on receptacle

(1) ETL rated

Max Duty Cycle	Max Speed
100 %	12 in/sec

c UL us LISTED 18TC

ETL US Intertek 4007950

Conforms to UL Std 325

Certified to CSA Std C22.22 No. 247


MAINTENANCE RECORD
15 Amps
4 Amps
VIKING