




Air Conditioning & Heating

GSZ16

COOLING CAPACITY: 18,000 TO 60,000 BTU/H

HEATING CAPACITY: 18,000 TO 60,000 BTU/H

**HIGH-EFFICIENCY
SPLIT SYSTEM HEAT PUMP
UP TO 16 SEER & 9.0 HSPF
1½ TO 5 TONS**



Contents

Nomenclature.....	2
Product Specifications.....	3
Expanded Cooling Data	4
Expanded Heating Data.....	18
Performance Data	20
AHRI Ratings	21
Dimensions	33
Wiring Diagrams	34
Accessories	36

Standard Features

- High-efficiency scroll compressor
- SmartShift® technology to ensure quiet reliable defrost
- Single-speed ECM condenser fan motor
- Factory-installed bi-flow liquid-line filter drier
- Factory-installed suction-line accumulator
- Factory-installed compressor crankcase heater
- Factory-installed high-capacity muffler
- High- and low-pressure switches
- Service valves with sweat connections and easy access to gauge ports
- Copper tube/enhanced aluminum fin coil
- Fully charged for 15' of tubing length
- Contactor with lug connection
- Ground lug connection
- AHRI Certified; ETL Listed

Cabinet Features

- Goodman® brand sound control top design
- Steel louver coil guard
- Heavy-gauge galvanized-steel cabinet
- Attractive Architectural Gray powder-paint finish with 500-hour salt-spray approval
- Top and side maintenance access
- Service ports and controls are accessible while unit is operating
- When properly anchored, meets the 2010 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)



Proper sizing and installation of equipment is critical to achieving optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your contractor for details or visit www.energystar.gov.



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
■ ISO 9001 ■

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV GL
■ ISO 14001 ■



* Complete warranty details available from your local dealer or at www.goodmanmfg.com. To receive the 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec.

		G	S	Z	16	036	1	AA		
		1	2	3	4,5	6,7,8	9	10,11		
Brand		G Goodman® Brand						Engineering *		
										Major & Minor revisions * Not used for inventory control.
Product Category		S Split System						Electrical		
										1 - 208/230 V, 1 Phase, 60 Hz
Unit Type		X Condenser R-410A Z Heat Pump R-410A						Nominal Capacity		
										018 - 1½ tons 042 3½ Tons 024 - 2 tons 048 4 Tons 030 - 2½ tons 060 5 Tons 036 - 3 tons
Efficiency		13 13 SEER 16 16 SEER 14 14 SEER 18 18 SEER								

	GSZ16 0181B*	GSZ16 0241B*	GSZ16 0301B*	GSZ16 0361B*	GSZ16 0421B*	GSZ16 0481B*	GSZ16 0601B*
NOMINAL CAPACITIES							
Cooling (BTU/h)	18,000	24,000	30,000	36,000	42,000	48,000	60,000
Heating (BTU/h)	18,000	24,000	30,000	36,000	42,000	48,000	60,000
Decibels	72	75	75	73	73	74	76
COMPRESSOR							
RLA	9.0	10.9	13.4	14.1	16.7	19.9	28.8
LRA	47.5	62.9	72.5	72.2	109.0	109.0	152.9
Type	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll
CONDENSER FAN MOTOR							
Horsepower	1/6	1/6	1/6	1/4	1/4	1/4	1/6
FLA	0.95	1.1	1.1	1.30	1.2	1.30	1
REFRIGERATION SYSTEM							
Refrigerant Line Size ¹							
Liquid Line Size ("O.D.)	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Suction Line Size ("O.D.)	3/4"	3/4"	3/4"	7/8"	1 1/8"	1 1/8"	1 1/8"
Refrigerant Connection Size							
Liquid Valve Size ("O.D.)	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Suction Valve Size ("O.D.)	3/4"	3/4"	7/8"	7/8"	7/8"	7/8"	7/8"
Valve Connection Type	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat
Refrigerant Charge (oz.)	140	150	160	175	180	231	291
ELECTRICAL DATA							
Volts/Phase (60 Hz)	208/230	208/230	208/230	208/230	208/230	208/230	208/230
Minimum Circuit Ampacity ²	12.2	14.7	18.0	18.9	22.1	26.2	37
Max. Overcurrent Protection ³	20	25	30	30	35	45	60
Min / Max Volts	197/253	197/253	197/253	197/253	197/253	197/253	197/253
Electrical Conduit Size	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"
UNIT WEIGHTS							
Equipment Weight	174	180	186	220	226	250	306
Shipping Weight	189	200	206	240	237	270	326
ENERGY STAR® CERTIFIED ^							
							NO

^ Energy Star Notes

Proper sizing and installation of equipment is critical to achieving optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your contractor for details or visit www.energystar.gov.

The www.energystar.gov website provides up-to-date system combinations certified to meet ENERGY STAR requirements. See Page 21 for all ENERGY STAR certified combinations as of this document's revision date.

¹ Tested and rated in accordance with AHRI Standard 210/240

² Wire size should be determined in accordance with National Electrical Codes; extensive wire runs will require larger wire sizes

³ Must use time-delay fuses or HACR-type circuit breakers of the same size as noted.

NOTES

- Always check the S&R plate for electrical data on the unit being installed.
- Installer will need to supply 3/8" to 1 1/8" adapters for suction line connections.
- Unit is charged with refrigerant for 15' of 3/8" liquid line. System charge must be adjusted per Installation Instructions Final Charge Procedure.
- Installation of these units requires the specified TXV Kit to be installed on the indoor coil.
THE SPECIFIED TXV IS DETERMINED BY THE OUTDOOR UNIT NOT THE INDOOR COIL.

		OUTDOOR AMBIENT TEMPERATURE																								
		65°F				75°F				85°F				95°F				105°F				115°F				
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	
70	525	MBh	18.3	18.6	19.1	-	18.1	18.4	19.0	-	17.7	17.9	18.5	-	16.8	17.1	17.7	-	15.8	16.1	16.6	-	14.9	15.2	15.7	-
		S/T	0.62	0.54	0.41	-	0.63	0.55	0.41	-	0.65	0.58	0.44	-	1.00	0.60	0.46	-	1.00	0.62	0.48	-	1.00	0.67	0.53	-
		Δ T	20	18	14	-	20	18	14	-	20	18	15	-	20	18	14	-	19	18	14	-	21	19	15	-
		kW	0.99	0.99	0.99	-	1.11	1.11	1.11	-	1.25	1.25	1.24	-	1.39	1.39	1.39	-	1.56	1.55	1.55	-	1.75	1.74	1.74	-
		Amps	4.2	4.2	4.2	-	4.7	4.7	4.7	-	5.4	5.4	5.3	-	6.0	6.0	6.0	-	6.8	6.8	6.8	-	7.6	7.6	7.6	-
		HI PR	233	234	236	-	270	271	272	-	308	309	311	-	350	351	352	-	394	395	397	-	442	443	445	-
		LO PR	127	129	132	-	135	137	140	-	142	143	147	-	148	149	152	-	153	155	158	-	160	162	165	-
70	600	MBh	18.6	18.8	19.4	-	18.4	18.6	19.2	-	17.9	18.2	18.7	-	17.1	17.3	17.9	-	16.1	16.3	16.9	-	15.2	15.4	16.0	-
		S/T	0.68	0.61	0.47	-	0.69	0.61	0.47	-	1.00	0.64	0.50	-	1.00	0.66	0.52	-	1.00	0.68	0.54	-	1.00	1.00	0.59	-
		Δ T	19	17	13	-	19	17	13	-	19	17	14	-	19	17	13	-	18	16	13	-	19	18	14	-
		kW	1.00	1.00	1.00	-	1.12	1.12	1.12	-	1.25	1.25	1.25	-	1.40	1.40	1.40	-	1.56	1.56	1.56	-	1.75	1.75	1.75	-
		Amps	4.2	4.2	4.2	-	4.8	4.8	4.8	-	5.4	5.4	5.4	-	6.1	6.0	6.0	-	6.8	6.8	6.8	-	7.7	7.7	7.7	-
		HI PR	235	236	238	-	272	273	274	-	310	311	313	-	352	353	354	-	396	397	399	-	444	445	447	-
		LO PR	129	131	134	-	137	138	142	-	144	145	148	-	149	151	154	-	155	157	160	-	162	164	167	-
70	675	MBh	18.8	19.1	19.6	-	18.7	18.9	19.5	-	18.2	18.5	19.0	-	17.4	17.6	18.2	-	16.4	16.6	17.2	-	15.5	15.7	16.3	-
		S/T	0.72	0.64	0.50	-	0.73	0.65	0.51	-	1.00	0.67	0.53	-	1.00	0.69	0.55	-	1.00	0.72	0.58	-	1.00	1.00	0.63	-
		Δ T	18	16	12	-	18	16	12	-	18	16	13	-	18	16	12	-	17	16	12	-	19	17	13	-
		kW	1.00	1.00	1.00	-	1.12	1.12	1.12	-	1.26	1.26	1.26	-	1.40	1.40	1.40	-	1.57	1.57	1.56	-	1.76	1.76	1.75	-
		Amps	4.2	4.2	4.2	-	4.8	4.8	4.8	-	5.4	5.4	5.4	-	6.1	6.1	6.1	-	6.8	6.8	6.8	-	7.7	7.7	7.7	-
		HI PR	237	238	240	-	274	275	276	-	312	313	315	-	354	355	356	-	398	399	401	-	446	447	449	-
		LO PR	131	133	136	-	139	141	144	-	146	147	151	-	151	153	156	-	157	159	162	-	164	166	169	-
75	525	MBh	18.3	18.6	19.1	20.0	18.2	18.4	19.0	19.8	17.7	17.9	18.5	19.3	16.9	17.1	17.7	18.5	15.9	16.1	16.7	17.5	14.9	15.2	15.7	16.6
		S/T	0.76	0.68	0.54	0.39	1.00	0.68	0.54	0.40	1.00	0.71	0.57	0.42	1.00	0.73	0.59	0.44	1.00	1.00	0.61	0.47	1.00	1.00	0.67	0.52
		Δ T	24	22	18	15	24	22	18	15	24	22	19	15	24	22	18	15	23	22	18	15	25	23	19	16
		kW	0.99	0.99	0.99	1.00	1.11	1.11	1.11	1.12	1.25	1.25	1.24	1.25	1.39	1.39	1.39	1.40	1.55	1.55	1.55	1.56	1.75	1.74	1.74	1.75
		Amps	4.2	4.2	4.2	4.2	4.7	4.7	4.7	4.8	5.4	5.4	5.3	5.4	6.0	6.0	6.0	6.0	6.8	6.8	6.8	6.8	7.6	7.6	7.6	7.7
		HI PR	233	234	236	240	270	271	273	277	308	309	311	315	350	351	353	357	395	396	397	401	442	443	445	449
		LO PR	127	129	132	138	135	137	140	145	142	143	147	152	148	149	152	158	153	155	158	163	160	162	165	170
75	600	MBh	18.6	18.8	19.4	20.2	18.4	18.7	19.2	20.0	17.9	18.2	18.7	19.6	17.1	17.4	17.9	18.7	16.1	16.4	16.9	17.7	15.2	15.4	16.0	16.8
		S/T	0.82	0.74	0.60	0.45	1.00	0.74	0.61	0.46	1.00	0.77	0.63	0.48	1.00	0.79	0.65	0.50	1.00	1.00	0.67	0.53	1.00	1.00	0.73	0.58
		Δ T	23	21	17	14	23	21	17	14	23	21	18	14	23	21	17	14	22	20	17	14	23	22	18	15
		kW	1.00	1.00	0.99	1.00	1.12	1.12	1.11	1.12	1.25	1.25	1.25	1.26	1.40	1.40	1.39	1.40	1.56	1.56	1.56	1.57	1.75	1.75	1.75	1.76
		Amps	4.2	4.2	4.2	4.2	4.8	4.8	4.8	4.8	5.4	5.4	5.4	5.4	6.0	6.0	6.0	6.1	6.8	6.8	6.8	6.8	7.7	7.7	7.7	7.7
		HI PR	235	236	238	242	272	273	275	279	310	311	313	317	352	353	355	359	397	398	399	403	444	445	447	451
		LO PR	129	131	134	139	137	138	142	147	144	145	149	154	149	151	154	160	155	157	160	165	162	164	167	172
75	675	MBh	18.9	19.1	19.7	20.5	18.7	18.9	19.5	20.3	18.2	18.5	19.0	19.9	17.4	17.6	18.2	19.0	16.4	16.6	17.2	18.0	15.5	15.7	16.3	17.1
		S/T	0.85	0.77	0.63	0.49	1.00	0.78	0.64	0.49	1.00	0.81	0.67	0.52	1.00	0.83	0.69	0.54	1.00	1.00	0.71	0.56	1.00	1.00	0.76	0.61
		Δ T	22	20	16	13	22	20	16	13	22	20	17	13	22	20	16	13	21	20	16	13	23	21	17	14
		kW	1.00	1.00	1.00	1.01	1.12	1.12	1.12	1.13	1.26	1.26	1.25	1.26	1.40	1.40	1.40	1.41	1.57	1.56	1.56	1.57	1.76	1.76	1.75	1.76
		Amps	4.2	4.2	4.2	4.3	4.8	4.8	4.8	4.8	5.4	5.4	5.4	5.4	6.1	6.1	6.1	6.1	6.8	6.8	6.8	6.8	7.7	7.7	7.7	7.7
		HI PR	237	238	240	244	274	275	277	281	312	313	315	319	354	355	356	361	399	400	401	405	446	447	449	453
		LO PR	131	133	136	141	139	141	144	149	146	147	151	156	151	153	156	162	157	159	162	167	164	166	169	174

DB: Entering Indoor Dry Bulb Temperature
High and low pressures are measured at the liquid and suction service valves.
Shaded area reflects ACCA (TVA) Rating Conditions.
kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) Rating Conditions.

kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

		OUTDOOR AMBIENT TEMPERATURE																																			
		65°F						75°F						85°F						95°F						105°F						115°F					
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71								
80	MBh	18.4	18.7	19.2	20.1	18.3	18.5	19.1	19.9	17.8	18.0	18.6	19.4	17.0	17.2	17.8	18.6	15.9	16.2	16.8	17.6	15.0	15.3	15.8	16.7	15.0	15.3	15.8	16.7								
	S/T	1.00	0.81	0.67	0.52	1.00	0.81	0.67	0.53	1.00	0.84	0.70	0.55	1.00	1.00	0.72	0.57	1.00	1.00	0.74	0.59	1.00	1.00	0.79	0.65	1.00	1.00	0.79	0.65								
	Δ T	28	26	23	19	28	26	22	19	28	26	23	19	28	26	22	19	27	26	22	19	29	27	23	20	29	27	23	20								
	kW	0.99	0.99	0.99	1.00	1.11	1.11	1.11	1.12	1.25	1.25	1.24	1.25	1.39	1.39	1.39	1.40	1.55	1.55	1.55	1.56	1.75	1.74	1.74	1.75	1.75	1.74	1.74	1.75								
	Amps	4.2	4.2	4.2	4.2	4.7	4.7	4.7	4.8	5.4	5.4	5.3	5.4	6.0	6.0	6.0	6.1	6.8	6.8	6.8	6.8	7.6	7.6	7.6	7.7	7.6	7.6	7.7	7.7								
	Hi PR	234	235	236	240	270	271	273	277	309	310	312	316	350	351	353	357	395	396	398	402	443	444	444	445	440	443	444	445	450							
	Lo PR	128	129	133	138	136	137	140	146	142	144	147	153	148	150	153	158	154	155	159	164	161	162	166	161	162	166	171	171								
	MBh	18.7	18.9	19.5	20.3	18.5	18.8	19.3	20.1	18.0	18.3	18.8	19.7	17.2	17.5	18.0	18.8	16.2	16.4	17.0	17.8	15.3	15.5	16.1	16.9	15.3	15.5	16.1	16.9	16.9							
	S/T	1.00	0.87	0.73	0.58	1.00	0.87	0.73	0.59	1.00	1.00	0.76	0.61	1.00	1.00	0.78	0.63	1.00	1.00	0.80	0.66	1.00	1.00	1.00	0.71	1.00	1.00	1.00	0.71	0.71							
	Δ T	27	25	21	18	27	25	21	18	27	25	22	18	27	25	21	18	26	25	21	18	27	26	22	19	27	26	22	19	19							
85	kW	1.00	1.00	0.99	1.00	1.12	1.12	1.12	1.13	1.26	1.26	1.26	1.26	1.40	1.40	1.40	1.41	1.57	1.57	1.56	1.57	1.76	1.75	1.75	1.76	1.76	1.75	1.75	1.76	1.76							
	Amps	4.2	4.2	4.2	4.2	4.8	4.8	4.8	4.8	5.4	5.4	5.4	5.4	6.1	6.1	6.1	6.1	6.8	6.8	6.8	6.8	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7							
	Hi PR	236	237	238	242	272	273	275	279	311	312	314	318	352	353	355	359	397	398	400	404	445	446	447	451	445	448	449	450	453							
	Lo PR	130	131	135	140	137	139	142	148	144	146	149	154	150	152	155	160	156	157	160	166	163	164	167	173	165	166	170	175	175							
	MBh	18.9	19.2	19.8	20.6	18.8	19.0	19.6	20.4	18.3	18.6	19.1	19.9	17.5	17.7	18.3	19.1	16.5	16.7	17.3	18.1	15.6	15.8	16.4	17.2	15.6	15.8	16.4	17.2	17.2							
	S/T	1.00	0.90	0.76	0.62	1.00	0.91	0.77	0.62	1.00	1.00	0.80	0.65	1.00	1.00	0.82	0.67	1.00	1.00	0.84	0.69	1.00	1.00	1.00	0.74	1.00	1.00	1.00	0.74	0.74							
	Δ T	26	24	21	17	26	24	20	17	26	24	21	17	26	24	20	17	25	24	20	17	27	25	21	18	27	25	21	18	18							
	kW	1.00	1.00	1.00	1.01	1.12	1.12	1.12	1.13	1.26	1.26	1.26	1.26	1.40	1.40	1.40	1.41	1.57	1.57	1.56	1.57	1.76	1.76	1.75	1.76	1.76	1.75	1.75	1.76	1.76							
	Amps	4.2	4.2	4.2	4.3	4.8	4.8	4.8	4.8	5.4	5.4	5.4	5.4	6.1	6.1	6.1	6.1	6.8	6.8	6.8	6.8	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7							
	Hi PR	238	239	240	244	274	275	277	281	313	314	315	320	354	355	357	361	399	400	402	406	447	448	449	453	447	448	449	450	455	455						
Lo PR	132	133	137	142	140	141	144	150	146	148	151	157	152	154	157	162	158	159	162	168	165	166	170	175	165	166	170	175	175								

DB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects AHRI Rating Conditions.

kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

IDB: Entering Indoor Dry Bulb Temperature
 High and low pressures are measured at the liquid and suction service valves.
 Shaded area reflects AHRI Rating Conditions.
 kW = Total system power
 Amps = Outdoor unit amps (compressor + fan)

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																																															
				65°F								75°F								85°F								95°F								105°F								115°F							
				ENTERING INDOOR WET BULB TEMPERATURE																																															
		59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71																		
700	MBh	24.4	24.8	25.5	-	24.2	24.5	25.3	-	23.6	23.9	24.6	-	22.5	22.8	23.5	-	21.1	21.5	22.2	-	19.9	20.2	21.0	-	19.9	20.2	21.0	-	19.9	20.2	21.0	-																		
	S/T	0.62	0.54	0.40	-	0.62	0.55	0.41	-	0.65	0.57	0.43	-	1.00	0.59	0.45	-	1.00	0.62	0.48	-	1.00	0.67	0.53	-	1.00	0.67	0.53	-	1.00	0.67	0.53	-																		
	Δ T	20	18	15	-	20	18	14	-	20	18	15	-	20	18	14	-	19	18	14	-	21	19	15	-	21	19	15	-	21	19	15	-																		
	kW	1.33	1.32	1.32	-	1.49	1.48	1.48	-	1.66	1.66	1.66	-	1.86	1.86	1.85	-	2.07	2.07	2.07	-	2.32	2.32	2.32	-	2.32	2.32	2.32	-	2.32	2.32	2.32	-																		
	Amps	5.5	5.5	5.5	-	6.2	6.2	6.2	-	7.0	7.0	7.0	-	7.9	7.9	7.9	-	8.9	8.9	8.9	-	10.1	10.1	10.1	-	10.1	10.1	10.1	-	10.1	10.1	10.1	-																		
800	HI PR	241	242	243	-	279	280	281	-	318	319	321	-	361	362	364	-	407	408	410	-	457	458	459	-	457	458	459	-	457	458	459	-																		
	LO PR	126	127	131	-	133	135	138	-	140	142	145	-	146	147	151	-	151	153	156	-	158	160	163	-	158	160	163	-	158	160	163	-																		
	MBh	24.7	25.1	25.8	-	24.5	24.9	25.6	-	23.9	24.2	25.0	-	22.8	23.1	23.9	-	21.4	21.8	22.5	-	20.2	20.6	21.3	-	20.2	20.6	21.3	-	20.2	20.6	21.3	-																		
	S/T	0.68	0.60	0.46	-	0.69	0.61	0.47	-	0.71	0.63	0.50	-	1.00	0.65	0.52	-	1.00	0.68	0.54	-	1.00	0.73	0.59	-	1.00	0.73	0.59	-	1.00	0.73	0.59	-																		
	Δ T	19	17	13	-	19	17	13	-	19	17	14	-	19	17	13	-	18	17	13	-	19	18	14	-	19	18	14	-	19	18	14	-																		
900	kW	1.33	1.33	1.33	-	1.49	1.49	1.49	-	1.67	1.67	1.67	-	1.86	1.86	1.86	-	2.08	2.08	2.08	-	2.33	2.33	2.33	-	2.33	2.33	2.33	-	2.33	2.33	2.33	-																		
	Amps	5.5	5.5	5.5	-	6.3	6.2	6.2	-	7.1	7.1	7.1	-	8.0	7.9	7.9	-	8.9	8.9	8.9	-	10.1	10.1	10.1	-	10.1	10.1	10.1	-	10.1	10.1	10.1	-																		
	HI PR	243	244	245	-	281	282	283	-	320	321	323	-	363	364	366	-	409	411	412	-	459	460	462	-	459	460	462	-	459	460	462	-																		
	LO PR	128	129	132	-	135	137	140	-	142	144	147	-	148	149	152	-	153	155	158	-	160	162	165	-	160	162	165	-	160	162	165	-																		
	MBh	25.1	25.5	26.2	-	24.9	25.2	26.0	-	24.3	24.6	25.3	-	23.2	23.5	24.2	-	21.8	22.2	22.9	-	20.6	21.0	21.7	-	20.6	21.0	21.7	-	20.6	21.0	21.7	-																		
700	S/T	0.71	0.64	0.50	-	0.72	0.64	0.50	-	1.00	0.67	0.53	-	1.00	0.69	0.55	-	1.00	0.71	0.57	-	1.00	1.00	0.63	-	1.00	1.00	0.63	-	1.00	1.00	0.63	-																		
	Δ T	18	16	12	-	18	16	12	-	18	16	13	-	18	16	12	-	17	16	12	-	19	17	13	-	19	17	13	-	19	17	13	-																		
	kW	1.34	1.34	1.34	-	1.50	1.50	1.50	-	1.68	1.68	1.67	-	1.87	1.87	1.87	-	2.09	2.09	2.08	-	2.34	2.34	2.34	-	2.34	2.34	2.34	-	2.34	2.34	2.34	-																		
	Amps	5.6	5.6	5.5	-	6.3	6.3	6.3	-	7.1	7.1	7.1	-	8.0	8.0	8.0	-	9.0	9.0	9.0	-	10.1	10.1	10.1	-	10.1	10.1	10.1	-	10.1	10.1	10.1	-																		
	HI PR	245	246	247	-	283	284	285	-	322	323	325	-	365	366	368	-	411	413	414	-	461	462	463	-	461	462	463	-	461	462	463	-																		
LO PR	LO PR	130	131	134	-	137	139	142	-	144	146	149	-	150	151	154	-	155	157	160	-	162	164	167	-	162	164	167	-	162	164	167	-																		

75	MBh	24.4	24.8	25.5	26.6	24.2	24.6	25.3	26.4	23.6	23.9	24.6	25.8	22.5	22.8	23.6	24.7	21.1	21.5	22.2	23.3	19.9	20.3	21.0	22.1
	S/T	0.75	0.67	0.53	0.39	1.00	0.68	0.54	0.39	1.00	0.70	0.57	0.42	1.00	0.72	0.59	0.44	1.00	0.75	0.61	0.46	1.00	1.00	0.66	0.52
	Δ T	24	22	19	15	24	22	18	15	24	22	19	15	24	22	18	15	23	22	18	15	25	23	19	16
	kW	1.32	1.32	1.32	1.33	1.48	1.48	1.48	1.49	1.66	1.66	1.66	1.67	1.86	1.85	1.85	1.86	2.07	2.07	2.07	2.08	2.32	2.32	2.32	2.33
	Amps	5.5	5.5	5.5	5.5	6.2	6.2	6.2	6.3	7.0	7.0	7.0	7.1	7.9	7.9	7.9	7.9	8.9	8.9	8.9	8.9	10.1	10.0	10.0	10.1
800	HI PR	241	242	244	248	279	280	282	286	319	320	321	326	361	363	364	368	408	409	410	415	457	458	460	464
	LO PR	126	127	131	136	133	135	138	144	140	142	145	150	146	147	151	156	151	153	156	161	158	160	163	168
	MBh	24.8	25.1	25.8	26.9	24.5	24.9	25.6	26.7	23.9	24.2	25.0	26.1	22.8	23.1	23.9	25.0	21.5	21.8	22.5	23.6	20.2	20.6	21.3	22.4
	S/T	0.81	0.73	0.60	0.45	1.00	0.74	0.60	0.46	1.00	0.77	0.63	0.48	1.00	0.79	0.65	0.50	1.00	1.00	0.67	0.52	1.00	1.00	0.72	0.58
	Δ T	23	21	17	14	23	21	17	14	23	21	18	14	23	21	17	14	22	21	17	14	23	22	18	15
900	kW	1.33	1.33	1.33	1.34	1.49	1.49	1.49	1.50	1.67	1.67	1.67	1.68	1.86	1.86	1.86	1.87	2.08	2.08	2.08	2.09	2.33	2.33	2.33	2.34
	Amps	5.5	5.5	5.5	5.6	6.3	6.2	6.2	6.3	7.1	7.1	7.0	7.1	7.9	7.9	7.9	8.0	8.9	8.9	8.9	9.0	10.1	10.1	10.1	10.1
	HI PR	243	244	246	250	281	282	284	288	321	322	323	328	364	365	366	370	410	411	412	417	459	460	462	466
	LO PR	128	129	132	138	135	137	140	145	142	144	147	152	148	149	152	158	153	155	158	163	160	162	165	170
	MBh	25.1	25.5	26.2	27.3	24.9	25.3	26.0	27.1	24.3	24.6	25.4	26.5	23.2	23.5	24.3	25.4	21.8	22.2	22.9	24.0	20.6	21.0	21.7	22.8
700	S/T	0.85	0.77	0.63	0.48	1.00	0.77	0.64	0.49	1.00	0.80	0.66	0.52	1.00	0.82	0.68	0.54	1.00	1.00	0.70	0.56	1.00	1.00	0.76	0.61
	Δ T	22	20	16	13	22	20	16	13	22	20	17	13	22	20	16	13	21	20	16	13	23	21	17	14
	kW	1.34	1.34	1.34	1.35	1.50	1.50	1.50	1.51	1.68	1.68	1.67	1.69	1.87	1.87	1.87	1.88	2.09	2.08	2.08	2.09	2.34	2.34	2.33	2.35
	Amps	5.6	5.5	5.5	5.6	6.3	6.3	6.3	6.3	7.1	7.1	7.1	7.1	8.0	8.0	8.0	8.0	9.0	9.0	8.9	9.0	10.1	10.1	10.1	10.2
	HI PR	245	246	248	252	283	284	286	290	323	324	325	330	365	367	368	372	412	413	414	419	461	462	464	468
900	LO PR	130	131	134	140	137	139	142	147	144	146	149	154	150	151	154	160	155	157	160	165	162	164	167	172

DB: Entering Indoor Dry Bulb Temperature

Shaded area reflects ACCA (TVA) Rating Conditions.

kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

		OUTDOOR AMBIENT TEMPERATURE																													
		75°F						85°F						95°F						105°F						115°F					
IDB	AIRFLOW	ENTERING INDOOR WET BULB TEMPERATURE																													
		59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71		
700	MBh	24.6	24.9	25.6	26.7	24.3	24.7	25.4	26.5	23.7	24.0	24.8	25.9	22.6	22.9	23.7	24.8	21.3	21.6	22.3	23.5	20.0	20.4	21.1	22.2						
	S/T	1.00	0.80	0.66	0.52	1.00	0.81	0.67	0.52	1.00	0.83	0.69	0.55	1.00	1.00	0.71	0.57	1.00	1.00	0.74	0.59	1.00	1.00	0.79	0.64						
	Δ T	28	26	23	19	28	26	23	19	28	26	23	19	28	26	22	19	27	26	22	19	29	27	23	20						
	kW	1.33	1.32	1.32	1.33	1.49	1.48	1.48	1.49	1.66	1.66	1.66	1.67	1.86	1.86	1.85	1.86	2.07	2.07	2.07	2.08	2.32	2.32	2.32	2.33						
	Amps	5.5	5.5	5.5	5.5	6.2	6.2	6.2	6.3	7.0	7.0	7.0	7.1	7.9	7.9	7.9	8.0	8.9	8.9	8.9	8.9	10.1	10.1	10.1	10.1						
	Hi PR	241	242	244	248	279	280	282	286	319	320	322	326	362	363	365	369	408	409	411	415	457	458	460	464						
	LO PR	126	128	131	136	134	136	139	144	141	142	145	151	146	148	151	156	152	153	157	162	159	160	164	169						
800	MBh	24.9	25.2	26.0	27.1	24.7	25.0	25.7	26.8	24.0	24.4	25.1	26.2	22.9	23.3	24.0	25.1	21.6	21.9	22.7	23.8	20.4	20.7	21.4	22.5						
	S/T	1.00	0.86	0.72	0.58	1.00	0.87	0.73	0.58	1.00	0.89	0.76	0.61	1.00	1.00	0.78	0.63	1.00	1.00	0.80	0.65	1.00	1.00	0.85	0.70						
	Δ T	27	25	21	18	27	25	21	18	27	25	22	18	27	25	21	18	26	25	21	18	28	26	22	19						
	kW	1.33	1.33	1.33	1.34	1.49	1.49	1.49	1.50	1.67	1.67	1.67	1.68	1.86	1.86	1.86	1.87	2.08	2.08	2.08	2.09	2.33	2.33	2.33	2.34						
	Amps	5.5	5.5	5.5	5.6	6.3	6.2	6.2	6.3	7.1	7.1	7.1	7.1	8.0	7.9	7.9	8.0	8.9	8.9	8.9	9.0	10.1	10.1	10.1	10.1						
	Hi PR	243	244	246	250	281	282	284	288	321	322	324	328	364	365	367	371	410	411	413	417	459	460	462	466						
	LO PR	128	130	133	138	136	137	141	146	143	144	147	153	148	150	153	158	154	155	159	164	161	162	165	171						
900	MBh	25.3	25.6	26.3	27.5	25.0	25.4	26.1	27.2	24.4	24.8	25.5	26.6	23.3	23.7	24.4	25.5	22.0	22.3	23.0	24.2	20.7	21.1	21.8	22.9						
	S/T	1.00	0.90	0.76	0.61	1.00	0.90	0.76	0.62	1.00	1.00	0.79	0.64	1.00	1.00	0.81	0.66	1.00	1.00	0.83	0.69	1.00	1.00	0.85	0.74						
	Δ T	26	24	21	17	26	24	20	17	26	24	21	17	26	24	20	17	25	24	20	17	27	25	21	18						
	kW	1.34	1.34	1.34	1.35	1.50	1.50	1.50	1.51	1.68	1.68	1.67	1.69	1.87	1.87	1.87	1.88	2.09	2.09	2.09	2.10	2.34	2.34	2.34	2.35						
	Amps	5.6	5.6	5.5	5.6	6.3	6.3	6.3	6.3	7.1	7.1	7.1	7.1	8.0	8.0	8.0	8.0	9.0	9.0	9.0	9.0	10.1	10.1	10.1	10.2						
	Hi PR	245	246	248	252	283	284	286	290	323	324	326	330	366	367	369	373	412	413	415	419	461	462	464	468						
	LO PR	130	132	135	140	138	139	143	148	145	146	149	155	150	152	155	160	156	157	161	166	163	164	168	173						

85	700	MBh	25.0	25.3	26.0	27.2	24.8	25.1	25.8	26.9	24.1	24.5	25.2	26.3	23.0	23.4	24.1	25.2	21.7	22.0	22.7	23.9	20.5	20.8	21.5	22.6
		S/T	1.00	0.90	0.77	0.62	1.00	1.00	0.77	0.63	1.00	1.00	0.80	0.65	1.00	1.00	0.82	0.67	1.00	1.00	1.00	0.69	1.00	1.00	1.00	0.75
		Δ T	31	30	26	23	31	30	26	23	32	30	26	23	31	29	26	23	31	29	26	22	32	30	27	23
		kW	1.33	1.33	1.32	1.34	1.49	1.49	1.48	1.50	1.67	1.67	1.66	1.67	1.86	1.86	1.86	1.87	2.07	2.07	2.07	2.08	2.33	2.33	2.32	2.34
		Amps	5.5	5.5	5.5	5.5	6.2	6.2	6.2	6.3	7.0	7.0	7.0	7.1	7.9	7.9	7.9	8.0	8.9	8.9	8.9	9.0	10.1	10.1	10.1	10.1
		HI PR	242	243	245	249	280	281	283	287	320	321	323	327	363	364	366	370	409	410	412	416	459	460	461	465
	LO PR	128	130	133	138	136	137	141	146	143	144	147	153	148	150	153	158	154	155	159	164	161	162	166	171	
	800	MBh	25.3	25.6	26.4	27.5	25.1	25.4	26.1	27.3	24.4	24.8	25.5	26.6	23.3	23.7	24.4	25.5	22.0	22.3	23.1	24.2	20.8	21.1	21.8	23.0
		S/T	1.00	0.97	0.83	0.68	1.00	1.00	0.83	0.69	1.00	1.00	0.86	0.71	1.00	1.00	0.88	0.73	1.00	1.00	1.00	0.76	1.00	1.00	1.00	0.81
		Δ T	30	28	25	22	30	28	25	21	30	29	25	22	1.87	1.87	1.86	1.88	2.08	2.08	2.08	2.09	2.34	2.33	2.33	2.34
		kW	1.34	1.34	1.33	1.35	1.50	1.50	1.49	1.50	1.67	1.67	1.67	1.68	1.87	1.87	1.87	1.88	2.08	2.08	2.08	2.09	2.34	2.33	2.33	2.34
		Amps	5.5	5.5	5.5	5.6	6.3	6.3	6.3	6.3	7.1	7.1	7.1	7.1	8.0	8.0	8.0	8.0	9.0	8.9	8.9	9.0	10.1	10.1	10.1	10.1
		HI PR	244	246	247	251	282	283	285	289	322	323	325	329	365	366	368	372	411	412	414	418	461	462	463	467
	LO PR	130	132	135	140	138	139	142	148	144	146	149	155	150	152	155	160	156	157	160	166	163	164	167	173	
	900	MBh	25.7	26.0	26.7	27.9	25.5	25.8	26.5	27.6	24.8	25.2	25.9	27.0	23.7	24.1	24.8	25.9	22.4	22.7	23.5	24.6	21.2	21.5	22.2	23.3
		S/T	1.00	1.00	0.86	0.72	1.00	1.00	0.87	0.72	1.00	1.00	0.89	0.75	1.00	1.00	0.91	0.77	1.00	1.00	1.00	0.79	1.00	1.00	1.00	0.84
		Δ T	29	28	24	21	29	27	24	21	30	28	24	21	21	29	27	24	21	29	27	24	20	30	28	25
		kW	1.34	1.34	1.34	1.35	1.50	1.50	1.50	1.51	1.68	1.68	1.68	1.69	1.87	1.87	1.87	1.88	2.09	2.09	2.09	2.10	2.34	2.34	2.34	2.35
Amps		5.6	5.6	5.6	5.6	6.3	6.3	6.3	6.3	7.1	7.1	7.1	7.2	8.0	8.0	8.0	8.0	9.0	9.0	9.0	9.0	10.1	10.1	10.1	10.2	
HI PR		246	248	249	253	284	285	287	291	324	325	327	331	367	368	370	374	413	414	416	420	463	464	465	469	
LO PR	132	134	137	142	140	141	145	150	146	148	151	157	152	154	157	162	158	159	162	168	165	166	169	175		

High and low pressures are measured at the liquid and suction service valves.

DB: Entering Indoor Dry Bulb Temperature

Shaded area reflects AHRI Rating Conditions.

Amps = Outdoor unit amps (compressor + fan)

kW = Total system power

		OUTDOOR AMBIENT TEMPERATURE																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
70	MBh	29.4	29.8	30.7	-	29.1	29.5	30.4	-	28.3	28.8	29.6	-	27.0	27.4	28.3	-	25.4	25.8	26.7	-	23.9	24.4	25.2	-
	S/T	0.63	0.56	0.42	-	0.64	0.56	0.42	-	0.67	0.59	0.45	-	1.00	0.61	0.47	-	1.00	0.63	0.49	-	1.00	0.68	0.54	-
	Δ T	20	18	15	-	20	18	15	-	20	18	15	-	20	18	15	-	20	18	14	-	21	19	15	-
	kW	1.57	1.57	1.56	-	1.77	1.77	1.76	-	1.99	1.99	1.98	-	2.23	2.23	2.23	-	2.50	2.50	2.49	-	2.81	2.81	2.81	-
	Amps	6.5	6.4	6.4	-	7.4	7.4	7.3	-	8.4	8.4	8.4	-	9.5	9.5	9.5	-	10.7	10.7	10.7	-	12.2	12.1	12.1	-
	HI PR	246	247	249	-	285	286	288	-	325	327	328	-	369	370	372	-	416	417	419	-	467	468	469	-
	LO PR	124	125	129	-	131	133	136	-	138	140	143	-	144	145	148	-	149	151	154	-	156	157	161	-
	MBh	29.7	30.1	31.0	-	29.4	29.8	30.7	-	28.7	29.1	29.9	-	27.3	27.8	28.6	-	25.7	26.1	27.0	-	24.3	24.7	25.6	-
	S/T	0.68	0.60	0.46	-	0.69	0.61	0.47	-	0.71	0.64	0.50	-	1.00	0.66	0.52	-	1.00	0.68	0.54	-	1.00	0.73	0.59	-
	Δ T	19	17	14	-	19	17	14	-	19	17	14	-	19	17	14	-	19	17	13	-	20	18	15	-
75	kW	1.58	1.58	1.57	-	1.78	1.77	1.77	-	2.00	2.00	1.99	-	2.24	2.24	2.23	-	2.51	2.51	2.50	-	2.82	2.82	2.82	-
	Amps	6.5	6.5	6.5	-	7.4	7.4	7.4	-	8.4	8.4	8.4	-	9.5	9.5	9.5	-	10.8	10.7	10.7	-	12.2	12.2	12.2	-
	HI PR	248	249	251	-	287	288	289	-	327	328	330	-	371	372	374	-	418	419	421	-	468	469	471	-
	LO PR	125	127	130	-	133	134	138	-	140	141	144	-	145	147	150	-	151	152	155	-	157	159	162	-
	MBh	30.3	30.7	31.6	-	30.0	30.4	31.3	-	29.2	29.7	30.5	-	27.9	28.3	29.2	-	26.3	26.7	27.6	-	24.8	25.3	26.1	-
	S/T	0.72	0.64	0.50	-	0.73	0.65	0.51	-	0.75	0.67	0.54	-	1.00	0.69	0.56	-	1.00	0.72	0.58	-	1.00	0.77	0.63	-
	Δ T	18	16	13	-	18	16	12	-	18	16	13	-	18	16	12	-	18	16	12	-	19	17	13	-
	kW	1.59	1.59	1.58	-	1.79	1.78	1.78	-	2.01	2.01	2.00	-	2.25	2.25	2.24	-	2.52	2.52	2.51	-	2.83	2.83	2.83	-
	Amps	6.5	6.5	6.5	-	7.5	7.4	7.4	-	8.5	8.5	8.4	-	9.6	9.6	9.5	-	10.8	10.8	10.8	-	12.2	12.2	12.2	-
	HI PR	250	251	253	-	289	290	292	-	330	331	332	-	373	374	376	-	421	422	423	-	471	472	474	-
	LO PR	128	129	133	-	135	137	140	-	142	144	147	-	148	149	152	-	153	155	158	-	160	161	165	-
75	MBh	29.4	29.8	30.7	32.0	29.1	29.5	30.4	31.7	28.4	28.8	29.6	31.0	27.0	27.5	28.3	29.7	25.4	25.8	26.7	28.1	24.0	24.4	25.2	26.6
	S/T	0.77	0.69	0.55	0.40	0.77	0.69	0.56	0.41	1.00	0.72	0.58	0.43	1.00	0.74	0.60	0.45	1.00	0.76	0.62	0.48	1.00	1.00	0.68	0.53
	Δ T	24	22	19	15	24	22	19	15	24	22	19	15	24	22	19	15	24	22	18	15	25	23	20	16
	kW	1.57	1.57	1.56	1.58	1.77	1.76	1.76	1.78	1.99	1.99	1.98	2.00	2.23	2.23	2.22	2.24	2.50	2.50	2.49	2.51	2.81	2.81	2.81	2.82
	Amps	6.4	6.4	6.4	6.5	7.4	7.4	7.3	7.4	8.4	8.4	8.4	8.4	9.5	9.5	9.5	9.5	10.7	10.7	10.7	10.8	12.2	12.1	12.1	12.2
	HI PR	246	247	249	253	285	286	288	292	326	327	328	333	369	370	372	376	417	418	419	424	467	468	470	474
	LO PR	124	125	129	134	131	133	136	141	138	140	143	148	144	145	148	154	149	151	154	159	156	157	161	166
	MBh	29.7	30.1	31.0	32.3	29.4	29.9	30.7	32.1	28.7	29.1	30.0	31.3	27.4	27.8	28.6	30.0	25.8	26.2	27.0	28.4	24.3	24.7	25.6	26.9
	S/T	0.81	0.74	0.60	0.45	0.82	0.74	0.60	0.46	1.00	0.77	0.63	0.48	1.00	0.79	0.65	0.50	1.00	0.81	0.67	0.53	1.00	1.00	0.72	0.58
	Δ T	23	21	18	14	23	21	18	14	23	21	18	14	23	21	18	14	23	21	17	14	24	22	19	15
75	kW	1.58	1.57	1.57	1.59	1.77	1.77	1.77	1.78	2.00	2.00	1.99	2.01	2.24	2.24	2.23	2.25	2.51	2.50	2.50	2.52	2.82	2.82	2.82	2.83
	Amps	6.5	6.5	6.5	6.5	7.4	7.4	7.4	7.4	8.4	8.4	8.4	8.5	9.5	9.5	9.5	9.6	10.7	10.7	10.7	10.8	12.2	12.2	12.2	12.2
	HI PR	248	249	251	255	287	288	290	294	327	328	330	334	371	372	374	378	418	419	421	425	469	470	471	476
	LO PR	125	127	130	135	133	134	138	143	140	141	144	149	145	147	150	155	151	152	155	161	157	159	162	167
	MBh	30.3	30.7	31.6	32.9	30.0	30.4	31.3	32.6	29.3	29.7	30.5	31.9	27.9	28.4	29.2	30.6	26.3	26.7	27.6	29.0	24.9	25.3	26.2	27.5
	S/T	0.85	0.78	0.64	0.49	1.00	0.78	0.64	0.50	1.00	0.81	0.67	0.52	1.00	0.83	0.69	0.54	1.00	1.00	0.71	0.56	1.00	1.00	0.76	0.62
	Δ T	22	20	17	13	22	20	17	13	22	20	17	13	22	20	17	13	22	20	16	13	23	21	17	14
	kW	1.59	1.58	1.58	1.60	1.79	1.78	1.78	1.80	2.01	2.01	2.00	2.02	2.25	2.25	2.24	2.26	2.52	2.51	2.51	2.53	2.83	2.83	2.83	2.84
	Amps	6.5	6.5	6.5	6.6	7.4	7.4	7.4	7.5	8.5	8.5	8.4	8.5	9.6	9.6	9.5	9.6	10.8	10.8	10.8	10.8	12.2	12.2	12.2	12.3
	HI PR	250	252	253	258	289	290	292	296	330	331	333	337	374	375	376	381	421	422	424	428	471	472	474	478
	LO PR	128	129	133	138	135	137	140	145	142	144	147	152	148	149	152	158	153	155	158	163	160	161	165	170

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) Rating Conditions.

kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

IDB		OUTDOOR AMBIENT TEMPERATURE																		115°F																			
		65°F						75°F						85°F						95°F						105°F						115°F							
		ENTERING INDOOR WET BULB TEMPERATURE																																					
		59	63	67	71	75	79	83	87	91	95	99	103	107	111	115	119	123	127	131	135	139	143	147	151	155	159	163	167	171	175	179	183	187	191	195	199	203	
80	AIRFLOW	59	63	67	71	75	79	83	87	91	95	99	103	107	111	115	119	123	127	131	135	139	143	147	151	155	159	163	167	171	175	179	183	187	191	195	199	203	
	MBh	29.5	29.9	30.8	32.2	33.6	35.0	36.4	37.8	39.2	40.6	42.0	43.4	44.8	46.2	47.6	49.0	50.4	51.8	53.2	54.6	56.0	57.4	58.8	60.2	61.6	63.0	64.4	65.8	67.2	68.6	70.0	71.4	72.8	74.2	75.6	77.0	78.4	
	S/T	1.00	0.82	0.68	0.53	0.40	0.28	0.17	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
	ΔT	28	26	23	19	16	13	10	7	4	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	kW	1.57	1.57	1.56	1.58	1.59	1.60	1.61	1.62	1.63	1.64	1.65	1.66	1.67	1.68	1.69	1.70	1.71	1.72	1.73	1.74	1.75	1.76	1.77	1.78	1.79	1.80	1.81	1.82	1.83	1.84	1.85	1.86	1.87	1.88	1.89	1.90	1.91	1.92
975	AIRFLOW	29.5	29.9	30.8	32.2	33.6	35.0	36.4	37.8	39.2	40.6	42.0	43.4	44.8	46.2	47.6	49.0	50.4	51.8	53.2	54.6	56.0	57.4	58.8	60.2	61.6	63.0	64.4	65.8	67.2	68.6	70.0	71.4	72.8	74.2	75.6	77.0	78.4	
	S/T	1.00	0.82	0.68	0.53	0.40	0.28	0.17	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
	ΔT	28	26	23	19	16	13	10	7	4	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	kW	1.57	1.57	1.56	1.58	1.59	1.60	1.61	1.62	1.63	1.64	1.65	1.66	1.67	1.68	1.69	1.70	1.71	1.72	1.73	1.74	1.75	1.76	1.77	1.78	1.79	1.80	1.81	1.82	1.83	1.84	1.85	1.86	1.87	1.88	1.89	1.90	1.91	1.92
	Amps	6.5	6.4	6.4	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
1125	AIRFLOW	29.5	29.9	30.8	32.2	33.6	35.0	36.4	37.8	39.2	40.6	42.0	43.4	44.8	46.2	47.6	49.0	50.4	51.8	53.2	54.6	56.0	57.4	58.8	60.2	61.6	63.0	64.4	65.8	67.2	68.6	70.0	71.4	72.8	74.2	75.6	77.0	78.4	
	S/T	1.00	0.82	0.68	0.53	0.40	0.28	0.17	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
	ΔT	28	26	23	19	16	13	10	7	4	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	kW	1.57	1.57	1.56	1.58	1.59	1.60	1.61	1.62	1.63	1.64	1.65	1.66	1.67	1.68	1.69	1.70	1.71	1.72	1.73	1.74	1.75	1.76	1.77	1.78	1.79	1.80	1.81	1.82	1.83	1.84	1.85	1.86	1.87	1.88	1.89	1.90	1.91	1.92
	Amps	6.5	6.4	6.4	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	

IDB: Entering Indoor Dry Bulb Temperature
 High and low pressures are measured at the liquid and suction service valves.
 Shaded area reflects AHRI Rating Conditions.
 kW = Total system power
 Amps = Outdoor unit amps (compressor + fan)

		Outdoor Ambient Temperature																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	Airflow	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
70	MBh	35.3	35.7	36.8	-	34.9	35.4	36.5	-	34.0	34.5	35.6	-	32.5	33.0	34.0	-	30.6	31.0	32.1	-	28.8	29.3	30.3	-
	S/T	0.66	0.59	0.45	-	0.67	0.59	0.46	-	0.69	0.62	0.48	-	1.00	0.64	0.50	-	1.00	0.66	0.52	-	1.00	0.71	0.58	-
	Δ T	19	17	14	-	19	17	14	-	20	18	14	-	19	17	14	-	19	17	14	-	20	18	15	-
	kW	1.89	1.88	1.88	-	2.12	2.12	2.11	-	2.38	2.38	2.37	-	2.66	2.66	2.65	-	2.97	2.97	2.97	-	3.34	3.34	3.33	-
	Amps	7.7	7.7	7.7	-	8.8	8.8	8.7	-	10.0	10.0	9.9	-	11.2	11.2	11.2	-	12.7	12.7	12.7	-	14.4	14.4	14.3	-
	HI PR	248	249	251	-	287	288	290	-	328	329	331	-	372	373	374	-	419	420	422	-	469	470	472	-
	LO PR	124	125	128	-	131	133	136	-	138	139	142	-	143	145	148	-	149	150	153	-	155	157	160	-
	MBh	35.9	36.4	37.4	-	35.6	36.1	37.1	-	34.7	35.2	36.2	-	33.1	33.6	34.6	-	31.2	31.7	32.7	-	29.4	29.9	31.0	-
	S/T	0.70	0.62	0.49	-	0.71	0.63	0.50	-	0.73	0.66	0.52	-	1.00	0.67	0.54	-	1.00	0.70	0.56	-	1.00	0.75	0.61	-
	Δ T	18	16	13	-	18	16	13	-	18	17	13	-	18	16	13	-	18	16	12	-	19	17	14	-
1350	kW	1.90	1.89	1.89	-	2.13	2.13	2.12	-	2.39	2.39	2.38	-	2.67	2.67	2.66	-	2.98	2.98	2.98	-	3.35	3.35	3.35	-
	Amps	7.8	7.8	7.7	-	8.8	8.8	8.8	-	10.0	10.0	10.0	-	11.3	11.3	11.3	-	12.7	12.7	12.7	-	14.4	14.4	14.4	-
	HI PR	251	252	253	-	289	290	292	-	330	331	333	-	374	375	377	-	421	422	424	-	472	473	474	-
	LO PR	126	128	131	-	133	135	138	-	140	141	145	-	145	147	150	-	151	152	155	-	158	159	162	-
	MBh	36.7	37.2	38.2	-	36.4	36.9	37.9	-	35.5	35.9	37.0	-	33.9	34.4	35.4	-	32.0	32.5	33.5	-	30.2	30.7	31.8	-
	S/T	0.71	0.63	0.50	-	0.71	0.64	0.50	-	0.74	0.66	0.53	-	1.00	0.68	0.55	-	1.00	0.70	0.57	-	1.00	0.76	0.62	-
	Δ T	17	15	12	-	17	15	12	-	17	16	12	-	17	15	12	-	17	15	12	-	18	16	13	-
	kW	1.91	1.90	1.90	-	2.14	2.14	2.13	-	2.40	2.40	2.39	-	2.68	2.68	2.67	-	2.99	2.99	2.99	-	3.36	3.36	3.36	-
	Amps	7.8	7.8	7.8	-	8.9	8.9	8.8	-	10.1	10.0	10.0	-	11.3	11.3	11.3	-	12.8	12.8	12.8	-	14.5	14.5	14.4	-
	HI PR	253	254	256	-	292	293	295	-	332	334	335	-	376	377	379	-	424	425	426	-	474	475	477	-
	LO PR	129	130	133	-	136	138	141	-	143	144	147	-	148	150	153	-	153	155	158	-	160	162	165	-
75	MBh	35.3	35.8	36.8	38.4	35.0	35.5	36.5	38.1	34.1	34.5	35.6	37.2	32.5	33.0	34.0	35.6	30.6	31.1	32.1	33.7	28.8	29.3	30.4	32.0
	S/T	0.79	0.72	0.58	0.44	0.80	0.72	0.59	0.44	1.00	0.75	0.61	0.47	1.00	0.77	0.63	0.49	1.00	0.79	0.65	0.51	1.00	1.00	0.70	0.56
	Δ T	23	22	18	14	23	22	18	14	24	22	18	15	23	21	18	14	23	21	18	14	24	22	19	15
	kW	1.88	1.88	1.88	1.90	2.12	2.11	2.11	2.13	2.38	2.37	2.37	2.39	2.66	2.65	2.65	2.67	2.97	2.97	2.96	2.98	3.34	3.34	3.33	3.35
	Amps	7.7	7.7	7.7	7.8	8.8	8.8	8.7	8.8	10.0	9.9	9.9	10.0	11.2	11.2	11.2	11.3	12.7	12.7	12.6	12.7	14.4	14.3	14.3	14.4
	HI PR	248	250	251	256	287	288	290	294	328	329	331	335	372	373	375	379	419	420	422	426	469	471	472	477
	LO PR	124	125	128	134	131	133	136	141	138	139	142	147	143	145	148	153	149	150	153	158	155	157	160	165
	MBh	35.9	36.4	37.4	39.0	35.6	36.1	37.1	38.7	34.7	35.2	36.2	37.8	33.1	33.6	34.7	36.2	31.2	31.7	32.7	34.3	29.5	30.0	31.0	32.6
	S/T	0.83	0.75	0.62	0.48	1.00	0.76	0.62	0.48	1.00	0.78	0.65	0.51	1.00	0.80	0.67	0.53	1.00	0.83	0.69	0.55	1.00	1.00	0.74	0.60
	Δ T	22	20	17	13	22	20	17	13	23	21	17	14	22	20	17	13	22	20	17	13	23	21	18	14
1200	kW	1.90	1.89	1.89	1.91	2.13	2.13	2.12	2.14	2.39	2.39	2.38	2.40	2.67	2.67	2.66	2.68	2.98	2.98	2.98	2.99	3.35	3.35	3.34	3.36
	Amps	7.8	7.7	7.7	7.8	8.8	8.8	8.8	8.9	10.0	10.0	10.0	10.1	11.3	11.3	11.3	11.3	12.7	12.7	12.7	12.8	14.4	14.4	14.4	14.5
	HI PR	251	252	254	258	290	291	292	297	330	331	333	337	374	375	377	381	421	422	424	428	472	473	475	479
	LO PR	126	128	131	136	133	135	138	143	140	141	145	150	145	147	150	155	151	152	155	161	158	159	162	167
	MBh	36.7	37.2	38.2	39.8	36.4	36.9	37.9	39.5	35.5	36.0	37.0	38.6	33.9	34.4	35.4	37.0	32.0	32.5	33.5	35.1	30.3	30.7	31.8	33.4
	S/T	0.84	0.76	0.63	0.48	1.00	0.77	0.63	0.49	1.00	0.79	0.66	0.51	1.00	0.81	0.68	0.53	1.00	1.00	0.70	0.56	1.00	1.00	0.75	0.61
	Δ T	21	20	16	12	21	19	16	12	22	20	16	13	21	19	16	12	21	19	16	12	22	20	17	13
	kW	1.91	1.90	1.90	1.92	2.14	2.14	2.13	2.15	2.40	2.40	2.39	2.41	2.68	2.68	2.67	2.69	2.99	2.99	2.99	3.00	3.36	3.36	3.35	3.37
	Amps	7.8	7.8	7.8	7.9	8.9	8.9	8.8	8.9	10.1	10.0	10.0	10.1	11.3	11.3	11.3	11.4	12.8	12.8	12.7	12.8	14.5	14.4	14.4	14.5
	HI PR	253	254	256	260	292	293	295	299	333	334	335	340	377	378	379	384	424	425	427	431	474	475	477	481
	LO PR	129	130	133	138	136	138	141	146	143	144	147	152	148	150	153	158	153	155	158	163	160	162	165	170

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) Rating Conditions.

kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

		Outdoor Ambient Temperature																105°F								115°F											
		65°F				75°F				85°F								95°F								105°F								115°F			
		Entering Indoor Wet Bulb Temperature																																			
IDB	Airflow	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71								
80	MBh	35.5	35.9	37.0	38.6	35.1	35.6	36.7	38.3	34.2	34.7	35.8	37.4	32.7	33.2	34.2	35.8	30.8	31.2	32.3	33.9	29.0	29.5	30.5	32.1	29.0	29.5	30.5	32.1								
	S/T	1.00	0.84	0.71	0.56	1.00	0.85	0.71	0.57	1.00	0.87	0.74	0.59	1.00	0.89	0.76	0.61	1.00	1.00	0.78	0.64	1.00	1.00	0.83	0.69	1.00	1.00	0.83	0.69								
	Δ T	28	26	22	19	28	26	22	19	28	26	22	19	28	26	22	18	27	25	22	18	29	27	23	19	29	27	23	19								
	kW	1.88	1.88	1.88	1.90	2.12	2.12	2.11	2.13	2.38	2.37	2.37	2.39	2.66	2.66	2.65	2.67	2.97	2.97	2.97	2.98	3.34	3.34	3.33	3.35	3.34	3.34	3.33	3.35								
	Amps	7.7	7.7	7.7	7.8	8.8	8.8	8.7	8.8	10.0	9.9	9.9	10.0	11.2	11.2	11.2	11.3	12.7	12.7	12.7	12.7	14.4	14.4	14.3	14.4	14.4	14.4	14.3	14.4								
	HI PR	249	250	252	256	288	289	291	295	328	329	331	336	372	373	375	379	419	421	422	427	470	471	473	477	470	471	473	477								
	LO PR	124	126	129	134	132	133	136	142	138	140	143	148	144	145	148	153	149	151	154	159	156	157	160	166	156	157	160	166								
1200	MBh	36.1	36.6	37.6	39.2	35.8	36.3	37.3	38.9	34.9	35.4	36.4	38.0	33.3	33.8	34.8	36.4	31.4	31.9	32.9	34.5	29.7	30.1	31.2	32.8	29.7	30.1	31.2	32.8								
	S/T	1.00	0.88	0.74	0.60	1.00	0.88	0.75	0.61	1.00	0.91	0.77	0.63	1.00	1.00	0.79	0.65	1.00	1.00	0.81	0.67	1.00	1.00	0.87	0.72	1.00	1.00	0.87	0.72								
	Δ T	27	25	21	17	26	25	21	17	27	25	21	18	26	25	21	17	26	24	21	17	27	26	22	18	27	26	22	18								
	kW	1.90	1.89	1.89	1.91	2.13	2.13	2.12	2.14	2.39	2.39	2.38	2.40	2.67	2.67	2.66	2.68	2.98	2.98	2.98	2.99	3.35	3.35	3.34	3.36	3.35	3.35	3.34	3.36								
	Amps	7.8	7.8	7.7	7.8	8.8	8.8	8.8	8.9	10.0	10.0	10.0	10.1	11.3	11.3	11.3	11.3	12.7	12.7	12.7	12.8	14.4	14.4	14.4	14.5	14.4	14.4	14.4	14.5								
	HI PR	251	252	254	258	290	291	293	297	331	332	334	338	375	376	377	382	422	423	425	429	472	473	475	479	472	473	475	479								
	LO PR	127	128	131	136	134	135	139	144	140	142	145	150	146	147	151	156	151	153	156	161	158	160	163	168	158	160	163	168								
1350	MBh	36.9	37.4	38.4	40.0	36.6	37.1	38.1	39.7	35.7	36.1	37.2	38.8	34.1	34.6	35.6	37.2	32.2	32.7	33.7	35.3	30.4	30.9	32.0	33.6	30.4	30.9	32.0	33.6								
	S/T	1.00	0.89	0.75	0.61	1.00	0.89	0.76	0.61	1.00	0.92	0.78	0.64	1.00	1.00	0.80	0.66	1.00	1.00	0.82	0.68	1.00	1.00	0.87	0.73	1.00	1.00	0.87	0.73								
	Δ T	26	24	20	17	26	24	20	16	26	24	20	17	26	24	20	16	25	23	20	16	26	25	21	17	26	25	21	17								
	kW	1.91	1.90	1.90	1.92	2.14	2.14	2.13	2.15	2.40	2.40	2.39	2.41	2.68	2.68	2.67	2.69	2.99	2.99	2.99	3.00	3.36	3.36	3.35	3.37	3.36	3.36	3.35	3.37								
	Amps	7.8	7.8	7.8	7.9	8.9	8.9	8.8	8.9	10.1	10.0	10.0	10.1	11.3	11.3	11.3	11.4	12.8	12.8	12.8	12.8	14.5	14.5	14.4	14.5	14.5	14.5	14.4	14.5								
	HI PR	254	255	256	261	292	294	295	300	333	334	336	340	377	378	380	384	424	425	427	431	475	476	477	482	475	476	477	482								
	LO PR	129	131	134	139	137	138	141	146	143	145	148	153	149	150	153	158	154	156	159	164	161	162	165	171	161	162	165	171								

85	MBh	36.0	36.5	37.6	39.2	35.7	36.2	37.3	38.8	34.8	35.3	36.3	37.9	33.3	33.7	34.8	36.4	31.3	31.8	32.9	34.5	29.6	30.1	31.1	32.7
	S/T	1.00	0.94	0.81	0.66	1.00	0.95	0.81	0.67	1.00	1.00	0.84	0.70	1.00	1.00	0.86	0.71	1.00	1.00	0.88	0.74	1.00	1.00	1.00	0.79
	Δ T	31	29	26	22	31	29	26	22	32	30	26	22	31	29	26	22	31	29	26	22	32	30	27	23
	kW	1.89	1.89	1.88	1.90	2.12	2.12	2.12	2.13	2.38	2.38	2.38	2.39	2.66	2.66	2.66	2.67	2.98	2.97	2.97	2.99	3.34	3.34	3.34	3.36
	Amps	7.7	7.7	7.7	7.8	8.8	8.8	8.8	8.8	10.0	10.0	10.0	10.0	11.3	11.3	11.3	11.2	12.7	12.7	12.7	12.8	14.4	14.4	14.4	14.4
	HI PR	250	251	253	257	289	290	292	296	330	331	332	337	373	374	376	380	421	422	423	428	471	472	474	478
	LO PR	126	128	131	136	134	135	138	143	140	142	145	150	146	147	150	155	151	152	156	161	158	159	162	167
1200	MBh	36.7	37.2	38.2	39.8	36.4	36.9	37.9	39.5	35.5	35.9	37.0	38.6	33.9	34.4	35.4	37.0	32.0	32.5	33.5	35.1	30.2	30.7	31.8	33.4
	S/T	1.00	0.98	0.84	0.70	1.00	1.00	0.85	0.71	1.00	1.00	0.87	0.73	1.00	1.00	0.89	0.75	1.00	1.00	0.92	0.77	1.00	1.00	1.00	0.82
	Δ T	30	28	25	21	30	28	25	21	30	29	25	21	30	28	25	21	30	28	25	21	31	29	26	22
	kW	1.90	1.90	1.89	1.91	2.13	2.13	2.13	2.15	2.39	2.39	2.39	2.40	2.67	2.67	2.67	2.69	2.99	2.99	2.98	3.00	3.36	3.35	3.35	3.37
	Amps	7.8	7.8	7.8	7.8	8.8	8.8	8.8	8.9	10.0	10.0	10.0	10.1	11.3	11.3	11.3	11.4	12.8	12.7	12.7	12.8	14.4	14.4	14.4	14.5
	HI PR	252	253	255	259	291	292	294	298	332	333	335	339	376	377	379	383	423	424	426	430	473	474	476	480
	LO PR	128	130	133	138	136	137	140	146	142	144	147	152	148	149	152	158	153	155	158	163	160	161	165	170
1350	MBh	37.5	37.9	39.0	40.6	37.1	37.6	38.7	40.3	36.2	36.7	37.8	39.4	34.7	35.2	36.2	37.8	32.8	33.3	34.3	35.9	31.0	31.5	32.6	34.1
	S/T	1.00	0.99	0.85	0.71	1.00	1.00	0.86	0.71	1.00	1.00	0.88	0.74	1.00	1.00	0.90	0.76	1.00	1.00	0.88	0.78	1.00	1.00	1.00	0.83
	Δ T	29	27	24	20	29	27	24	20	30	28	24	20	29	27	24	20	29	27	24	20	30	28	25	21
	kW	1.91	1.91	1.90	1.92	2.14	2.14	2.14	2.16	2.40	2.40	2.40	2.41	2.68	2.68	2.68	2.70	3.00	3.00	2.99	3.01	3.37	3.36	3.36	3.38
	Amps	7.8	7.8	7.8	7.9	8.9	8.9	8.9	8.9	10.1	10.1	10.0	10.1	11.4	11.4	11.3	11.4	12.8	12.8	12.8	12.9	14.5	14.5	14.5	14.5
	HI PR	255	256	258	262	294	295	296	301	334	335	337	341	378	379	381	385	425	426	428	432	476	477	479	483
	LO PR	131	133	136	141	138	140	143	148	145	146	149	155	150	152	155	160	156	157	160	166	163	164	167	172

DB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects AHRI Rating Conditions.

kW = Total system power

Amperes = Outdoor unit amperes (compressor + fan)

IDB: Entering Indoor Dry Bulb Temperature
 High and low pressures are measured at the liquid and suction service valves.
 Shaded area reflects AHRI Rating Conditions.
 kW = Total system power
 Amps = Outdoor unit amps (compressor + fan)

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																																			
				65°F						75°F						85°F						95°F						105°F						115°F					
				ENTERING INDOOR WET BULB TEMPERATURE																																			
70	1140	MBh	40.2	40.8	41.9	-	39.8	40.4	41.6	-	38.8	39.4	40.6	-	37.0	37.6	38.8	-	34.8	35.4	36.6	-	32.9	33.4	34.6	-													
		S/T	0.64	0.57	0.44	-	0.65	0.58	0.44	-	0.67	0.60	0.47	-	0.69	0.62	0.49	-	1.00	0.64	0.51	-	1.00	0.69	0.56	-													
		Δ T	20	18	14	-	20	18	14	-	20	18	15	-	20	18	14	-	20	18	14	-	21	19	15	-													
		kW	2.13	2.13	2.13	-	2.40	2.40	2.40	-	2.71	2.70	2.70	-	3.03	3.03	3.02	-	3.40	3.39	3.39	-	3.82	3.82	3.82	-													
		Amps	8.5	8.5	8.5	-	9.7	9.7	9.7	-	11.1	11.1	11.1	-	12.6	12.6	12.6	-	14.3	14.3	14.2	-	16.2	16.2	16.2	-													
	1400	Hi PR	247	248	249	-	285	286	288	-	326	327	329	-	369	370	372	-	416	417	419	-	466	467	469	-													
		LO PR	121	123	126	-	129	130	133	-	135	136	140	-	140	142	145	-	146	147	150	-	152	154	157	-													
		MBh	41.4	42.0	43.2	-	41.1	41.6	42.8	-	40.0	40.6	41.8	-	38.3	38.8	40.0	-	36.1	36.6	37.8	-	34.1	34.7	35.8	-													
		S/T	0.69	0.61	0.48	-	0.69	0.62	0.49	-	0.72	0.64	0.51	-	1.00	0.66	0.53	-	1.00	0.68	0.55	-	1.00	0.73	0.60	-													
		Δ T	18	16	13	-	18	16	13	-	19	17	13	-	18	16	13	-	18	16	12	-	19	17	14	-													
1575	kW	2.15	2.15	2.15	-	2.42	2.42	2.42	-	2.73	2.72	2.72	-	3.05	3.05	3.05	-	3.42	3.41	3.41	-	3.84	3.84	3.84	-														
	Amps	8.6	8.6	8.6	-	9.8	9.8	9.8	-	11.2	11.2	11.2	-	12.7	12.7	12.7	-	14.4	14.3	14.3	-	16.3	16.3	16.3	-														
	Hi PR	250	251	253	-	289	290	292	-	329	331	332	-	373	374	376	-	420	421	423	-	470	471	473	-														
	LO PR	125	127	130	-	132	134	137	-	139	140	143	-	144	146	149	-	149	151	154	-	156	158	161	-														
	MBh	42.5	43.1	44.3	-	42.2	42.7	43.9	-	41.1	41.7	42.9	-	39.4	39.9	41.1	-	37.2	37.7	38.9	-	35.2	35.7	36.9	-														
	S/T	0.68	0.60	0.47	-	0.68	0.61	0.48	-	0.71	0.63	0.50	-	1.00	0.65	0.52	-	1.00	0.67	0.54	-	1.00	0.72	0.59	-														
	Δ T	17	15	12	-	17	15	12	-	18	16	12	-	17	15	12	-	17	15	11	-	18	16	13	-														
	kW	2.17	2.16	2.16	-	2.44	2.43	2.43	-	2.74	2.74	2.73	-	3.06	3.06	3.06	-	3.43	3.43	3.42	-	3.86	3.85	3.85	-														
	Amps	8.6	8.6	8.6	-	9.9	9.9	9.8	-	11.3	11.2	11.2	-	12.7	12.7	12.7	-	14.4	14.4	14.4	-	16.4	16.4	16.3	-														
	Hi PR	253	254	256	-	292	293	294	-	332	333	335	-	376	377	378	-	423	424	425	-	473	474	476	-														
LO PR	128	130	133	-	135	137	140	-	142	143	146	-	147	149	152	-	153	154	157	-	159	161	164	-															

75	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
	MbH	40.2	40.8	42.0	43.8	39.9	40.4	41.6	43.4	38.8	39.4	40.6	42.4	37.0	37.6	38.8	40.6	36.1	36.7	37.9	39.7	34.1	34.7	35.9	37.7	32.9	33.4	34.6	36.4	32.9	33.4	34.6	36.4
	S/T	0.77	0.69	0.56	0.43	0.77	0.70	0.57	0.43	1.00	0.72	0.59	0.46	1.00	0.74	0.61	0.47	1.00	0.81	0.68	0.54	1.00	1.00	0.73	0.59	1.00	0.81	0.68	0.55	1.00	0.81	0.68	0.55
	Δ T	24	22	19	15	24	22	19	15	25	23	19	15	24	22	19	15	24	22	18	15	24	22	20	16	24	22	18	15	25	23	20	16
	kW	2.13	2.13	2.13	2.15	2.40	2.40	2.40	2.42	2.70	2.70	2.70	2.72	3.03	3.03	3.02	3.04	3.39	3.39	3.39	3.41	3.82	3.82	3.82	3.84	3.39	3.39	3.39	3.41	3.82	3.82	3.82	3.84
	Amps	8.5	8.5	8.4	8.5	9.7	9.7	9.7	9.8	11.1	11.1	11.1	11.2	12.6	12.6	12.6	12.7	14.3	14.2	14.2	14.3	16.2	16.2	16.2	16.3	14.3	14.2	14.2	14.3	16.2	16.2	16.2	16.3
	Hi PR	247	248	250	254	286	287	288	293	326	327	329	333	369	371	372	377	416	417	419	423	467	468	469	474	416	417	419	423	467	468	469	474
	LO PR	121	123	126	131	129	130	133	138	135	136	140	145	140	142	145	150	146	147	150	155	152	154	157	162	146	147	150	155	152	154	157	162
	MbH	41.5	42.0	43.2	45.0	41.1	41.7	42.8	44.7	40.1	40.6	41.8	43.6	38.3	38.8	40.0	41.8	36.1	36.7	37.9	39.7	34.1	34.7	35.9	37.7	32.9	33.4	34.6	36.4	32.9	33.4	34.6	36.4
	S/T	0.81	0.74	0.61	0.47	0.82	0.74	0.61	0.47	1.00	0.77	0.64	0.50	1.00	0.79	0.66	0.52	1.00	0.81	0.68	0.54	1.00	1.00	0.73	0.59	1.00	0.81	0.68	0.55	1.00	0.81	0.68	0.55

IDB: Entering Indoor Dry Bulb Temperature
 High and low pressures are measured at the liquid and suction service valves.
 Shaded area reflects ACCA (TVA) Rating Conditions.
 kW = Total system power
 Amps = Outdoor unit amps (compressor + fan)

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																							
				65°F				75°F				85°F				95°F				105°F				115°F			
				ENTERING INDOOR WET BULB TEMPERATURE																							
59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71				
80	1140	MBh	40.4	41.0	42.2	44.0	40.1	40.6	41.8	43.6	39.0	39.6	40.8	42.6	37.3	37.8	39.0	40.8	35.1	35.6	36.8	38.6	33.1	33.6	34.8	36.6	
		S/T	0.89	0.82	0.68	0.55	1.00	0.82	0.69	0.55	1.00	0.85	0.71	0.58	1.00	0.86	0.73	0.60	1.00	1.00	0.75	0.62	1.00	1.00	0.80	0.67	
		Δ T	29	27	23	19	29	27	23	19	29	27	23	20	29	27	23	19	28	27	23	19	30	28	24	20	
		kW	2.13	2.13	2.13	2.15	2.40	2.40	2.40	2.42	2.70	2.70	2.70	2.72	3.03	3.03	3.02	3.05	3.40	3.39	3.39	3.41	3.82	3.82	3.82	3.84	
		Amps	8.5	8.5	8.5	8.6	9.7	9.7	9.7	9.8	11.1	11.1	11.1	11.2	12.6	12.6	12.6	12.7	14.3	14.3	14.2	14.3	16.2	16.2	16.2	16.3	
	Hi/PR	247	248	250	254	286	287	289	293	326	327	329	333	370	371	373	377	417	418	420	424	467	468	470	474		
	LO/PR	122	123	126	132	129	131	134	139	136	137	140	145	141	142	145	151	146	148	151	156	153	154	157	162		
	1400	MBh	41.7	42.2	43.4	45.2	41.3	41.9	43.1	44.9	40.3	40.8	42.0	43.8	38.5	39.1	40.2	42.0	36.3	36.9	38.1	39.9	34.3	34.9	36.1	37.9	
		S/T	1.00	0.86	0.73	0.59	1.00	0.86	0.73	0.60	1.00	0.89	0.76	0.62	1.00	1.00	0.78	0.64	1.00	1.00	0.80	0.66	1.00	1.00	0.85	0.71	
		Δ T	27	25	21	18	27	25	21	18	27	25	22	18	27	25	21	18	27	25	21	17	28	26	22	19	
kW		2.15	2.15	2.15	2.17	2.42	2.42	2.42	2.44	2.73	2.72	2.72	2.74	3.05	3.05	3.04	3.07	3.42	3.41	3.41	3.43	3.84	3.84	3.84	3.86		
Amps		8.6	8.6	8.5	8.6	9.8	9.8	9.8	9.9	11.2	11.2	11.2	11.3	12.7	12.7	12.7	12.8	14.4	14.3	14.3	14.4	16.3	16.3	16.3	16.4		
1575	Hi/PR	251	252	254	258	290	291	292	297	330	331	333	337	374	375	376	381	421	422	423	428	471	472	473	478		
	LO/PR	126	127	130	135	133	134	137	143	139	141	144	149	145	146	149	154	150	151	155	160	157	158	161	166		
	MBh	42.8	43.3	44.5	46.3	42.4	43.0	44.1	46.0	41.4	41.9	43.1	44.9	39.6	40.1	41.3	43.1	37.4	38.0	39.1	41.0	35.4	36.0	37.2	39.0		
	S/T	1.00	0.85	0.72	0.58	1.00	0.85	0.72	0.59	1.00	0.88	0.75	0.61	1.00	1.00	0.77	0.63	1.00	1.00	0.79	0.65	1.00	1.00	0.84	0.70		
	Δ T	26	24	20	17	26	24	20	17	26	24	21	17	26	24	20	17	26	24	20	16	27	25	21	18		
85	1140	kW	2.17	2.16	2.16	2.18	2.44	2.43	2.43	2.45	2.74	2.73	2.73	2.75	3.06	3.06	3.06	3.08	3.43	3.43	3.42	3.44	3.86	3.85	3.85	3.87	
		Amps	8.6	8.6	8.6	8.7	9.9	9.9	9.8	9.9	11.2	11.2	11.2	11.3	12.7	12.7	12.7	12.8	14.4	14.4	14.4	14.5	16.4	16.4	16.3	16.4	
		Hi/PR	249	250	251	256	287	288	290	294	328	329	330	335	371	372	374	378	418	419	421	425	468	469	471	475	
		LO/PR	124	125	128	133	131	132	135	141	137	139	142	147	143	144	147	152	148	149	153	158	155	156	159	164	
		MBh	42.3	42.9	44.1	45.9	42.0	42.5	43.7	45.5	40.9	41.5	42.7	44.5	39.2	39.7	40.9	42.7	37.0	37.5	38.7	40.5	35.0	35.6	36.7	38.5	
1400	S/T	1.00	0.96	0.83	0.69	1.00	1.00	0.83	0.69	1.00	1.00	0.86	0.72	1.00	1.00	0.87	0.74	1.00	1.00	0.90	0.76	1.00	1.00	1.00	0.81		
	Δ T	31	29	25	21	31	29	25	21	31	29	26	22	31	29	25	21	31	29	25	21	32	30	26	22		
	kW	2.16	2.16	2.15	2.17	2.43	2.43	2.42	2.44	2.73	2.73	2.72	2.74	3.06	3.05	3.05	3.07	3.42	3.42	3.41	3.44	3.85	3.85	3.84	3.86		
	Amps	8.6	8.6	8.6	8.7	9.8	9.8	9.8	9.9	11.2	11.2	11.2	11.3	12.7	12.7	12.7	12.8	14.4	14.4	14.3	14.4	16.3	16.3	16.3	16.4		
	Hi/PR	252	253	255	259	291	292	294	298	331	332	334	338	375	376	378	382	422	423	425	429	472	473	475	479		
1575	LO/PR	127	129	132	137	135	136	139	144	141	143	146	151	146	148	151	156	152	153	156	161	158	160	163	168		
	MBh	43.4	44.0	45.2	47.0	43.1	43.6	44.8	46.6	42.0	42.6	43.8	45.6	40.2	40.8	42.0	43.8	38.1	38.6	39.8	41.6	36.1	36.6	37.8	39.6		
	S/T	1.00	0.95	0.82	0.68	1.00	1.00	0.82	0.68	1.00	1.00	0.85	0.71	1.00	1.00	0.86	0.73	1.00	1.00	1.00	0.75	1.00	1.00	1.00	0.80		
	Δ T	30	28	24	20	30	28	24	20	30	28	25	21	30	28	24	20	30	28	24	20	31	29	25	21		
	kW	2.17	2.17	2.16	2.18	2.44	2.44	2.43	2.45	2.74	2.74	2.74	2.76	3.07	3.07	3.06	3.08	3.43	3.43	3.43	3.45	3.86	3.86	3.85	3.87		
85	1575	Amps	8.7	8.6	8.6	8.7	9.9	9.9	9.9	10.0	11.3	11.3	11.2	11.3	12.8	12.8	12.7	12.8	14.4	14.4	14.4	14.5	16.4	16.4	16.4	16.5	
		Hi/PR	255	256	258	262	294	295	296	301	334	335	337	341	378	379	380	385	424	426	427	431	475	476	477	482	
		LO/PR	131	132	135	140	138	139	142	147	144	146	149	154	150	151	154	159	155	156	159	164	162	163	166	171	
		Shaded area reflects AHRI Rating Conditions.																				kW = Total system power					
		DB: Entering Indoor Dry Bulb Temperature																				Amperes = Outdoor unit amperes (compressor + fan)					

		OUTDOOR AMBIENT TEMPERATURE																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71				
70	1400	MBh	46.4	47.0	48.4	-	46.0	46.6	48.0	-	44.8	45.4	46.8	-	42.7	43.4	44.7	-	40.2	40.9	42.2	-			
		S/T	0.65	0.58	0.45	-	0.66	0.59	0.45	-	0.69	0.61	0.48	-	0.70	0.63	0.50	-	1.00	0.65	0.52	-			
		Δ T	19	17	14	-	19	17	14	-	19	18	14	-	19	17	14	-	19	17	13	-			
		kW	2.47	2.47	2.46	-	2.78	2.77	2.77	-	3.12	3.12	3.12	-	3.50	3.50	3.49	-	3.92	3.91	3.91	-			
		Amps	10.0	10.0	10.0	-	11.4	11.4	11.4	-	13.0	13.0	13.0	-	14.7	14.7	14.7	-	16.6	16.6	16.6	-			
		HI PR	246	247	249	-	284	285	287	-	324	326	327	-	368	369	371	-	415	416	417	-			
		LO PR	121	123	126	-	128	130	133	-	135	136	139	-	140	142	145	-	145	147	150	-			
	1600	MBh	47.2	47.9	49.2	-	46.8	47.5	48.8	-	45.6	46.3	47.6	-	43.6	44.2	45.6	-	41.0	41.7	43.1	-			
		S/T	0.69	0.62	0.48	-	0.70	0.62	0.49	-	0.72	0.65	0.51	-	0.74	0.67	0.53	-	1.00	0.69	0.55	-			
		Δ T	18	16	13	-	18	16	13	-	18	16	13	-	18	16	13	-	18	16	12	-			
kW		2.48	2.48	2.47	-	2.79	2.79	2.78	-	3.14	3.14	3.13	-	3.51	3.51	3.51	-	3.93	3.93	3.92	-				
Amps		10.1	10.1	10.0	-	11.5	11.5	11.5	-	13.1	13.1	13.0	-	14.8	14.8	14.8	-	16.7	16.7	16.7	-				
HI PR		248	249	251	-	287	288	289	-	327	328	330	-	370	371	373	-	417	418	420	-				
LO PR		123	125	128	-	131	132	135	-	137	138	141	-	142	144	147	-	148	149	152	-				
1800	MBh	48.3	48.9	50.3	-	47.8	48.5	49.9	-	46.6	47.3	48.7	-	44.6	45.2	46.6	-	42.1	42.7	44.1	-				
	S/T	0.70	0.62	0.49	-	0.70	0.63	0.50	-	0.73	0.65	0.52	-	1.00	0.67	0.54	-	1.00	0.69	0.56	-				
	Δ T	17	15	12	-	17	15	12	-	17	16	12	-	17	15	12	-	17	15	11	-				
	kW	2.50	2.49	2.49	-	2.81	2.80	2.80	-	3.15	3.15	3.14	-	3.53	3.52	3.52	-	3.94	3.94	3.94	-				
	Amps	10.1	10.1	10.1	-	11.6	11.5	11.5	-	13.1	13.1	13.1	-	14.8	14.8	14.8	-	16.8	16.8	16.7	-				
	HI PR	250	251	253	-	289	290	292	-	329	330	332	-	373	374	375	-	419	420	422	-				
	LO PR	126	127	130	-	133	135	138	-	140	141	144	-	145	146	149	-	150	152	155	-				
75	1400	MBh	46.4	47.1	48.4	50.5	46.0	46.6	48.0	50.1	44.8	45.5	46.8	48.9	42.7	43.4	44.8	46.9	40.2	40.9	42.2	44.3			
		S/T	0.78	0.71	0.57	0.43	0.79	0.71	0.58	0.44	1.00	0.74	0.60	0.46	1.00	0.76	0.62	0.48	1.00	0.78	0.64	0.50			
		Δ T	23	21	18	14	23	21	18	14	24	22	18	15	23	21	18	14	23	21	18	14			
		kW	2.47	2.46	2.46	2.48	2.78	2.77	2.77	2.79	3.12	3.12	3.11	3.14	3.50	3.49	3.49	3.51	3.91	3.91	3.91	3.93			
		Amps	10.0	10.0	10.0	10.1	11.4	11.4	11.4	11.5	13.0	13.0	13.0	13.1	14.7	14.7	14.7	14.8	16.6	16.6	16.6	16.7			
		HI PR	246	247	249	253	284	285	287	291	325	326	327	332	368	369	371	375	415	416	418	422			
		LO PR	121	123	126	131	128	130	133	138	135	136	139	144	140	142	145	150	145	147	150	155			
	1600	MBh	47.2	47.9	49.3	51.4	46.8	47.5	48.9	50.9	45.6	46.3	47.7	49.7	43.6	44.2	45.6	47.7	41.1	41.7	43.1	45.2			
		S/T	0.82	0.74	0.61	0.47	0.82	0.75	0.62	0.48	1.00	0.77	0.64	0.50	1.00	0.79	0.66	0.52	1.00	0.81	0.68	0.54			
		Δ T	22	20	17	13	22	20	17	13	22	21	17	13	22	20	17	13	22	20	17	13			
kW		2.48	2.48	2.47	2.50	2.79	2.79	2.78	2.81	3.14	3.13	3.13	3.15	3.51	3.51	3.50	3.53	3.93	3.93	3.92	3.95				
Amps		10.1	10.1	10.0	10.1	11.5	11.5	11.4	11.6	13.1	13.1	13.0	13.1	14.8	14.8	14.7	14.9	16.7	16.7	16.7	16.8				
HI PR		248	249	251	255	287	288	289	294	327	328	330	334	370	371	373	377	417	418	420	424				
LO PR		123	125	128	133	131	132	135	140	137	138	141	147	142	144	147	152	148	149	152	157				
1800	MBh	48.3	48.9	50.3	52.4	47.9	48.5	49.9	52.0	46.7	47.3	48.7	50.8	44.6	45.3	46.6	48.7	42.1	42.7	44.1	46.2				
	S/T	0.82	0.75	0.62	0.48	1.00	0.76	0.62	0.48	1.00	0.78	0.65	0.51	1.00	0.80	0.67	0.53	1.00	0.82	0.69	0.55				
	Δ T	21	19	16	12	21	19	16	12	22	20	16	12	21	19	16	12	21	19	16	12				
	kW	2.49	2.49	2.49	2.51	2.80	2.80	2.80	2.82	3.15	3.15	3.14	3.17	3.52	3.52	3.52	3.54	3.94	3.94	3.93	3.96				
	Amps	10.1	10.1	10.1	10.2	11.5	11.5	11.5	11.6	13.1	13.1	13.1	13.2	14.8	14.8	14.8	14.9	16.8	16.7	16.7	16.8				
	HI PR	251	252	253	258	289	290	292	296	329	330	332	336	373	374	376	380	420	421	422	427				
	LO PR	126	127	130	136	133	135	138	143	140	141	144	149	145	146	149	155	150	152	155	160				

DB: Entering Indoor Dry Bulb Temperature

Shaded area reflects ACCA (TVA) Rating Conditions.

kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) Rating Conditions.

kW = Total system power
Amps = Outdoor unit amps (compressor + fan)

		OUTDOOR AMBIENT TEMPERATURE																																			
		65°F						75°F						85°F						95°F						105°F						115°F					
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71				
80	1400	MBh	46.6	47.3	48.7	50.8	46.2	46.9	48.3	50.3	45.0	45.7	47.1	49.1	43.0	43.6	45.0	47.1	40.5	41.1	42.5	44.6	38.2	38.8	40.2	42.3	38.2	38.8	40.2	42.3	38.2	38.8	40.2	42.3			
		S/T	0.90	0.83	0.70	0.56	1.00	0.84	0.70	0.56	1.00	0.86	0.73	0.59	1.00	0.88	0.75	0.61	1.00	1.00	0.77	0.63	1.00	1.00	0.82	0.68	1.00	1.00	0.82	0.68	1.00	1.00	0.82	0.68			
		Δ T	28	26	22	18	27	26	22	18	28	26	22	19	27	26	22	18	27	25	22	18	28	26	23	19	28	26	23	19	28	26	23	19			
		kW	2.47	2.46	2.46	2.48	2.78	2.77	2.77	2.79	3.12	3.12	3.12	3.14	3.50	3.49	3.49	3.51	3.92	3.91	3.91	3.93	4.41	4.40	4.40	4.42	4.41	4.40	4.40	4.42	4.41	4.40	4.40	4.42			
		Amps	10.0	10.0	10.0	10.1	11.4	11.4	11.4	11.5	13.0	13.0	13.0	13.1	14.7	14.7	14.7	14.8	16.6	16.6	16.6	16.7	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9			
		HiPR	246	247	249	253	285	286	288	292	325	326	328	332	369	370	371	376	415	416	418	422	465	466	468	472	465	466	468	472	465	466	468	472			
		LoPR	122	123	126	131	129	130	133	139	135	137	140	145	141	142	145	150	146	147	150	156	153	154	157	162	153	154	157	162	153	154	157	162			
		MBh	47.5	48.1	49.5	51.6	47.1	47.7	49.1	51.2	45.9	46.5	47.9	50.0	43.8	44.5	45.8	47.9	41.3	42.0	43.3	45.4	39.0	39.7	41.0	43.1	39.0	39.7	41.0	43.1	39.0	39.7	41.0	43.1			
80	1600	S/T	1.00	0.87	0.73	0.59	1.00	0.87	0.74	0.60	1.00	0.90	0.76	0.62	1.00	0.92	0.78	0.64	1.00	1.00	0.80	0.66	1.00	1.00	0.85	0.71	1.00	1.00	0.85	0.71	1.00	1.00	0.85	0.71			
		Δ T	26	25	21	17	26	24	21	17	27	25	21	18	26	24	21	17	26	24	21	17	27	25	22	18	27	25	22	18	27	25	22	18			
		kW	2.48	2.48	2.47	2.50	2.79	2.79	2.78	2.81	3.14	3.14	3.13	3.15	3.51	3.51	3.50	3.53	3.93	3.93	3.92	3.95	4.42	4.42	4.42	4.44	4.42	4.42	4.42	4.44	4.42	4.42	4.44	4.44			
		Amps	10.1	10.1	10.0	10.1	11.5	11.5	11.5	11.6	13.1	13.1	13.0	13.1	14.8	14.8	14.7	14.9	16.7	16.7	16.7	16.8	18.9	18.9	18.9	19.0	18.9	18.9	18.9	18.9	18.9	18.9	19.0	19.0			
		HiPR	249	250	251	256	287	288	290	294	327	329	330	334	371	372	374	378	418	419	420	425	468	469	470	475	468	469	470	475	468	469	470	475			
		LoPR	124	125	128	133	131	133	136	141	138	139	142	147	143	144	147	152	148	150	153	158	155	156	159	164	155	156	159	164	155	156	159	164			
		MBh	48.5	49.2	50.5	52.6	48.1	48.8	50.1	52.2	46.9	47.6	48.9	51.0	44.9	45.5	46.9	49.0	42.3	43.0	44.4	46.4	40.0	40.7	42.1	44.1	40.0	40.7	42.1	44.1	40.0	40.7	42.1	44.1			
		S/T	1.00	0.87	0.74	0.60	1.00	0.88	0.75	0.61	1.00	0.90	0.77	0.63	1.00	1.00	0.79	0.65	1.00	1.00	0.81	0.67	1.00	1.00	0.86	0.72	1.00	1.00	0.86	0.72	1.00	1.00	0.86	0.72			
80	1800	Δ T	25	24	20	16	25	24	20	16	26	24	20	17	25	24	20	16	25	23	20	16	26	24	21	17	26	24	21	17	27	25	22	18			
		kW	2.50	2.49	2.49	2.51	2.81	2.80	2.80	2.82	3.15	3.15	3.14	3.17	3.53	3.52	3.52	3.54	3.94	3.94	3.94	3.96	4.43	4.43	4.43	4.45	4.43	4.43	4.43	4.45	4.43	4.43	4.45	4.45			
		Amps	10.1	10.1	10.1	10.2	11.5	11.5	11.5	11.6	13.1	13.1	13.1	13.2	14.8	14.8	14.8	14.9	16.8	16.7	16.7	16.8	19.0	19.0	19.0	19.1	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.1			
		HiPR	251	252	254	258	290	291	292	297	330	331	333	337	373	374	376	380	420	421	423	427	470	471	473	477	470	471	473	477	470	471	473	477			
		LoPR	126	128	131	136	134	135	138	143	140	142	145	150	145	147	150	155	151	152	155	160	157	159	162	167	157	159	162	167	157	159	162	167			
		85	1400	MBh	47.4	48.1	49.4	51.5	47.0	47.7	49.0	51.1	45.8	46.5	47.8	49.9	43.8	44.4	45.8	47.9	41.2	41.9	43.3	45.3	38.9	39.6	41.0	43.1	38.9	39.6	41.0	43.1	38.9	39.6	41.0	43.1	
				S/T	1.00	0.93	0.80	0.66	1.00	0.94	0.80	0.66	1.00	1.00	0.83	0.69	1.00	1.00	0.85	0.71	1.00	1.00	0.87	0.73	1.00	1.00	0.82	0.68	1.00	1.00	0.82	0.68	1.00	1.00	0.82	0.68	
				Δ T	31	29	26	22	31	29	26	22	31	30	26	22	31	29	26	22	31	29	25	22	32	30	27	23	32	30	27	23	32	30	27	23	
kW	2.47			2.47	2.47	2.49	2.78	2.78	2.78	2.80	3.13	3.13	3.12	3.14	3.50	3.50	3.50	3.52	3.92	3.92	3.91	3.94	4.41	4.41	4.40	4.43	4.41	4.41	4.40	4.43	4.41	4.41	4.40	4.43			
Amps	10.0			10.0	10.0	10.1	11.4	11.4	11.4	11.5	13.0	13.0	13.0	13.1	14.7	14.7	14.7	14.8	16.7	16.6	16.6	16.7	18.9	18.9	18.9	19.0	18.9	18.9	18.9	19.0	18.9	18.9	19.0	19.0			
HiPR	248			249	250	255	286	287	289	293	326	327	329	333	370	371	372	377	416	418	419	423	466	467	469	473	466	467	469	473	466	467	469	473			
LoPR	123			125	128	133	131	132	135	140	137	139	142	147	142	144	147	152	148	149	152	157	154	156	159	164	154	156	159	164	154	156	159	164			
MBh	48.3			48.9	50.3	52.4	47.8	48.5	49.9	51.9	46.7	47.3	48.7	50.8	44.6	45.2	46.6	48.7	42.1	42.7	44.1	46.2	39.8	40.4	41.8	43.9	39.8	40.4	41.8	43.9	39.8	40.4	41.8	43.9			
85	1600	S/T	1.00	0.97	0.83	0.69	1.00	0.97	0.84	0.70	1.00	1.00	0.86	0.72	1.00	1.00	0.88	0.74	1.00	1.00	0.90	0.76	1.00	1.00	0.81	0.81	1.00	1.00	0.81	0.81	1.00	1.00	0.81	0.81			
		Δ T	30	28	25	21	30	28	25	21	30	28	25	21	30	28	25	21	30	28	24	21	31	29	26	22	31	29	26	22	31	29	26	22			
		kW	2.49	2.49	2.48	2.50	2.80	2.80	2.79	2.81	3.14	3.14	3.14	3.16	3.52	3.52	3.51	3.53	3.94	3.93	3.93	3.95	4.43	4.42	4.42	4.44	4.43	4.42	4.42	4.44	4.43	4.44	4.43	4.46			
		Amps	10.1	10.1	10.1	10.2	11.5	11.5	11.5	11.6	13.1	13.1	13.1	13.2	14.8	14.8	14.8	14.9	16.7	16.7	16.7	16.8	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.1			
		HiPR	250	251	253	257	288	289	291	295	329	330	331	336	372	373	375	379	419	420	422	426	469	470	471	476	469	470	471	476	469	470	471	476			
		LoPR	126	127	130	135	133	134	137	143	139	141	144	149	145	146	149	154	150	151	154	160	157	158	161	166	157	158	161	166	157	158	161	166			
		MBh	49.3	49.9	51.3	53.4	48.9	49.5	50.9	53.0	47.7	48.3	49.7	51.8	45.6	46.3	47.6	49.7	43.1	43.8	45.1	47.2	40.8	41.5	42.8	44.9	40.8	41.5	42.8	44.9	40.8	41.5	42.8	44.9			
		S/T	1.00	0.97	0.84	0.70	1.00	1.00	0.85	0.71	1.00	1.00	0.87	0.73	1.00	1.00	0.89	0.75	1.00	1.00	0.91	0.77	1.00	1.00	0												

		OUTDOOR AMBIENT TEMPERATURE																																			
		65°F						75°F						85°F						95°F						105°F						115°F					
		ENTERING INDOOR WET BULB TEMPERATURE																																			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71												
70	1750	MBh	57.8	58.6	60.3	-	57.3	58.1	59.8	-	55.8	56.6	58.3	-	53.2	54.0	55.7	-	50.0	50.8	52.5	-	47.1	48.0	49.7	-											
		S/T	0.64	0.57	0.43	-	0.65	0.57	0.43	-	0.67	0.60	0.46	-	0.69	0.62	0.48	-	1.00	0.64	0.50	-	1.00	0.69	0.55	-											
		Δ T	19	17	14	-	19	17	14	-	19	17	14	-	19	17	14	-	19	17	13	-	20	18	15	-											
		kW	3.20	3.20	3.19	-	3.61	3.61	3.60	-	4.06	4.06	4.05	-	4.56	4.55	4.55	-	5.10	5.10	5.09	-	5.75	5.75	5.74	-											
		Amps	12.5	12.4	12.4	-	14.3	14.3	14.3	-	16.4	16.4	16.4	-	18.7	18.6	18.6	-	21.2	21.2	21.1	-	24.1	24.1	24.1	-											
	HI PR	260	261	263	-	301	302	304	-	344	345	346	-	390	391	393	-	439	440	442	-	492	493	495	-												
	LO PR	119	121	124	-	126	128	131	-	133	134	137	-	138	139	142	-	143	145	148	-	150	151	154	-												
70	1890	MBh	58.2	59.0	60.8	-	57.7	58.5	60.3	-	56.2	57.0	58.8	-	53.6	54.5	56.2	-	50.5	51.3	53.0	-	47.6	48.4	50.1	-											
		S/T	0.68	0.60	0.46	-	0.68	0.60	0.47	-	0.71	0.63	0.49	-	0.73	0.65	0.51	-	1.00	0.67	0.53	-	1.00	0.72	0.59	-											
		Δ T	18	17	13	-	18	16	13	-	18	17	13	-	18	16	13	-	18	16	13	-	19	17	14	-											
		kW	3.21	3.21	3.20	-	3.62	3.62	3.61	-	4.08	4.07	4.07	-	4.57	4.56	4.56	-	5.12	5.11	5.11	-	5.76	5.76	5.75	-											
		Amps	12.5	12.5	12.5	-	14.4	14.4	14.3	-	16.5	16.4	16.4	-	18.7	18.7	18.7	-	21.2	21.2	21.2	-	24.2	24.2	24.1	-											
	HI PR	261	262	264	-	302	303	305	-	345	346	348	-	391	392	394	-	441	442	444	-	494	495	497	-												
	LO PR	120	122	125	-	127	129	132	-	134	135	138	-	139	140	143	-	144	146	149	-	151	152	155	-												
2250	MBh	59.7	60.5	62.2	-	59.2	60.0	61.7	-	57.7	58.5	60.2	-	55.1	55.9	57.6	-	51.9	52.7	54.5	-	49.1	49.9	51.6	-												
		S/T	0.72	0.64	0.50	-	0.72	0.65	0.51	-	0.75	0.67	0.54	-	0.77	0.69	0.56	-	1.00	0.72	0.58	-	1.00	0.77	0.63	-											
		Δ T	17	15	12	-	17	15	12	-	17	15	12	-	17	15	12	-	17	15	12	-	18	16	13	-											
		kW	3.24	3.24	3.23	-	3.65	3.64	3.64	-	4.10	4.10	4.09	-	4.59	4.59	4.58	-	5.14	5.14	5.13	-	5.79	5.78	5.78	-											
		Amps	12.6	12.6	12.6	-	14.5	14.5	14.5	-	16.6	16.6	16.5	-	18.8	18.8	18.8	-	21.3	21.3	21.3	-	24.3	24.3	24.2	-											
	HI PR	264	266	267	-	30																															

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																																			
				65°F						75°F						85°F						95°F						105°F						115°F					
				ENTERING INDOOR WET BULB TEMPERATURE																																			
59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71												
80	1750	MBh	58.1	58.9	60.6	63.3	57.6	58.4	60.1	62.7	56.1	56.9	58.6	61.2	53.5	54.3	56.0	58.7	50.4	51.2	52.9	55.5	47.5	48.3	50.0	52.6													
		S/T	0.90	0.82	0.69	0.54	1.00	0.83	0.69	0.55	1.00	0.86	0.72	0.57	1.00	0.88	0.74	0.59	1.00	0.90	0.76	0.62	1.00	1.00	0.81	0.67													
		Δ T	27	25	22	18	27	25	22	18	27	25	22	18	27	25	22	18	27	25	21	18	28	26	22	19													
		kW	3.20	3.20	3.19	3.22	3.61	3.61	3.60	3.63	3.63	4.06	4.06	4.05	4.08	4.55	4.55	4.54	4.58	5.10	5.10	5.09	5.13	5.75	5.75	5.74	5.77												
		Amps	12.5	12.4	12.4	12.6	14.3	14.3	14.3	14.4	14.4	16.4	16.4	16.4	16.5	18.6	18.6	18.6	18.7	21.2	21.1	21.1	21.3	24.1	24.1	24.1	24.2												
	Hi/PR	261	262	264	268	301	303	304	309	344	345	347	352	390	391	393	398	440	441	443	447	493	494	494	496	501													
	LO/PR	120	121	124	129	127	128	131	136	133	135	138	143	143	139	140	143	148	144	145	148	153	150	152	155	160													
	1890	MBh	58.6	59.4	61.1	63.7	58.1	58.9	60.6	63.2	56.6	57.4	59.1	61.7	54.0	54.8	56.5	59.1	50.8	51.6	53.3	56.0	47.9	48.7	50.5	53.1													
		S/T	0.93	0.86	0.72	0.57	1.00	0.86	0.73	0.58	1.00	0.89	0.75	0.61	1.00	0.91	0.77	0.63	1.00	1.00	0.79	0.65	1.00	1.00	0.84	0.70													
		Δ T	26	24	21	18	26	24	21	18	26	25	21	18	26	24	21	18	26	24	21	17	27	25	22	18													
kW		3.21	3.21	3.20	3.24	3.62	3.62	3.61	3.64	3.64	4.08	4.07	4.07	4.10	4.57	4.56	4.56	4.59	5.12	5.11	5.11	5.14	5.76	5.76	5.75	5.78													
Amps		12.5	12.5	12.5	12.6	14.4	14.4	14.3	14.5	14.5	16.5	16.4	16.4	16.6	18.7	18.7	18.7	18.8	21.2	21.2	21.2	21.3	24.2	24.2	24.1	24.3													
2250	Hi/PR	262	263	265	269	303	304	306	310	346	347	348	353	392	393	396	399	441	442	444	449	494	495	495	497	502													
	LO/PR	121	122	125	130	128	129	132	137	134	136	139	144	140	141	144	149	145	146	149	154	151	153	156	161														
	MBh	60.0	60.8	62.6	65.2	59.5	60.3	62.0	64.7	58.0	58.8	60.5	63.2	55.4	56.2	58.0	60.6	52.3	53.1	54.8	57.4	49.4	50.2	51.9	54.5														
	S/T	1.00	0.90	0.76	0.62	1.00	0.91	0.77	0.62	1.00	0.93	0.79	0.65	1.00	0.95	0.81	0.67	1.00	1.00	0.84	0.69	1.00	1.00	0.89	0.74														
	Δ T	25	23	20	16	25	23	20	16	25	23</																												

GSZ160181B* - ASPT29B14A* + TXV

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	23.1	21.7	20.3	18.9	18.0	17.4	15.7	14.2	13.0	12.0	11.4	11.0	10.5	9.4	8.2	7.0	5.9
T/R	20.6	19.5	18.4	17.3	16.7	16.1	14.6	13.1	12.0	11.1	10.5	10.2	9.8	8.7	7.6	6.5	5.4
kW	1.37	1.35	1.34	1.33	1.32	1.31	1.30	1.29	1.27	1.26	1.25	1.24	1.23	1.22	1.21	1.20	1.18
Amps	6.7	6.2	5.7	5.3	5.1	4.9	4.6	4.4	4.1	3.9	3.7	3.6	3.5	3.3	3.1	2.8	2.5
COP	4.95	4.69	4.43	4.17	4.00	3.87	3.55	3.23	2.98	2.80	2.67	2.60	2.50	2.25	1.99	1.72	1.45

GSZ160241B* - ASPT29B14A* + TXV

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	30.9	29.0	27.1	25.2	24.0	23.1	20.9	18.8	17.2	15.9	15.0	14.5	13.9	12.3	10.7	9.1	7.5
T/R	27.5	26.0	24.6	23.1	22.2	21.4	19.4	17.4	15.9	14.7	13.9	13.4	12.8	11.4	9.9	8.4	7.0
kW	1.83	1.81	1.79	1.77	1.76	1.75	1.73	1.71	1.69	1.67	1.65	1.63	1.63	1.61	1.58	1.56	1.54
Amps	9.0	8.2	7.6	7.1	6.8	6.6	6.2	5.8	5.5	5.2	4.9	4.7	4.6	4.3	4.0	3.7	3.3
COP	4.94	4.68	4.43	4.17	4.00	3.87	3.54	3.23	2.98	2.80	2.67	2.60	2.50	2.24	1.98	1.71	1.43

GSZ160301B* - ASPT37C14A* + TXV

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	39.1	36.4	33.9	31.1	29.4	28.0	24.7	21.7	19.2	17.4	16.0	15.2	14.3	11.9	9.5	7.2	4.8
T/R	35.1	32.9	30.7	28.5	27.2	26.0	22.9	20.1	17.8	16.1	14.8	14.1	13.2	11.0	8.8	6.6	4.4
kW	2.42	2.35	2.27	2.20	2.15	2.12	2.05	1.98	1.90	1.83	1.76	1.71	1.68	1.61	1.54	1.46	1.39
Amps	11.0	10.1	9.3	8.7	8.3	8.1	7.6	7.1	6.7	6.4	6.0	5.8	5.7	5.3	4.9	4.5	4.0
COP	4.73	4.55	4.37	4.15	4.00	3.87	3.53	3.21	2.96	2.78	2.66	2.60	2.48	2.16	1.82	1.43	1.01

GSZ160361B* - ASPT37C14A* + TXV

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	44.5	41.9	39.2	36.7	35.0	33.8	30.8	28.0	25.6	23.9	22.7	22.0	21.1	19.0	16.8	14.6	12.5
T/R	39.6	37.6	35.6	33.6	32.4	31.3	28.5	25.9	23.7	22.1	21.0	20.4	19.6	17.6	15.6	13.6	11.5
kW	2.62	2.60	2.59	2.57	2.56	2.56	2.54	2.53	2.52	2.50	2.49	2.48	2.47	2.46	2.45	2.43	2.42
Amps	13.3	12.2	11.3	10.5	10.1	9.8	9.2	8.7	8.2	7.8	7.3	7.1	6.9	6.5	6.0	5.5	5.0
COP	4.99	4.72	4.45	4.18	4.00	3.87	3.55	3.24	2.98	2.80	2.67	2.60	2.50	2.26	2.01	1.76	1.51

Above information is for nominal CFM and 70 degree indoor dry bulb. Instantaneous capacity listed.

Goodman Manufacturing Company, L.P. reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations.

GSZ160421B* - ASPT47D14A* + TXV

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	51.0	47.9	44.9	41.9	40.0	38.6	35.2	31.9	29.2	27.2	25.8	25.0	24.0	21.5	19.0	16.5	14.0
T/R	45.4	43.1	40.7	38.4	37.0	35.8	32.6	29.5	27.0	25.2	23.9	23.1	22.2	19.9	17.6	15.3	13.0
kW	3.31	3.26	3.21	3.16	3.13	3.11	3.05	3.00	2.95	2.90	2.85	2.82	2.80	2.75	2.69	2.64	2.59
Amps	16.4	15.1	14.0	13.0	12.5	12.2	11.4	10.8	10.2	9.6	9.1	8.8	8.6	8.1	7.5	6.9	6.2
COP	4.51	4.31	4.10	3.89	3.75	3.64	3.37	3.11	2.90	2.75	2.65	2.60	2.51	2.29	2.07	1.83	1.58

GSZ160481B* - ASPT49D14A* + TXV

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	62.1	57.9	53.7	49.6	47.0	45.0	40.0	35.5	31.8	29.0	26.9	25.8	24.4	20.9	17.3	13.8	10.3
T/R	55.3	52.0	48.8	45.5	43.5	41.7	37.0	32.8	29.4	26.9	24.9	23.9	22.6	19.3	16.0	12.8	9.5
kW	3.83	3.72	3.62	3.51	3.44	3.40	3.29	3.19	3.08	2.97	2.86	2.80	2.76	2.65	2.54	2.44	2.33
Amps	17.9	16.4	15.2	14.1	13.5	13.2	12.4	11.6	11.0	10.4	9.8	9.5	9.3	8.7	8.1	7.4	6.6
COP	4.75	4.56	4.35	4.14	4.00	3.88	3.56	3.26	3.02	2.86	2.75	2.70	2.59	2.31	2.00	1.66	1.29

GSZ160601B* - CAPF4961D6D* + TXV / MBVC2000AA-1A*

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	76.8	72.1	67.5	62.9	60.0	57.9	52.6	47.5	43.4	40.4	38.2	37.0	35.5	31.6	27.8	24.0	20.1
T/R	68.3	64.8	61.2	57.7	55.6	53.6	48.7	44.0	40.2	37.4	35.4	34.3	32.8	29.3	25.7	22.2	18.6
kW	5.05	4.99	4.92	4.86	4.82	4.79	4.73	4.66	4.60	4.53	4.47	4.43	4.40	4.33	4.27	4.20	4.14
Amps	25.2	23.2	21.4	19.9	19.0	18.5	17.4	16.3	15.4	14.6	13.8	13.3	13.0	12.1	11.3	10.3	9.2
COP	4.45	4.23	4.02	3.80	3.65	3.54	3.26	2.99	2.77	2.61	2.51	2.45	2.36	2.14	1.91	1.67	1.43

Above information is for nominal CFM and 70 degree indoor dry bulb. Instantaneous capacity listed.

Goodman Manufacturing Company, L.P. reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations.

GSZ160181B* + ASPT29B14A* + TXV				
CONDITIONS: 80 °F IBD, 67 °F IWB @ 600 CFM				
OUTDOOR TEM. ° F.	TOTAL BTU/H	SENSIBLE BTU/H	LATENT BTU/H	TOTAL WATTS
75	19,300	14,089	5,211	1,120
80	19,050	14,189	4,862	1,185
85	18,800	14,288	4,512	1,250
90	18,400	14,164	4,236	1,325
95	18,000	14,040	3,960	1,400
100	17,500	13,820	3,680	1,480
105	17,000	13,600	3,400	1,560
110	16,550	14,850	1,700	1,655
115	16,100	16,100	0	1,750
TVA CONDITIONS @ 95° OD DB, 75° ID DB 63° ID WB				
95°	17,400	13,746	3,654	1,400

GSZ160241B* + ASPT29B14A* + TXV				
CONDITIONS: 80 °F IBD, 67 °F IWB @ 800 CFM				
OUTDOOR TEM. ° F.	TOTAL BTU/H	SENSIBLE BTU/H	LATENT BTU/H	TOTAL WATTS
75	25,700	18,761	6,939	1,490
80	25,400	18,919	6,482	1,580
85	25,100	19,076	6,024	1,670
90	24,550	18,898	5,652	1,765
95	24,000	18,720	5,280	1,860
100	23,350	18,440	4,910	1,970
105	22,700	18,160	4,540	2,080
110	22,050	18,175	3,875	2,205
115	21,400	18,190	3,210	2,330
TVA CONDITIONS @ 95° OD DB, 75° ID DB 63° ID WB				
95°	23,100	18,249	4,851	1,860

GSZ160301B* + ASPT37C14A* + TXV				
CONDITIONS: 80 °F IBD, 67 °F IWB @ 975 CFM				
OUTDOOR TEM. ° F.	TOTAL BTU/H	SENSIBLE BTU/H	LATENT BTU/H	TOTAL WATTS
75	30,900	22,557	8,343	1,770
80	30,500	22,717	7,784	1,880
85	30,100	22,876	7,224	1,990
90	29,450	22,670	6,780	2,110
95	28,800	22,464	6,336	2,230
100	28,000	22,112	5,888	2,365
105	27,200	21,760	5,440	2,500
110	26,450	21,803	4,648	2,660
115	25,700	21,845	3,855	2,820
TVA CONDITIONS @ 95° OD DB, 75° ID DB 63° ID WB				
95°	27,800	21,962	5,838	2,240

GSZ160361B* + ASPT37C14A* + TXV				
CONDITIONS: 80 °F IBD, 67 °F IWB @ 1060 CFM				
OUTDOOR TEM. ° F.	TOTAL BTU/H	SENSIBLE BTU/H	LATENT BTU/H	TOTAL WATTS
75	36,700	26,424	10,276	2,090
80	36,250	26,637	9,613	2,225
85	35,800	26,850	8,950	2,360
90	35,000	26,592	8,408	2,505
95	34,200	26,334	7,866	2,650
100	33,250	25,926	7,325	2,815
105	32,300	25,517	6,783	2,980
110	31,400	25,569	5,832	3,170
115	30,500	25,620	4,880	3,360
TVA CONDITIONS @ 95° OD DB, 75° ID DB 63° ID WB				
95°	33,000	25,740	7,260	2,660

GSZ160421B* + ASPT47D14A* + TXV				
CONDITIONS: 80 °F IBD, 67 °F IWB @ 1140 CFM				
OUTDOOR TEM. ° F.	TOTAL BTU/H	SENSIBLE BTU/H	LATENT BTU/H	TOTAL WATTS
75	41,800	28,842	12,958	2,400
80	41,300	28,905	12,395	2,550
85	40,800	28,968	11,832	2,700
90	39,900	28,719	11,181	2,860
95	39,000	28,470	10,530	3,020
100	37,900	28,035	9,865	3,205
105	36,800	27,600	9,200	3,390
110	35,800	27,720	8,080	3,615
115	34,800	27,840	6,960	3,840
TVA CONDITIONS @ 95° OD DB, 75° ID DB 63° ID WB				
95°	37,600	27,824	9,776	3,030

GSZ160481B* + ASPT49D14A* + TXV				
CONDITIONS: 80 °F IBD, 67 °F IWB @ 1400 CFM				
OUTDOOR TEM. ° F.	TOTAL BTU/H	SENSIBLE BTU/H	LATENT BTU/H	TOTAL WATTS
75	48,800	34,160	14,640	2,800
80	48,200	34,454	13,746	2,975
85	47,600	34,748	12,852	3,150
90	46,550	34,437	12,114	3,340
95	45,500	34,125	11,375	3,530
100	44,250	33,618	10,633	3,740
105	43,000	33,110	9,890	3,950
110	41,800	33,201	8,599	4,200
115	40,600	33,292	7,308	4,450
TVA CONDITIONS @ 95° OD DB, 75° ID DB 63° ID WB				
95°	43,900	33,364	10,536	3,530

GSZ160601B* - CAPF4961D6D* + TXV/ MBVC2000AA-1A*				
CONDITIONS: 80 °F IBD, 67 °F IWB @ 1850 CFM				
OUTDOOR TEM. ° F.	TOTAL BTU/H	SENSIBLE BTU/H	LATENT BTU/H	TOTAL WATTS
75	60,600	44,238	16,362	3,610
80	59,850	44,282	15,569	3,840
85	59,100	44,325	14,775	4,070
90	57,800	43,915	13,885	4,315
95	56,500	43,505	12,995	4,560
100	54,900	42,806	12,094	4,835
105	53,300	42,107	11,193	5,110
110	51,900	42,264	9,637	5,430
115	50,500	42,420	8,080	5,750
TVA Conditions @ 95° OD DB, 75° ID DB 63° ID WB				
95°	54,500	42,510	11,990	4,560

ENERGY STAR® CERTIFIED COMBINATIONS [^]

OUTDOOR UNIT	INDOOR UNITS	COOLING RATINGS ^{>}				TVA RATINGS ³		HEATING RATINGS ^{>}			CFM	AHRI #
	COILS/AIR HANDLERS	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0181B*	ASPT25B14A*	17,400	14,000	15.0	12.5	16,800	13,600	17,800	8.5	10,500	580	8331265
	ASPT29B14A*	18,000	14,400	16.0	13.0	17,400	14,200	18,000	9.0	11,000	600	8331264
	AVPTC24B14A*	17,200	13,800	15.0	12.5	16,600	13,400	17,400	8.5	10,000	600	8331269
	CA*F3137*6A*+MBVC1200**-1A*+TXV	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	600	8601428
	CA*F3636*6D*+MBVC1200**-1A*+TXV	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	600	8601426
GSZ16 0241B*	ASPT25B14A*	23,000	18,400	15.0	12.5	22,200	18,000	23,800	8.5	14,000	680	8331271
	ASPT29B14A*	24,000	19,200	16.0	13.0	23,200	18,800	24,000	9.0	14,500	800	8331270
	AVPTC24B14A*	22,800	18,200	15.0	12.5	22,000	17,800	23,000	8.5	14,000	800	8331276
	CA*F3137*6A*+MBVC1200**-1A*+TXV	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	810	8601446
	CA*F3636*6D*+MBVC1200**-1A*+TXV	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8601444
GSZ16 0301B*	ASPT37B14A*	28,400	22,600	15.0	12.5	27,400	22,200	29,000	8.5	15,000	950	8331278
	ASPT37C14A*	28,800	23,000	16.0	13.0	27,800	22,600	29,400	9.5	15,200	975	8331277
	AVPTC30C14A*	28,600	22,800	15.0	12.5	27,600	22,400	29,000	8.5	15,200	940	8331281
	CA*F3743*6D*+MBVC1600**-1A*+TXV	28,600	22,800	16.0	13.0	27,600	22,400	28,600	9.0	15,200	1,010	8601466
GSZ16 0361B*	ASPT37B14A*	33,600	26,200	15.0	12.5	32,400	25,600	34,600	8.5	21,000	1,050	8331283
	ASPT37C14A*	34,200	26,600	16.0	13.0	33,000	26,000	35,000	9.5	22,000	1,060	8331282
	ASPT47D14A*	35,000	27,200	16.0	13.0	33,800	26,600	35,000	9.0	19,000	1,200	8601489
	AVPTC36C14A*	32,600	25,400	15.0	12.5	31,400	24,800	34,000	8.5	21,600	1,100	8331286
	CA*F3743*6D*+MBVC1600**-1A*+TXV	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,080	8601495
	CA*F4961*6D*+MBVC1600**-1A*+TXV	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,080	8601503
GSZ16 0421B*	ASPT47C14B*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	24,000	1,100	201817168
	ASPT47D14A*	39,000	29,400	16.0	13.0	37,600	28,800	40,000	9.0	25,000	1,140	8331287
	ASPT49D14A*	40,000	30,200	16.0	13.0	38,600	29,400	41,000	9.0	25,600	1,320	8602898
	AVPTC42D14A*	39,000	29,400	15.0	12.5	37,600	28,800	40,000	8.5	25,000	1,110	8331290
	AVPTC49D14A*	40,000	28,000	16.0	13.0	38,600	22,700	38,500	9.0	25,000	1,250	8996207
	CA*F4961*6D*+MBVC2000**-1A*+TXV	41,000	30,800	16.0	13.0	39,600	30,200	39,000	9.0	25,000	1,500	8601526
GSZ16 0481B*	ASPT47C14B*	44,500	34,000	15.0	12.5	42,800	33,200	46,500	8.5	25,000	1,425	201817170
	ASPT49D14A*	45,500	34,800	16.0	13.0	43,800	34,000	47,000	9.0	25,800	1,400	8331291
	AVPTC48D14A*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,400	8331294
	CA*F4961*6D*+MBVC2000**-1A*+TXV	45,500	34,800	16.0	13.0	43,800	34,000	48,000	9.0	26,000	1,570	8601537
GSZ16 0601B*	CA*F4961*6D*+MBVC2000**-1A*+TXV	56,500	44,800	16.0	12.5	54,400	43,600	60,000	9.0	37,000	1,890	8560979

[^] Proper sizing and installation of equipment is critical to achieving optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your contractor for details or visit www.energystar.gov. The www.energystar.gov website provides up to date system combinations certified to meet ENERGY STAR requirements.

[>] Rated in accordance with ANSI/AHRI Standard 210/240

¹ Seasonal Energy Efficiency Ratio

² Energy Efficiency Ratio @ 80°F/ 67°F/ 95°F

³ TVA Rating: BTU/h @ 75°F/ 63°F - 95°F

⁴ Rated heating capacity at 47°F outdoor per AHRI 210/240

⁵ HSPF = Heating Seasonal Performance Factor

⁶ Heating capacity at 17°F outdoor

⁷ CFM at High stage

⁸ CFM at Intermediate and low stage

NOTES

- Always check the S&R plate for electrical data on the unit being installed.
- When matching outdoor unit to indoor unit, use the piston supplied with the outdoor unit or that specified on the piston kit chart supplied with the indoor unit.
- EEP - Order from Service Dept. Part No. B13707-38 or new Solid State Board B13707-35S. Part No. B13707-38 is not interchangeable with B13707-35S. The Goodman® Brand gas furnace contains the EEP cooling time delay

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0181B*	ACNF31XX16A*		17,000	13,600	14.0	12.0	16,400	13,400	17,000	8.2	11,900	600	8740462
	ACNF31XX16A*+TXV		17,200	13,800	14.5	12.2	16,600	13,400	17,600	8.5	11,900	600	8740463
	ARUF31B14A*+TXV		17,000	13,600	14.5	12.0	16,400	13,400	17,400	8.2	11,000	560	8331268
	AVPTC25B14A*		17,400	14,000	15.0	12.5	16,800	13,600	17,800	8.5	10,500	640	8996198
	AVPTC29B14A*		17,800	14,200	16.0	13.0	17,200	14,000	18,000	9.0	11,000	585	8996199
	AWUF19XX16A*+TXV		17,000	13,600	14.5	12.0	16,400	13,400	17,400	8.2	10,000	580	8331266
	AWUF31XX16A*+TXV		17,000	13,600	16.0	13.0	16,400	13,400	17,200	8.5	10,000	620	8331267
	CA*F3137*6A*+TXV	G*VC960403BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	610	8327048
	CA*F3137*6A*+TXV	G*VC960603BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	620	8327049
	CA*F3137*6A*+TXV	G*VC960803BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	610	8327050
	CA*F3137*6A*+TXV	A*VC960403BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	610	8327073
	CA*F3137*6A*+TXV	A*VC960603BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	620	8327074
	CA*F3137*6A*+TXV	A*VC960803BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	610	8327075
	CA*F3137*6A*+TXV	G*VM970603BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	620	8332190
	CA*F3137*6A*+TXV	G*VM970803BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	610	8332191
	CA*F3137*6A*+TXV	A*VM970603BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	620	8332209
	CA*F3137*6A*+TXV	A*VM970803BNA*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	610	8332210
	CA*F3137*6A*+TXV	G*VC80604B*B*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	620	8601427
	CA*F3137*6A*+TXV	A*VC80604B*B*	17,600	14,200	16.0	13.0	17,000	13,800	17,600	9.0	10,000	620	8601565
	CA*F3137*6A*+TXV	G*VC80603B*B*	17,600	14,200	15.0	12.5	17,000	13,800	17,600	8.5	10,000	600	9924257
	CA*F3137*6A*+TXV	G*VC80803B*B*	17,600	14,200	15.0	12.5	17,000	13,800	17,600	8.5	10,000	600	9924261
	CA*F3636*6D*+TXV	G*VC960403BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	610	8327045
	CA*F3636*6D*+TXV	G*VC960603BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	620	8327046
	CA*F3636*6D*+TXV	G*VC960803BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	610	8327047
	CA*F3636*6D*+TXV	A*VC960403BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	610	8327070
	CA*F3636*6D*+TXV	A*VC960603BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	620	8327071
	CA*F3636*6D*+TXV	A*VC960803BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	610	8327072
	CA*F3636*6D*+TXV	G*VM970603BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	620	8332188
	CA*F3636*6D*+TXV	G*VM970803BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	610	8332189
	CA*F3636*6D*+TXV	A*VM970603BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	620	8332207
	CA*F3636*6D*+TXV	A*VM970803BNA*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	610	8332208
	CA*F3636*6D*+TXV	G*VC80604B*B*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	620	8601425
	CA*F3636*6D*+TXV	A*VC80604B*B*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	620	8601566
	CA*F3636*6D*+TXV	G*VC80603B*B*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	600	9924258
	CA*F3636*6D*+TXV	G*VC80803B*B*	17,200	13,800	15.0	12.5	16,600	13,400	17,200	8.5	10,000	600	9924262
	CHPF3636B6C*+MBVC1200**-1A*+TXV		17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	600	8601435
	CHPF3636B6C*+TXV	G*VC960403BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601429
	CHPF3636B6C*+TXV	G*VC960603BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601430
	CHPF3636B6C*+TXV	G*VC960803BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601431
	CHPF3636B6C*+TXV	G*VM970603BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601432
	CHPF3636B6C*+TXV	G*VM970803BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601433
	CHPF3636B6C*+TXV	G*VC80604B*B*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	620	8601434
	CHPF3636B6C*+TXV	A*VC80604B*B*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	620	8601567
	CHPF3636B6C*+TXV	A*VC960403BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601568
	CHPF3636B6C*+TXV	A*VC960603BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601569
	CHPF3636B6C*+TXV	A*VC960803BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601570
	CHPF3636B6C*+TXV	A*VM970603BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601571
	CHPF3636B6C*+TXV	A*VM970803BNA*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	610	8601572
	CHPF3636B6C*+TXV	G*VC80603B*B*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	600	9924259
	CHPF3636B6C*+TXV	G*VC80803B*B*	17,400	14,000	15.0	12.5	16,800	13,600	17,400	8.5	10,000	600	9924263
	CSCF3036N6D*+MBVC1200**-1A*+TXV		17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	600	8601442
	CSCF3036N6D*+TXV	G*VC960403BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601436
	CSCF3036N6D*+TXV	G*VC960603BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601437
	CSCF3036N6D*+TXV	G*VC960803BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601438

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS ¹				TVA RATINGS ³		HEATING RATINGS ¹			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0181B* (Contd.)	CSCF3036N6D*+TXV	G*VM970603BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601439
	CSCF3036N6D*+TXV	G*VM970803BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601440
	CSCF3036N6D*+TXV	G*VC80604B*B*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	620	8601441
	CSCF3036N6D*+TXV	A*VC80604B*B*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	620	8601573
	CSCF3036N6D*+TXV	A*VC960403BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601574
	CSCF3036N6D*+TXV	A*VC960603BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601575
	CSCF3036N6D*+TXV	A*VC960803BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601576
	CSCF3036N6D*+TXV	A*VM970603BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601577
	CSCF3036N6D*+TXV	A*VM970803BNA*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	610	8601578
	CSCF3036N6D*+TXV	G*VC80603B*B*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	600	9924260
	CSCF3036N6D*+TXV	G*VC80803B*B*	17,000	13,600	15.0	12.5	16,400	13,400	17,000	8.5	10,000	600	9924264
GSZ16 0241B*	ACNF30XX16D*+TXV		22,400	17,800	14.0	11.5	21,600	17,400	22,800	8.2	14,000	800	8331274
	ACNF31XX16A*		22,400	17,800	14.0	12.0	21,600	17,400	22,200	8.2	14,300	730	8740464
	ACNF31XX16A*+TXV		23,000	18,400	14.5	12.2	22,200	18,000	22,800	8.5	14,500	730	8740465
	ARUF31B14A*+TXV		22,800	18,200	14.5	12.0	22,000	17,800	23,000	8.2	14,500	850	8331275
	ASPT37C14A*		24,000	19,200	16.0	13.0	23,200	18,800	24,000	9.5	14,500	875	8814283
	AVPTC25B14A*		23,000	18,400	15.0	12.5	22,200	18,000	23,800	8.5	14,000	850	8996200
	AVPTC29B14A*		24,000	19,200	16.0	13.0	23,200	18,800	24,000	9.0	14,500	795	8996201
	AWUF25XX16A*+TXV		21,200	16,800	14.0	11.5	20,400	16,400	22,000	8.2	13,500	700	8331272
	AWUF31XX16A*+TXV		22,800	18,200	15.0	12.5	22,000	17,800	23,000	8.5	14,000	845	8331273
	AWUF32XX16A*+TXV		22,800	18,200	15.0	12.5	22,000	17,800	22,000	8.5	14,000	845	9057922
	CA*F3137*6A*+EEP+TXV		22,400	17,800	14.0	11.5	21,600	17,400	23,200	8.2	14,000	800	9122267
	CA*F3137*6A*+MBR1200AA-1A*+TXV		23,000	18,400	14.5	12.0	22,200	18,000	23,600	8.2	14,000	800	8936393
	CA*F3137*6A*+TXV	G*VC960403BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	800	8327054
	CA*F3137*6A*+TXV	G*VC960603BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	815	8327055
	CA*F3137*6A*+TXV	G*VC960803BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	810	8327056
	CA*F3137*6A*+TXV	A*VC960403BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	800	8327079
	CA*F3137*6A*+TXV	A*VC960603BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	815	8327080
	CA*F3137*6A*+TXV	A*VC960803BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	810	8327081
	CA*F3137*6A*+TXV	G*VM970603BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	815	8332194
	CA*F3137*6A*+TXV	G*VM970803BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	810	8332195
	CA*F3137*6A*+TXV	A*VM970603BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	815	8332213
	CA*F3137*6A*+TXV	A*VM970803BNA*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	810	8332214
	CA*F3137*6A*+TXV	G*VC80604B*B*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	815	8601445
	CA*F3137*6A*+TXV	A*VC80604B*B*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	815	8601579
	CA*F3137*6A*+TXV	G*VC80603B*B*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	750	9924265
	CA*F3137*6A*+TXV	G*VC80803B*B*	23,400	18,600	16.0	13.0	22,600	18,200	23,600	9.0	14,000	800	9924269
	CA*F3636*6D*+EEP+TXV		23,000	18,400	14.0	11.5	22,200	18,000	24,000	8.2	14,000	800	9134486
	CA*F3636*6D*+TXV	G*VC960403BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	800	8327051
	CA*F3636*6D*+TXV	G*VC960603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8327052
	CA*F3636*6D*+TXV	G*VC960803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8327053
	CA*F3636*6D*+TXV	A*VC960403BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	800	8327076
	CA*F3636*6D*+TXV	A*VC960603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8327077
	CA*F3636*6D*+TXV	A*VC960803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8327078
	CA*F3636*6D*+TXV	G*VM970603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8332192
	CA*F3636*6D*+TXV	G*VM970803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8332193
	CA*F3636*6D*+TXV	A*VM970603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8332211
	CA*F3636*6D*+TXV	A*VM970803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8332212
	CA*F3636*6D*+TXV	G*VC80604B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8601443
	CA*F3636*6D*+TXV	A*VC80604B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8601580
	CA*F3636*6D*+TXV	G*VC80603B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	750	9924266
	CA*F3636*6D*+TXV	G*VC80803B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	800	9924270
	CA*F3636*6D*+TXV	G*VC80804C*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	800	9924273
	CHPF3636B6C*+MBVC1200**-1A*+TXV		23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	810	8601453

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0241B* (Contd.)	CHPF3636B6C*+TXV	G*VC960403BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	800	8601447
	CHPF3636B6C*+TXV	G*VC960603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	790	8601448
	CHPF3636B6C*+TXV	G*VC960803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	810	8601449
	CHPF3636B6C*+TXV	G*VM970603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	790	8601450
	CHPF3636B6C*+TXV	G*VM970803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	810	8601451
	CHPF3636B6C*+TXV	G*VC80604B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	815	8601452
	CHPF3636B6C*+TXV	A*VC80604B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	815	8601581
	CHPF3636B6C*+TXV	A*VC960403BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	800	8601582
	CHPF3636B6C*+TXV	A*VC960603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	790	8601583
	CHPF3636B6C*+TXV	A*VC960803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	810	8601584
	CHPF3636B6C*+TXV	A*VM970603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	790	8601585
	CHPF3636B6C*+TXV	A*VM970803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	810	8601586
	CHPF3636B6C*+TXV	G*VC80603B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	750	9924267
	CHPF3636B6C*+TXV	G*VC80803B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,400	8.5	14,000	750	9924271
	CSCF3036N6D*+MBVC1200**-1A*+TXV		23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8601460
	CSCF3036N6D*+TXV	G*VC960403BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	800	8601454
	CSCF3036N6D*+TXV	G*VC960603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	790	8601455
	CSCF3036N6D*+TXV	G*VC960803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8601456
	CSCF3036N6D*+TXV	G*VM970603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	790	8601457
	CSCF3036N6D*+TXV	G*VM970803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8601458
	CSCF3036N6D*+TXV	G*VC80604B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8601459
	CSCF3036N6D*+TXV	A*VC80604B*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	815	8601587
	CSCF3036N6D*+TXV	A*VC960403BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	800	8601588
	CSCF3036N6D*+TXV	A*VC960603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	790	8601589
	CSCF3036N6D*+TXV	A*VC960803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8601590
	CSCF3036N6D*+TXV	A*VM970603BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	790	8601591
	CSCF3036N6D*+TXV	A*VM970803BNA*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	810	8601592
	CSCF3036N6D*+TXV	G*VC80603B*B*	23,000	18,400	14.5	12.2	22,200	18,000	23,000	8.2	14,000	750	9924268
	CSCF3036N6D*+TXV	G*VC80803B*B*	23,000	18,400	14.5	12.2	22,200	18,000	23,000	8.2	14,000	800	9924272
	CSCF3036N6D*+TXV	G*VC80804C*B*	23,000	18,400	15.0	12.5	22,200	18,000	23,200	8.5	14,000	800	9924274
GSZ16 0301B*	ACNF30XX16D*+TXV		27,600	22,000	14.0	11.5	26,600	21,600	28,000	8.2	15,200	870	8602896
	ARUF37C14A*+TXV		28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.2	15,200	990	8331280
	ASPT33C14B*		28,600	22,800	15.0	12.5	27,600	22,400	29,000	8.5	17,500	1,000	201817162
	AVPTC33C14A*		28,600	22,800	15.0	12.5	27,600	22,400	29,000	8.5	17,500	965	10207416
	AVPTC37B14A*		28,400	22,600	15.0	12.5	27,400	22,200	29,000	8.5	15,000	925	8996202
	AVPTC37C14A*		28,800	23,000	16.0	13.0	27,800	22,600	29,400	9.0	15,200	930	8996203
	AWUF31XX16A*+TXV		28,000	22,400	15.0	12.5	27,000	21,800	28,000	8.5	15,000	950	8331279
	AWUF32XX16A*+TXV		28,000	22,400	15.0	12.5	27,000	21,800	28,000	8.2	15,000	950	8484190
	CA*F3137*6A*+EEP+TXV		28,600	22,800	14.0	11.5	27,600	22,400	28,600	8.2	15,200	1,000	9122268
	CA*F3137*6A*+MBR1200AA-1A*+TXV		28,000	22,400	14.5	12.0	27,000	21,800	28,600	8.2	15,200	1,020	8936396
	CA*F3137*6A*+TXV	G*VC960403BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,000	8327059
	CA*F3137*6A*+TXV	G*VC960603BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,005	8327060
	CA*F3137*6A*+TXV	G*VC960803BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,020	8327061
	CA*F3137*6A*+TXV	A*VC960403BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,000	8327084
	CA*F3137*6A*+TXV	A*VC960603BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,005	8327085
	CA*F3137*6A*+TXV	A*VC960803BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,020	8327086
	CA*F3137*6A*+TXV	G*VM970603BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,005	8332198
	CA*F3137*6A*+TXV	G*VM970803BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,020	8332199
	CA*F3137*6A*+TXV	A*VM970603BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,005	8332217
	CA*F3137*6A*+TXV	A*VM970803BNA*	28,800	23,000	15.0	12.5	27,800	22,600	29,000	8.5	15,200	1,020	8332218
	CA*F3137*6A*+TXV	G*VC80604B*B*	28,600	22,800	15.0	12.5	27,600	22,400	28,600	8.5	15,200	1,000	8601464
	CA*F3137*6A*+TXV	A*VC80604B*B*	28,600	22,800	15.0	12.5	27,600	22,400	28,600	8.5	15,200	1,000	8601593
	CA*F3137*6A*+TXV	G*VC80603B*B*	28,600	22,800	15.0	12.5	27,600	22,400	28,600	8.5	15,200	1,000	9924275
	CA*F3137*6A*+TXV	G*VC80803B*B*	28,600	22,800	15.0	12.5	27,600	22,400	28,600	8.5	15,200	950	9924280

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0301B* (Contd.)	CA*F3636*6D*+MBVC1600**-1A*+TXV		28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,010	8601463
	CA*F3636*6D*+TXV	G*VC960803BNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	1,020	8327057
	CA*F3636*6D*+TXV	G*VC960804CNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	990	8327058
	CA*F3636*6D*+TXV	A*VC960803BNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	1,020	8327082
	CA*F3636*6D*+TXV	A*VC960804CNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	990	8327083
	CA*F3636*6D*+TXV	G*VM970803BNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	1,020	8332196
	CA*F3636*6D*+TXV	G*VM970804CNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	990	8332197
	CA*F3636*6D*+TXV	A*VM970803BNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	1,020	8332215
	CA*F3636*6D*+TXV	A*VM970804CNA*	28,400	22,600	14.5	12.0	27,400	22,200	28,800	8.5	15,200	990	8332216
	CA*F3636*6D*+TXV	G*VC80604B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,000	8601461
	CA*F3636*6D*+TXV	G*VC80805C*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	990	8601462
	CA*F3636*6D*+TXV	A*VC80604B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,000	8601594
	CA*F3636*6D*+TXV	A*VC80805C*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	990	8601595
	CA*F3636*6D*+TXV	G*VC80603B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,000	9924276
	CA*F3636*6D*+TXV	G*VC80803B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	950	9924281
	CA*F3636*6D*+TXV	G*VC80804C*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,050	9924285
	CA*F3636*6D*+TXV	G*VC80805D*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,000	9924288
	CA*F3743*6D*+TXV	G*VC960804CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	990	8327062
	CA*F3743*6D*+TXV	G*VC961005CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	1,020	8327063
	CA*F3743*6D*+TXV	A*VC960804CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	990	8327087
	CA*F3743*6D*+TXV	A*VC961005CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	1,020	8327088
	CA*F3743*6D*+TXV	G*VM970804CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	990	8332200
	CA*F3743*6D*+TXV	G*VM971005CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	1,020	8332201
	CA*F3743*6D*+TXV	A*VM970804CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	990	8332219
	CA*F3743*6D*+TXV	A*VM971005CNA*	29,200	23,400	16.0	13.0	28,200	22,800	29,200	9.0	15,200	1,020	8332220
	CA*F3743*6D*+TXV	G*VC80805C*B*	28,600	22,800	16.0	13.0	27,600	22,400	28,600	9.0	15,200	990	8601465
	CA*F3743*6D*+TXV	A*VC80805C*B*	28,600	22,800	16.0	13.0	27,600	22,400	28,600	9.0	15,200	990	8601596
	CA*F3743*6D*+TXV	G*VC80805D*B*	28,600	22,800	16.0	13.0	27,600	22,400	28,600	9.0	15,200	1,000	9924289
	CA*F4961*6D*+EEP+TXV		29,000	23,200	14.0	12.0	28,000	22,600	29,200	8.5	18,400	1,000	9084880
	CAPT3743*4A*	G*VC960804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601467
	CAPT3743*4A*	G*VC961005CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601468
	CAPT3743*4A*	G*VM970804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601469
	CAPT3743*4A*	G*VM971005CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601470
	CAPT3743*4A*	G*VC80805C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601471
	CAPT3743*4A*	A*VC80805C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601597
	CAPT3743*4A*	A*VC960804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601598
	CAPT3743*4A*	A*VC961005CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601599
	CAPT3743*4A*	A*VM970804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601600
	CAPT3743*4A*	A*VM971005CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601601
	CAPT3743*4A*	G*VC80805D*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,000	9924290
	CAPT3743*4A*+MBVC1600**-1A*		28,400	22,600	15.5	12.5	27,400	22,200	28,600	8.5	15,200	1,010	8602897
	CHPF3636B6C*+TXV	G*VC960803BNA*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,020	8601472
	CHPF3636B6C*+TXV	G*VM970803BNA*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,020	8601473
	CHPF3636B6C*+TXV	G*VC80604B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,000	8601474
	CHPF3636B6C*+TXV	A*VC80604B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,000	8601602
	CHPF3636B6C*+TXV	A*VC960803BNA*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,020	8601603
	CHPF3636B6C*+TXV	A*VM970803BNA*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,020	8601604
	CHPF3636B6C*+TXV	G*VC80603B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	1,000	9924277
	CHPF3636B6C*+TXV	G*VC80803B*B*	28,000	22,400	14.5	12.0	27,000	21,800	28,000	8.5	15,200	950	9924282
	CHPF3743C6B*+EEP+TXV		27,800	22,200	14.0	12.0	26,800	21,600	28,000	8.2	15,200	1,000	9045601
	CHPF3743C6B*+MBVC1600**-1A*+TXV		28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,010	8601481
	CHPF3743C6B*+TXV	G*VC960803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,020	8601475
	CHPF3743C6B*+TXV	G*VC960804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	990	8601476
	CHPF3743C6B*+TXV	G*VM970803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,020	8601477

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0301B* (Contd.)	CHPF3743C6B*+TXV	G*VM970804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	990	8601478
	CHPF3743C6B*+TXV	G*VC80604B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,000	8601479
	CHPF3743C6B*+TXV	G*VC80805C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	990	8601480
	CHPF3743C6B*+TXV	A*VC80604B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,000	8601605
	CHPF3743C6B*+TXV	A*VC80805C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	990	8601606
	CHPF3743C6B*+TXV	A*VC960803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,020	8601607
	CHPF3743C6B*+TXV	A*VC960804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	990	8601608
	CHPF3743C6B*+TXV	A*VM970803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,020	8601609
	CHPF3743C6B*+TXV	A*VM970804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	990	8601610
	CHPF3743C6B*+TXV	G*VC80603B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,000	9924278
	CHPF3743C6B*+TXV	G*VC80803B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	950	9924283
	CHPF3743C6B*+TXV	G*VC80804C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,000	9924286
	CHPF3743C6B*+TXV	G*VC80805D*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,200	8.5	15,200	1,000	9924291
	CSCF3642N6D*+EEP+TXV		27,800	22,200	14.0	11.5	26,800	21,600	28,000	8.2	15,200	1,000	9045600
	CSCF3642N6D*+MBVC1600**-1A*+TXV		28,400	22,600	15.5	12.5	27,400	22,200	28,600	8.5	15,200	1,010	8601488
	CSCF3642N6D*+TXV	G*VC960803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601482
	CSCF3642N6D*+TXV	G*VC960804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601483
	CSCF3642N6D*+TXV	G*VM970803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601484
	CSCF3642N6D*+TXV	G*VM970804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601485
	CSCF3642N6D*+TXV	G*VC80604B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,000	8601486
	CSCF3642N6D*+TXV	G*VC80805C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601487
	CSCF3642N6D*+TXV	A*VC80604B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,000	8601611
	CSCF3642N6D*+TXV	A*VC80805C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601612
	CSCF3642N6D*+TXV	A*VC960803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601613
	CSCF3642N6D*+TXV	A*VC960804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601614
	CSCF3642N6D*+TXV	A*VM970803BNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,020	8601615
	CSCF3642N6D*+TXV	A*VM970804CNA*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	990	8601616
	CSCF3642N6D*+TXV	G*VC80603B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,000	9924279
	CSCF3642N6D*+TXV	G*VC80803B*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	950	9924284
	CSCF3642N6D*+TXV	G*VC80804C*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,050	9924287
	CSCF3642N6D*+TXV	G*VC80805D*B*	28,400	22,600	15.0	12.5	27,400	22,200	28,600	8.5	15,200	1,000	9924292
GSZ16 0361B*	ARUF37D14A*+TXV		33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.2	22,000	1,040	8331285
	ASPT39C14B*		32,600	25,400	15.0	12.5	31,400	24,800	34,200	8.2	20,400	1,220	201817165
	AVPTC37B14A*		33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	20,000	1,080	8996204
	AVPTC37C14A*		34,200	26,600	16.0	13.0	33,000	26,000	35,000	9.0	21,000	1,130	8996205
	AVPTC39C14A*		32,600	25,400	15.0	12.5	31,400	24,800	34,200	8.2	20,400	1,120	10207417
	AWUF37XX16B*+TXV		32,400	25,200	14.0	11.5	31,200	24,600	33,400	8.2	19,600	1,100	8331284
	CA*F3137*6A*+TXV	G*VC960403BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,080	8327064
	CA*F3137*6A*+TXV	G*VC960603BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,070	8327065
	CA*F3137*6A*+TXV	G*VC960803BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,100	8327066
	CA*F3137*6A*+TXV	A*VC960403BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,080	8327089
	CA*F3137*6A*+TXV	A*VC960603BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,070	8327090
	CA*F3137*6A*+TXV	A*VC960803BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,100	8327091
	CA*F3137*6A*+TXV	G*VM970603BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,070	8332202
	CA*F3137*6A*+TXV	G*VM970803BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,100	8332203
	CA*F3137*6A*+TXV	A*VM970603BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,070	8332221
	CA*F3137*6A*+TXV	A*VM970803BNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,600	8.5	21,000	1,100	8332222
	CA*F3137*6A*+TXV	G*VC80604B*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,000	1,095	8601490
	CA*F3137*6A*+TXV	A*VC80604B*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,000	1,095	8601617
	CA*F3137*6A*+TXV	G*VC80603B*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,000	1,100	9924293
	CA*F3137*6A*+TXV	G*VC80803B*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,000	1,050	9924297
	CA*F3743*6D*+EEP+TXV		32,600	25,400	14.0	11.5	31,400	24,800	35,000	8.2	19,600	1,090	9101389
	CA*F3743*6D*+TXV	G*VC960804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,080	8601491
	CA*F3743*6D*+TXV	G*VM970804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,080	8601492

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0361B* (Contd.)	CA*F3743*6D*+TXV	G*VC80604B*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,095	8601493
	CA*F3743*6D*+TXV	G*VC80805C*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,075	8601494
	CA*F3743*6D*+TXV	A*VC80604B*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,095	8601618
	CA*F3743*6D*+TXV	A*VC80805C*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,075	8601619
	CA*F3743*6D*+TXV	A*VC960804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,080	8601620
	CA*F3743*6D*+TXV	A*VM970804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,080	8601621
	CA*F3743*6D*+TXV	G*VC80804C*B*	33,400	26,000	16.0	12.5	32,200	25,400	34,000	8.5	21,600	1,150	9924301
	CA*F3743*6D*+TXV	G*VC80805D*B*	33,400	26,000	15.0	12.5	32,200	25,400	34,000	8.5	21,600	1,100	9924305
	CA*F4961*6D*+MBR1600AA-1A*+TXV		33,400	26,000	14.5	12.0	32,200	25,400	34,000	8.2	22,000	1,030	8936394
	CA*F4961*6D*+MBVC2000**-1A*+TXV		34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.5	19,000	1,080	9007185
	CA*F4961*6D*+TXV	G*VC960804CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,090	8327067
	CA*F4961*6D*+TXV	G*VC961005CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,110	8327068
	CA*F4961*6D*+TXV	A*VC960804CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,090	8327092
	CA*F4961*6D*+TXV	A*VC961005CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,110	8327093
	CA*F4961*6D*+TXV	G*VM970804CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,090	8332204
	CA*F4961*6D*+TXV	G*VM971005CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,110	8332205
	CA*F4961*6D*+TXV	A*VM970804CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,090	8332223
	CA*F4961*6D*+TXV	A*VM971005CNA*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,110	8332224
	CA*F4961*6D*+TXV	G*VC80805C*B*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,090	8601501
	CA*F4961*6D*+TXV	G*VC81005C*B*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,110	8601502
	CA*F4961*6D*+TXV	A*VC80805C*B*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,090	8601622
	CA*F4961*6D*+TXV	A*VC81005C*B*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,110	8601623
	CA*F4961*6D*+TXV	G*VC80805D*B*	34,000	26,400	16.0	13.0	32,800	25,800	35,000	9.0	22,000	1,100	9924306
	CAPT3743*4A*	G*VC960804CNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,080	8601496
	CAPT3743*4A*	G*VM970804CNA*	30,000	23,400	14.5	12.0	29,000	22,800	34,000	8.5	21,600	1,080	8601497
	CAPT3743*4A*	G*VC80604B*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,095	8601498
	CAPT3743*4A*	G*VC80805C*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,075	8601499
	CAPT3743*4A*	A*VC80604B*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,095	8601624
	CAPT3743*4A*	A*VC80805C*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,075	8601625
	CAPT3743*4A*	A*VC960804CNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,080	8601626
	CAPT3743*4A*	A*VM970804CNA*	30,000	23,400	14.5	12.0	29,000	22,800	34,000	8.5	21,600	1,080	8601627
	CAPT3743*4A*	G*VC80804C*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,150	9924302
	CAPT3743*4A*	G*VC80805D*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,100	9924307
	CAPT3743*4A*+MBVC1600**-1A*		33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,600	1,080	8601500
	CAPT3743*4A*+MBVC2000**-1A*		32,800	25,400	16.0	13.0	31,600	24,800	34,000	9.5	22,200	1,170	9084879
	CAPT4961*4A*	G*VC960804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,090	8601504
	CAPT4961*4A*	G*VC961005CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,110	8601505
	CAPT4961*4A*	G*VM970804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,090	8601506
	CAPT4961*4A*	G*VM971005CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,110	8601507
	CAPT4961*4A*	A*VC960804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,090	8601628
	CAPT4961*4A*	A*VC961005CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,110	8601629
	CAPT4961*4A*	A*VM970804CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,090	8601630
	CAPT4961*4A*	A*VM971005CNA*	33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,110	8601631
	CAPT4961*4A*+MBVC1600**-1A*		33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	22,000	1,080	8601508
	CHPF3636B6C*+TXV	G*VC960803BNA*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,100	8601509
	CHPF3636B6C*+TXV	G*VM970803BNA*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,100	8601510
	CHPF3636B6C*+TXV	G*VC80604B*B*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,095	8601511
	CHPF3636B6C*+TXV	A*VC80604B*B*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,095	8601632
	CHPF3636B6C*+TXV	A*VC960803BNA*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,100	8601633
	CHPF3636B6C*+TXV	A*VM970803BNA*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,100	8601634
	CHPF3636B6C*+TXV	G*VC80603B*B*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,100	9924294
	CHPF3636B6C*+TXV	G*VC80803B*B*	32,000	24,800	14.5	12.0	30,800	24,200	34,200	8.5	21,000	1,050	9924298
	CHPF3743C6B*+MBVC1600**-1A*+TXV		33,400	26,000	15.0	12.5	32,200	25,400	34,400	8.5	21,400	1,080	8601518
	CHPF3743C6B*+TXV	G*VC960803BNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,100	8601512

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0361B* (Contd.)	CHPF3743C6B*+TXV	G*VC960804CNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,080	8601513
	CHPF3743C6B*+TXV	G*VM970803BNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,100	8601514
	CHPF3743C6B*+TXV	G*VM970804CNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,080	8601515
	CHPF3743C6B*+TXV	G*VC80604B*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,095	8601516
	CHPF3743C6B*+TXV	G*VC80805C*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,400	1,075	8601517
	CHPF3743C6B*+TXV	A*VC80604B*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,095	8601635
	CHPF3743C6B*+TXV	A*VC80805C*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,400	1,075	8601636
	CHPF3743C6B*+TXV	A*VC960803BNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,100	8601637
	CHPF3743C6B*+TXV	A*VC960804CNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,080	8601638
	CHPF3743C6B*+TXV	A*VM970803BNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,100	8601639
	CHPF3743C6B*+TXV	A*VM970804CNA*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,080	8601640
	CHPF3743C6B*+TXV	G*VC80603B*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,400	1,100	9924295
	CHPF3743C6B*+TXV	G*VC80803B*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,400	1,050	9924299
	CHPF3743C6B*+TXV	G*VC80804C*B*	33,000	25,600	14.5	12.0	31,800	25,000	34,000	8.5	21,400	1,100	9924303
	CHPF3743C6B*+TXV	G*VC80805D*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,400	1,200	9924308
	CHPF3743D6B*+MBVC2000**-1A*+TXV		33,400	26,000	16.0	13.0	32,200	25,400	34,400	9.0	18,000	1,080	9007184
	CSCF3642N6D*+MBVC1600**-1A*+TXV		33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,080	8601525
	CSCF3642N6D*+TXV	G*VC960803BNA*	32,800	25,400	14.5	12.0	31,600	24,800	34,600	8.5	21,600	1,100	8601519
	CSCF3642N6D*+TXV	G*VC960804CNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,080	8601520
	CSCF3642N6D*+TXV	G*VM970803BNA*	32,800	25,400	14.5	12.0	31,600	24,800	34,600	8.5	21,600	1,100	8601521
	CSCF3642N6D*+TXV	G*VM970804CNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,080	8601522
	CSCF3642N6D*+TXV	G*VC80604B*B*	32,800	25,400	14.5	12.0	31,600	24,800	34,600	8.5	21,600	1,095	8601523
	CSCF3642N6D*+TXV	G*VC80805C*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,075	8601524
	CSCF3642N6D*+TXV	A*VC80604B*B*	32,800	25,400	14.5	12.0	31,600	24,800	34,600	8.5	21,600	1,095	8601641
	CSCF3642N6D*+TXV	A*VC80805C*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,075	8601642
	CSCF3642N6D*+TXV	A*VC960803BNA*	32,800	25,400	14.5	12.0	31,600	24,800	34,600	8.5	21,600	1,100	8601643
	CSCF3642N6D*+TXV	A*VC960804CNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,080	8601644
	CSCF3642N6D*+TXV	A*VM970803BNA*	32,800	25,400	14.5	12.0	31,600	24,800	34,600	8.5	21,600	1,100	8601645
	CSCF3642N6D*+TXV	A*VM970804CNA*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,080	8601646
	CSCF3642N6D*+TXV	G*VC80603B*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,100	9924296
	CSCF3642N6D*+TXV	G*VC80803B*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,050	9924300
	CSCF3642N6D*+TXV	G*VC80804C*B*	32,800	25,400	14.5	12.0	31,600	24,800	34,600	8.5	21,600	1,150	9924304
	CSCF3642N6D*+TXV	G*VC80805D*B*	33,000	25,600	15.0	12.5	31,800	25,000	34,000	8.5	21,600	1,100	9924309
GSZ16 0421B*	ARUF47D14A*+TXV		38,500	29,000	14.5	12.0	37,200	28,400	40,000	8.5	25,600	1,200	8331289
	ASPT49C14A*		38,500	29,000	14.5	12.2	37,200	28,400	39,500	8.2	25,200	1,200	10207406
	AVPTC49C14A*		38,500	29,000	14.5	12.2	37,200	28,400	39,500	8.2	25,200	1,200	10207418
	AVPTC59C14A*		38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	24,000	1,250	8996206
	CA*F3743*6D*+EEP+TXV		38,000	28,600	14.0	11.5	36,600	28,000	39,000	8.2	25,600	1,200	9101390
	CA*F3743*6D*+TXV	G*VC960804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602899
	CA*F3743*6D*+TXV	G*VC961005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602900
	CA*F3743*6D*+TXV	G*VM970804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602901
	CA*F3743*6D*+TXV	G*VM971005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602902
	CA*F3743*6D*+TXV	G*VC80805C*B*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,190	8602903
	CA*F3743*6D*+TXV	G*VC81005C*B*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,170	8602904
	CA*F3743*6D*+TXV	A*VC80805C*B*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,190	8602933
	CA*F3743*6D*+TXV	A*VC81005C*B*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,170	8602934
	CA*F3743*6D*+TXV	A*VC960804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602935
	CA*F3743*6D*+TXV	A*VC961005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602936
	CA*F3743*6D*+TXV	A*VM970804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602937
	CA*F3743*6D*+TXV	A*VM971005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602938
	CA*F3743*6D*+TXV	G*VC80805D*B*	38,500	29,000	15.0	12.5	37,200	28,400	40,500	8.5	25,600	1,350	9924310
	CA*F4860*6D*+EEP+TXV		39,000	29,400	14.0	11.5	37,600	28,800	39,000	8.2	25,600	1,200	9101391
	CA*F4961*6D*+EEP+TXV		39,000	29,400	14.0	12.0	37,600	28,800	39,000	8.5	23,000	1,250	9084881

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0421B* (Contd.)	CA*F4961*6D*+MBR1600AA-1A*+TXV		39,500	29,800	14.5	12.0	38,000	29,000	40,000	8.5	25,400	1,275	8936397
	CA*F4961*6D*+TXV	G*VC960804CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8327096
	CA*F4961*6D*+TXV	G*VC961005CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8327097
	CA*F4961*6D*+TXV	A*VC960804CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8327098
	CA*F4961*6D*+TXV	A*VC961005CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8327099
	CA*F4961*6D*+TXV	G*VM970804CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8332226
	CA*F4961*6D*+TXV	G*VM971005CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8332227
	CA*F4961*6D*+TXV	A*VM970804CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8332228
	CA*F4961*6D*+TXV	A*VM971005CNA*	39,500	29,800	16.0	13.0	38,000	29,000	40,500	9.0	25,600	1,165	8332229
	CAPT3743*4A*	G*VC960804CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602905
	CAPT3743*4A*	G*VC961005CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602906
	CAPT3743*4A*	G*VM970804CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602907
	CAPT3743*4A*	G*VM971005CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602908
	CAPT3743*4A*	G*VC80805C*B*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,190	8602909
	CAPT3743*4A*	G*VC81005C*B*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,170	8602910
	CAPT3743*4A*	A*VC80805C*B*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,190	8602939
	CAPT3743*4A*	A*VC81005C*B*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,170	8602940
	CAPT3743*4A*	A*VC960804CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602941
	CAPT3743*4A*	A*VC961005CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602942
	CAPT3743*4A*	A*VM970804CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,185	8602943
	CAPT3743*4A*	A*VM971005CNA*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,180	8602944
	CAPT3743*4A*	G*VC80805D*B*	38,500	29,000	14.5	12.5	37,200	28,400	40,500	8.5	25,600	1,350	9924311
	CAPT4961*4A*	G*VC960804CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602911
	CAPT4961*4A*	G*VC961005CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602912
	CAPT4961*4A*	G*VM970804CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602913
	CAPT4961*4A*	G*VM971005CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602914
	CAPT4961*4A*	A*VC960804CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602945
	CAPT4961*4A*	A*VC961005CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602946
	CAPT4961*4A*	A*VM970804CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602947
	CAPT4961*4A*	A*VM971005CNA*	39,500	29,800	15.0	12.5	38,000	29,000	40,000	8.5	25,600	1,165	8602948
	CAPT4961*4A*+MBVC2000**-1A*		41,000	30,800	15.5	13.0	39,600	30,200	39,000	9.0	25,000	1,500	8601527
	CHPF3743C6B*+TXV	G*VC960804CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,185	8602921
	CHPF3743C6B*+TXV	G*VC961005CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,180	8602922
	CHPF3743C6B*+TXV	G*VM970804CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,185	8602923
	CHPF3743C6B*+TXV	G*VM971005CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,180	8602924
	CHPF3743C6B*+TXV	G*VC80805C*B*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,190	8602925
	CHPF3743C6B*+TXV	G*VC81005C*B*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,170	8602926
	CHPF3743C6B*+TXV	A*VC80805C*B*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,190	8602949
	CHPF3743C6B*+TXV	A*VC81005C*B*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,170	8602950
	CHPF3743C6B*+TXV	A*VC960804CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,185	8602951
	CHPF3743C6B*+TXV	A*VC961005CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,180	8602952
	CHPF3743C6B*+TXV	A*VM970804CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,185	8602953
	CHPF3743C6B*+TXV	A*VM971005CNA*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,180	8602954
	CHPF3743C6B*+TXV	G*VC80805D*B*	38,500	29,000	14.5	12.0	37,200	28,400	39,500	8.5	25,600	1,300	9924312
	CHPF3743D6B*+MBVC2000**-1A*+TXV		38,500	29,000	15.5	12.5	37,200	28,400	39,500	8.5	25,000	1,170	8601528
	CHPF3743D6B*+TXV	G*VC960804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,185	8602915
	CHPF3743D6B*+TXV	G*VC961005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,180	8602916
	CHPF3743D6B*+TXV	G*VM970804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,185	8602917
	CHPF3743D6B*+TXV	G*VM971005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,180	8602918
	CHPF3743D6B*+TXV	G*VC80805C*B*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,190	8602919
	CHPF3743D6B*+TXV	G*VC81005C*B*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,170	8602920
	CHPF3743D6B*+TXV	A*VC80805C*B*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,190	8602955
	CHPF3743D6B*+TXV	A*VC81005C*B*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,170	8602956
	CHPF3743D6B*+TXV	A*VC960804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,185	8602957

See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0421B* (Contd.)	CHPF3743D6B*+TXV	A*VC961005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,180	8602958
	CHPF3743D6B*+TXV	A*VM970804CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,185	8602959
	CHPF3743D6B*+TXV	A*VM971005CNA*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,180	8602960
	CHPF3743D6B*+TXV	G*VC80805D*B*	38,500	29,000	15.0	12.5	37,200	28,400	39,500	8.5	25,600	1,350	9924313
	CHPF4860D6D*+MBVC2000**-1A*+TXV		38,500	29,000	16.0	13.0	37,200	28,400	39,500	9.0	25,000	1,170	8601529
	CSCF3642N6D*+MBVC2000**-1A*+TXV		38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,000	1,170	8601530
	CSCF3642N6D*+TXV	G*VC960804CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,185	8602927
	CSCF3642N6D*+TXV	G*VC961005CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,180	8602928
	CSCF3642N6D*+TXV	G*VM970804CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,185	8602929
	CSCF3642N6D*+TXV	G*VM971005CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,180	8602930
	CSCF3642N6D*+TXV	G*VC80805C*B*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,190	8602931
	CSCF3642N6D*+TXV	G*VC81005C*B*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,170	8602932
	CSCF3642N6D*+TXV	A*VC80805C*B*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,190	8602961
	CSCF3642N6D*+TXV	A*VC81005C*B*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,170	8602962
	CSCF3642N6D*+TXV	A*VC960804CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,185	8602963
	CSCF3642N6D*+TXV	A*VC961005CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,180	8602964
	CSCF3642N6D*+TXV	A*VM970804CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,185	8602965
	CSCF3642N6D*+TXV	A*VM971005CNA*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,180	8602966
	CSCF3642N6D*+TXV	G*VC80805D*B*	38,000	28,600	15.0	12.0	36,600	28,000	40,500	8.5	25,600	1,350	9924314
GSZ16 0481B*	ARUF61D14A*+TXV		44,000	33,800	14.5	12.0	42,400	33,000	47,000	8.5	25,600	1,400	8331293
	ASPT47D14A*		45,000	34,400	15.0	12.5	43,400	33,600	45,000	8.5	24,000	1,425	9057590
	ASPT49C14A*		44,000	33,800	14.5	12.5	42,400	33,000	46,500	8.5	25,000	1,395	10207407
	ASPT61D14A*		45,500	34,800	16.0	13.0	43,800	34,000	47,000	9.0	25,800	1,400	8693537
	AVPTC49C14A*		44,000	33,800	14.5	12.5	42,400	33,000	46,500	8.5	25,000	1,420	10207419
	AVPTC59C14A*		44,500	34,000	15.0	12.5	42,800	33,200	46,500	8.5	25,000	1,485	8996208
	AVPTC61D14A*		45,500	34,800	16.0	13.0	43,800	34,000	46,000	9.5	25,000	1,455	8996209
	CA*F4860*6D*+EEP+TXV		45,000	34,400	14.5	12.0	43,400	33,600	46,000	8.5	26,000	1,400	9134487
	CA*F4961*6D*+MBR1600AA-1A*+TXV		44,000	33,800	14.5	12.0	42,400	33,000	47,000	8.5	26,000	1,475	8936395
	CA*F4961*6D*+TXV	G*VC961205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	9.0	26,000	1,430	8327069
	CA*F4961*6D*+TXV	A*VC961205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	9.0	26,000	1,430	8327094
	CA*F4961*6D*+TXV	G*VM971205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	9.0	26,000	1,430	8332206
	CA*F4961*6D*+TXV	A*VM971205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	9.0	26,000	1,430	8332225
	CA*F4961*6D*+TXV	G*VC960804CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,380	8601531
	CA*F4961*6D*+TXV	G*VC961005CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,430	8601532
	CA*F4961*6D*+TXV	G*VM970804CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,380	8601533
	CA*F4961*6D*+TXV	G*VM971005CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,430	8601534
	CA*F4961*6D*+TXV	G*VC80805C*B*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,400	8601535
	CA*F4961*6D*+TXV	G*VC81005C*B*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,380	8601536
	CA*F4961*6D*+TXV	A*VC80805C*B*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,400	8601647
	CA*F4961*6D*+TXV	A*VC81005C*B*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,380	8601648
	CA*F4961*6D*+TXV	A*VC960804CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,380	8601649
	CA*F4961*6D*+TXV	A*VC961005CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,430	8601650
	CA*F4961*6D*+TXV	A*VM970804CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,380	8601651
	CA*F4961*6D*+TXV	A*VM971005CNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,430	8601652
	CA*F4961*6D*+TXV	G*VC80805D*B*	44,500	34,000	15.0	12.5	42,800	33,200	47,500	8.5	26,000	1,500	9924315
	CAPT4961*4A*	G*VC960804CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,380	8601538
	CAPT4961*4A*	G*VC961005CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,430	8601539
	CAPT4961*4A*	G*VC961205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,000	9.0	26,000	1,430	8601540
	CAPT4961*4A*	G*VM970804CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,380	8601541
	CAPT4961*4A*	G*VM971005CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,430	8601542
	CAPT4961*4A*	G*VM971205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,000	9.0	26,000	1,430	8601543
	CAPT4961*4A*	G*VC80805C*B*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,400	8601544
	CAPT4961*4A*	G*VC81005C*B*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,380	8601545
	CAPT4961*4A*	A*VC80805C*B*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,400	8601653

See Notes on Page 32.


OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	Hi ⁴	HSPF ⁵	Low ⁶		
GSZ16 0481B* (Contd.)	CAPT4961*4A*	A*VC81005C*B*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,380	8601654
	CAPT4961*4A*	A*VC960804CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,380	8601655
	CAPT4961*4A*	A*VC961005CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,430	8601656
	CAPT4961*4A*	A*VC961205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,000	9.0	26,000	1,430	8601657
	CAPT4961*4A*	A*VM970804CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,380	8601658
	CAPT4961*4A*	A*VM971005CNA*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,430	8601659
	CAPT4961*4A*	A*VM971205DNA*	44,500	34,000	15.0	12.5	42,800	33,200	47,000	9.0	26,000	1,430	8601660
	CAPT4961*4A*	G*VC80805D*B*	44,500	34,000	14.5	12.0	42,800	33,200	47,000	8.5	26,000	1,500	9924316
	CAPT4961*4A*+MBVC2000**-1A*		45,500	34,800	15.5	12.5	43,800	34,000	47,500	9.0	26,000	1,570	8601546
	CHPF4860D6D*+MBVC2000**-1A*+TXV		44,500	34,000	15.5	12.5	42,800	33,200	47,500	9.0	25,800	1,570	8601555
	CHPF4860D6D*+TXV	G*VC960804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601547
	CHPF4860D6D*+TXV	G*VC961005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601548
	CHPF4860D6D*+TXV	G*VC961205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601549
	CHPF4860D6D*+TXV	G*VM970804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601550
	CHPF4860D6D*+TXV	G*VM971005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601551
	CHPF4860D6D*+TXV	G*VM971205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601552
	CHPF4860D6D*+TXV	G*VC80805C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,400	8601553
	CHPF4860D6D*+TXV	G*VC81005C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601554
	CHPF4860D6D*+TXV	A*VC80805C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,400	8601661
	CHPF4860D6D*+TXV	A*VC81005C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601662
	CHPF4860D6D*+TXV	A*VC960804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601663
	CHPF4860D6D*+TXV	A*VC961005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601664
	CHPF4860D6D*+TXV	A*VC961205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601665
	CHPF4860D6D*+TXV	A*VM970804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601666
	CHPF4860D6D*+TXV	A*VM971005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601667
	CHPF4860D6D*+TXV	A*VM971205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601668
	CHPF4860D6D*+TXV	G*VC80805D*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,500	9924317
	CSCF4860N6D*+MBVC2000**-1A*+TXV		44,500	34,000	15.5	12.5	42,800	33,200	47,500	9.0	25,800	1,570	8601564
	CSCF4860N6D*+TXV	G*VC960804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601556
	CSCF4860N6D*+TXV	G*VC961005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601557
	CSCF4860N6D*+TXV	G*VC961205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601558
	CSCF4860N6D*+TXV	G*VM970804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601559
	CSCF4860N6D*+TXV	G*VM971005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601560
	CSCF4860N6D*+TXV	G*VM971205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601561
	CSCF4860N6D*+TXV	G*VC80805C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,400	8601562
	CSCF4860N6D*+TXV	G*VC81005C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601563
	CSCF4860N6D*+TXV	A*VC80805C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,400	8601669
	CSCF4860N6D*+TXV	A*VC81005C*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601670
	CSCF4860N6D*+TXV	A*VC960804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601671
	CSCF4860N6D*+TXV	A*VC961005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601672
	CSCF4860N6D*+TXV	A*VC961205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601673
	CSCF4860N6D*+TXV	A*VM970804CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,380	8601674
	CSCF4860N6D*+TXV	A*VM971005CNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601675
	CSCF4860N6D*+TXV	A*VM971205DNA*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,430	8601676
	CSCF4860N6D*+TXV	G*VC80805D*B*	44,000	33,800	15.0	12.5	42,400	33,000	47,000	8.5	25,800	1,500	9924318
GSZ16 0601B*	AVPTC60D14A*		54,000	42,800	15.5	11.5	52,000	41,800	58,500	9.5	37,000	1,810	8560970
	AVPTC61D14A*		55,000	43,600	16.0	12.5	53,000	42,600	60,000	9.5	32,000	1,810	8996210
	CA*F4961*6D*+TXV	G*VC961005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560971
	CA*F4961*6D*+TXV	G*VM971005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560973
	CA*F4961*6D*+TXV	A*VC961005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560975
	CA*F4961*6D*+TXV	A*VM971005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560977
	CA*F4961*6D*+TXV	G*VC961205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560980
	CA*F4961*6D*+TXV	G*VM971205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560982
	CA*F4961*6D*+TXV	A*VC961205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560984


See Notes on Page 32.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS [^]				TVA RATINGS ³		HEATING RATINGS [^]			CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL	SENS.	SEER ¹	EER ²	TOTAL	SENS.	HI ⁴	HSPF ⁵	Low ⁶		
GSZ16 0601B* (Contd.)	CA*F4961*6D*+TXV	A*VM971205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560986
	CA*F4961*6D*+TXV	G*VC80805C*B*	54,000	42,800	15.0	11.3	52,000	41,800	60,000	9.0	34,000	1,820	8738083
	CA*F4961*6D*+TXV	G*VC81005C*B*	54,000	42,800	15.0	11.3	52,000	41,800	60,000	9.0	34,000	1,790	8738084
	CA*F4961*6D*+TXV	A*VC80805C*B*	54,000	42,800	15.0	11.3	52,000	41,800	60,000	9.0	34,000	1,820	8738099
	CA*F4961*6D*+TXV	A*VC81005C*B*	54,000	42,800	15.0	11.3	52,000	41,800	60,000	9.0	34,000	1,790	8738100
	CA*F4961*6D*+TXV	G*VC80805D*B*	54,000	42,800	15.0	11.3	52,000	41,800	60,000	9.0	34,000	1,650	9924319
	CAPT4961*4A*	G*VC961005CNA*	54,000	42,800	14.5	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560972
	CAPT4961*4A*	G*VM971005CNA*	54,000	42,800	14.5	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560974
	CAPT4961*4A*	A*VC961005CNA*	54,000	42,800	14.5	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560976
	CAPT4961*4A*	A*VM971005CNA*	54,000	42,800	14.5	11.5	52,000	41,800	58,000	8.5	37,000	1,750	8560978
	CAPT4961*4A*	G*VC961205DNA*	54,500	43,200	15.0	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560981
	CAPT4961*4A*	G*VM971205DNA*	54,500	43,200	15.0	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560983
	CAPT4961*4A*	A*VC961205DNA*	54,500	43,200	15.0	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560985
	CAPT4961*4A*	A*VM971205DNA*	54,500	43,200	15.0	11.5	52,600	42,200	58,500	8.5	37,000	1,885	8560987
	CAPT4961*4A*	G*VC80805C*B*	54,000	42,800	14.5	11.3	52,000	41,800	60,000	9.0	34,000	1,820	8738085
	CAPT4961*4A*	G*VC81005C*B*	54,000	42,800	14.5	11.3	52,000	41,800	60,000	9.0	34,000	1,790	8738086
	CAPT4961*4A*	A*VC80805C*B*	54,000	42,800	14.5	11.3	52,000	41,800	60,000	9.0	34,000	1,820	8738101
	CAPT4961*4A*	A*VC81005C*B*	54,000	42,800	14.5	11.3	52,000	41,800	60,000	9.0	34,000	1,790	8738102
	CAPT4961*4A*	G*VC80805D*B*	54,000	42,800	14.5	11.3	52,000	41,800	60,000	9.0	34,000	1,650	9924320
	CHPF4860D6D*+MBVC2000**~1A*+TXV		54,000	42,800	15.5	12.0	52,000	41,800	58,000	8.5	32,000	1,890	8669638
	CHPF4860D6D*+TXV	G*VC961005CNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,725	8738087
	CHPF4860D6D*+TXV	G*VM971005CNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,725	8738088
	CHPF4860D6D*+TXV	G*VC961205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,880	8738089
	CHPF4860D6D*+TXV	G*VM971205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,880	8738090
	CHPF4860D6D*+TXV	G*VC80805C*B*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,820	8738091
	CHPF4860D6D*+TXV	G*VC81005C*B*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,790	8738092
	CHPF4860D6D*+TXV	A*VC961005CNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,725	8738103
	CHPF4860D6D*+TXV	A*VM971005CNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,725	8738104
	CHPF4860D6D*+TXV	A*VC961205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,880	8738105
	CHPF4860D6D*+TXV	A*VM971205DNA*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,880	8738106
	CHPF4860D6D*+TXV	A*VC80805C*B*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,820	8738107
	CHPF4860D6D*+TXV	A*VC81005C*B*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,790	8738108
	CHPF4860D6D*+TXV	G*VC80805D*B*	54,500	43,200	15.5	11.5	52,600	42,200	60,000	9.0	34,000	1,650	9924321
	CSCF4860N6D*+TXV	G*VC961005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,725	8738093
	CSCF4860N6D*+TXV	G*VM971005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,725	8738094
	CSCF4860N6D*+TXV	G*VC961205DNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,880	8738095
	CSCF4860N6D*+TXV	G*VM971205DNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,880	8738096
	CSCF4860N6D*+TXV	G*VC80805C*B*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,820	8738097
	CSCF4860N6D*+TXV	G*VC81005C*B*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,790	8738098
	CSCF4860N6D*+TXV	A*VC961005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,725	8738109
	CSCF4860N6D*+TXV	A*VM971005CNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,725	8738110
	CSCF4860N6D*+TXV	A*VC961205DNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,880	8738111
	CSCF4860N6D*+TXV	A*VM971205DNA*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,880	8738112
	CSCF4860N6D*+TXV	A*VC80805C*B*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,820	8738113
	CSCF4860N6D*+TXV	A*VC81005C*B*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,790	8738114
	CSCF4860N6D*+TXV	G*VC80805D*B*	54,000	42,800	15.0	11.5	52,000	41,800	58,000	8.5	34,000	1,650	9924322


[^] Rated in accordance with ANSI/AHRI Standard 210/240¹ Seasonal Energy Efficiency Ratio² Energy Efficiency Ratio @ 80°F/ 67°F/ 95°F³ TVA Rating: BTU/h @ 75°F/ 63°F - 95°F⁴ Rated heating capacity at 47°F outdoor per AHRI 210/240⁵ HSPF = Heating Seasonal Performance Factor⁶ Heating capacity at 17°F outdoor**NOTES**

- Always check the S&R plate for electrical data on the unit being installed.
- When matching outdoor unit to indoor unit, use the piston supplied with the outdoor unit or that specified on the piston kit chart supplied with the indoor unit.
- EEP - Order from Service Dept. Part No. B13707-38 or new Solid State Board B13707-35S. Part No. B13707-38 is not interchangeable with B13707-35S. The Goodman Gas Furnace contains the EEP cooling time delay.





0140R00171 - D



Wiring is subject to change. Always refer to the wiring diagram or the unit for the most up-to-date wiring.

WARNING

High Voltage: Disconnect all power before servicing or installing this unit. Multiple power sources may be present. Failure to do so may cause property damage, personal injury, or death.

MODEL #	DESCRIPTION	GSZ16 018	GSZ16 024	GSZ16 030	GSZ16 036	GSZ16 042	GSZ16 048	GSZ16 060
ABK-20	Anchor Bracket Kit*	X	X	X	X	X	X	X
CSR-U-1	Hard-start Kit	X	X	X	X	X	X	
CSR-U-3	Hard-start Kit							X
FSK01A ¹	Freeze Protection Kit	X	X	X	X	X	X	X
LAKT01A	Low-Ambient Kit	X	X	X	X	X	X	X
OT18-60A ²	Outdoor Thermostat w/ Lockout Stat	X	X	X	X	X	X	X
TX2N4A ³	TXV Kit	X	X					
TX3N4	TXV Kit			X	X			
TX5N4	TXV Kit					X	X	X

⁰ Contains 20 brackets; four brackets needed to anchor unit to pad

¹ Installed on indoor coil

² Required for heat pump applications where ambient temperatures fall below 0°F with 50% or higher relative humidity.

³ Condensing units and heat pumps with reciprocating compressors require the use of start-assist components when used in conjunction with an indoor coil using a non-bleed thermal expansion valve refrigerant metering device or liquid line solenoid kit. The TXV should always be sized based on the tonnage of the outdoor unit.