



Product Categories / Plumbing / Toilets, Urinals & Repair Parts / Toilet Repair Parts & Accessories / Toilet Flush Valve Repair Parts & Accessories / Spud: Fits American Std Brand, For American Std...



AMERICAN STANDARD

Spud: Fits American Std Brand, For American Std, 1 1/2 in Size, Brass/Rubber

Item #4THJ7

UNSPSC #47131705

Mfr. Model #047007-0070A

Catalog Page #2757

Country of Origin Mexico. Country of Origin is subject to change.

Toilet flush-valve spuds, spud couplings, and friction rings form a water-tight connection between a flush valve (flushometer) and a toilet. Spuds are fittings with one end for attaching to a fixture's mouth. [View More](#)

Web Price

\$20.71 / each

Qty

1

Add to Cart

 Ship

 Pickup

Expected to arrive Tue, Jul 26.

Ship to 12020 | [Change](#)

Shipping Weight 0.56 lbs

[Ship Availability Terms](#)[Add to List](#)

Technical Specs

| | |
|-----------------------------------|---|
| Item | Spud |
| For Use With Category | Toilets |
| For Use With Sub-Category | Flush Valves |
| Fits Brand | American Standard |
| For Use with Series | American Standard |
| For Use With | Toilets |
| For Use With Grainger Item Number | 15W677, 1ZKZ2, 32V885, 5NTV8 |
| For Use With Mfr. Model Number | 2257001.020, 6571014.020, 6581015.020, 9504999.020, 9512999.020 |
| Size | 1 1/2 in |
| Material | Brass, Rubber |
| Includes | Brass Washer, Rubber Gasket and Brass Nut, Spud |

Compliance and Restrictions

This item is restricted in certain countries. [View all countries](#).

Documentation

[Repair Parts List](#)



Product Categories / Plumbing / Toilets, Urinals & Repair Parts / Flush Valves & Retrofit Kits / Manual Flush Valves / Manual Flush Valve: Sloan, 1.6 gpf Gallons per ...



SLOAN

Manual Flush Valve: Sloan, 1.6 gpf Gallons per Flush, 16 in Rough-In, 1 1/2 in Spud Coupling

Item #611M51

Mfr. Model #3788116

UNSPSC #40141609

Catalog Page #N/A

Country of Origin USA. Country of Origin is subject to change.

Manual toilet flush valves are sized to fit tankless toilets. These hand-activated valves have a spud coupling for attaching to a toilet spud. They typically require a high-pressure water supply to operate.

Web Price

\$299.42 / each

Qty

1

Add to Cart

 Ship

 Pickup

Expected to arrive Tue. Jul 26.

Ship to 12020 | Change

Shipping Weight 9.15 lbs

Ship Availability Terms

Add to List

Technical Specs

| | |
|-------------------------------|--------------------|
| Item | Manual Flush Valve |
| Flush Valve Location | Concealed |
| Fixture Connection | Rear Spud |
| Brand and Series | Sloan |
| For Use With Category | Toilets |
| Flush Mode | Single Flush |
| Gallons per Flush | 1.6 gpf |
| Flush Valve Design | Diaphragm |
| Rough-In | 16 in |
| Spud Coupling | 1 1/2 in |
| Inlet Size | 1 in IPS |
| Pressure Range | 15 to 80 psi |
| Finish | Rough Brass |
| Includes | Valve |
| Manufacturers Warranty Length | 3 yr |
| Standards | BAA |