

**CERTIFICATION OF WORK
PREVENTIVE MAINTENANCE**

(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: NY039 Date of Visit: 11/29/21

Contractor Personnel on Site:

- | | |
|-------------------------|----------|
| 1. <u>PATRICK BROWN</u> | 3. _____ |
| 2. _____ | 4. _____ |

Work Performed:


Preventive Maintenance - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)

1. WO#'S , 14978 , 14979 , 15146 -15149 , 15161 , 15165 , 15176 , 15186 ,
2. 15150 , 15151-15153
3. ASSET#'S , 9932 , 9935 , 9898 , 9929 , 9933 , 9934 , 9890 , 9940 ,
4. 9941 , 9946 , 9947 , 190917- , 269 , 250 , 251 , 263 , 268 , 265 , 266
5. _____

CERTIFICATION OF WORK

To be signed by the Contractor:

Print Name: Patrick Brown Date: 11/29/21

Signed: 

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: SGT STORMS Date: 11/29/21


Signed: 

E-Mail: _____

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST

GATES

SITE AND BLDG #: NY039 BLDG1

MECHANIC
SIGNATURE: 

DATE: 11/29/21

LOCATION/RM #: MOV parking

WO# 14979

ASSET # 9935

START TIME: 7:30AM

FINISH TIME: 8am

15165

190917-269

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
SPECIAL INSTRUCTIONS				
1	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	☒	☒	
2	Notify affected personnel before performing PM	☒	☒	
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	Inspect all pivot points, hinges, latches, etc. Apply lubricant where needed, wiping off excess.	☒	☒	used PB blaster garage door lubricant
2	Check all locking devices. Lubricate as required.	☒	☒	all are good
3	Inspect gate support rollers and track, lubricate and clean as required.	☒	☒	used white lithium grease
4	Check bolts, fasteners, and mounting hardware. Tighten as necessary.	☒	☒	all are tight
5	Check for any obstructions that prevent full swing or movement of the gate.	☒	☒	no obstructions
6	Check that shrubs and trees are pruned clear of gate.	☒	☒	shrubs and trees are clear of gate
7	Check hold open devices for proper operation. Lubricate as required.	☒	☒	
8	Check the top guard and ensure that it is properly fastened and the wires are tight. Tighten as required.	☒	☒	top gaurd and wires are tight
9	If applicable, inspect hydraulic driveline (hoses, fittings, and gauges) for signs of leakage.	☒	☒	no hydraulics
10	If applicable, inspect limit switches for proper operation. Adjust as needed.	☒	☒	limit switches are correct
11	If applicable, inspect photoeyes for proper operation and any signs of damage.	☒	☒	no sign's of damage
12	If applicable, have site personnel operate gate with CAC Card insuring proper operation.	☒	☒	gate functions properly with card
13	If applicable, clean control cabinent, ensuring free from debris and insects.	☒	☒	no debris or insects

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed discription of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes: the rear gate is under construction