

**CERTIFICATION OF WORK  
PREVENTIVE MAINTENANCE**

(To be completed by the Contractor and saved in the Contractor's CMMS)

FACID/Building: \_\_\_\_\_ Date of Visit: 6/14/19

Contractor Personnel on Site:

1. _____	3. _____
2. _____	4. _____

**Work Performed:**

**Preventive Maintenance** - Services Completed (Annual, Quarterly, Monthly, equipment identification, etc.)

1. \_\_\_\_\_
2. \_\_\_\_\_
3. \_\_\_\_\_
4. \_\_\_\_\_
5. \_\_\_\_\_

---

**CERTIFICATION OF WORK**

To be signed by the Contractor:

Print Name: Johnny W Brown Date: 6/14/19

Signed: 

To be signed by Facility Manager:

By signing the Certification of Work, the said government representative signature does not constitute acceptance of any work performed by the contractor, it only acknowledges that the contractor was on-site during the identified timeline:

Print Name/Rank: SPC. Tyler Packard Date: 6/14/19

Signed: 

E-Mail: \_\_\_\_\_

**PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST**  
**FAN COIL UNIT/ DUCTLESS MINI SPLIT**

SITE AND BLDG #: **MD019-01****2048**LOCATION/RM #: **WO# 8934****ASSET # 2050****8950****2049**MECHANIC  
SIGNATURE: 

DATE:

**6/14/19**START TIME **0900**

FINISH TIME:

**1630**

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
<b>SPECIAL INSTRUCTIONS</b>				
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
2	Schedule shutdown with operating personnel, as needed.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
3	As needed, de-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work. Follow lock out/tag out procedures at all times.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<b>TO BE PERFORMED AT EACH INSPECTION SERVICE</b>				
1	Check fan blades for dust buildup and clean if necessary.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
2	When applicable, check fan blades and moving parts for cracks and excessive wear.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
3	Tighten all electrical connectors to proper torque as needed.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
4	Check that the fan runs properly in all speeds as applicable.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
5	Check dampers and rotating auto diffusers for dirt accumulations, clean as necessary. Check felt, repair or replace as necessary.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
6	Check damper actuators and linkage for proper operation as applicable. Adjust linkage on dampers if out of alignment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
7	Lubricate mechanical connections of dampers sparingly as applicable.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
8	Check the valve(s) for signs of leakage and proper operation. If leak is detected, submit a UE.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
9	Clean coils by brushing, blowing, vacuuming, or pressure washing.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
10	Check coils for leaking, tightness of fittings.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
11	Use fin comb to straighten coil fins as needed.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
12	Check belts for wear and cracks, adjust tension or alignment as applicable. Replace belts when necessary.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
13	Check rigid couplings for alignment on direct drives, and for tightness of assembly	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
14	Vacuum interior of unit.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO, PROVIDE EXPLANATION)
		YES	NO	
15	Check filter door for proper gasketing and air leaks. Correct as necessary.			
16	Change the filter as needed with the correct size and type filter.			
17	Insure that drain(s) are clear and running.			
18	Clean up work area.			

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

**Additional Notes:**