

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST MANUAL/AUTOMATIC OVERHEAD DOORS

SITE AND BLDG #: 44024-358

MECHANIC SIGNATURE: Michael

DATE: 7/14/15

LOCATION/RM #: _____

WO# _____

ASSET # _____

START TIME: _____

FINISH TIME: _____

CHECK POINT	CHECKPOINT DESCRIPTION	TASK COMPLETE		NOTES/ ACTIONS (IF TASK COMPLETE IS CHECKED NO. PROVIDE EXPLANATION)
		YES	NO	
1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered.	<input checked="" type="checkbox"/>		
2	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	<input checked="" type="checkbox"/>		
TO BE PERFORMED AT EACH INSPECTION SERVICE				
1	Check with door operating personnel for any known deficiencies.	<input checked="" type="checkbox"/>		2 VISIT CASE DOORS
2	Inspect general arrangement of door and mechanism, mountings, standards, wind locks, anchor bolts, counterbalances, weather stripping, door sweeps etc. Clean, tighten, and adjust repair as required.	<input checked="" type="checkbox"/>		
3	If applicable, operate with power from start to stop and at intermediate positions. Observe performance of various components, such as brake, limit switches, door operating speed, motor, gear box, etc. Clean and adjust as needed.	<input checked="" type="checkbox"/>		
4	Check operation of safety edges, stops, electric eye, treadle, or other operating devices. Clean and make required adjustments or repairs.	<input checked="" type="checkbox"/>		
5	Check manual operation. Note brake release, motor disengagement, functioning or hand pulls, chains sprockets, clutch, etc.	<input checked="" type="checkbox"/>		
6	If applicable, examine all wiring, motor, starter, push button, etc., blow out or vacuum if needed.	<input checked="" type="checkbox"/>		
7	If applicable, inspect gear box, change or add oil as required.	<input checked="" type="checkbox"/>		
8	Perform required lubrication. Remove old or excess lubricant.	<input checked="" type="checkbox"/>		
9	Clean unit and mechanism thoroughly. Touch up paint where required.	<input checked="" type="checkbox"/>		
10	Clean up and remove all debris.	<input checked="" type="checkbox"/>		

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.
To be performed by: General Maintenance Worker

Additional Notes:

ASST
44-8A-9613
44-8A-9614
44-8A-9615
44-8A-9616
44-8A-9617
44-8A-9618
44-8A-9619
44-8A-9620
44-8A-9621
44-8A-9622
44-8A-9623
44-8A-9624
44-8A-9625
44-8A-9626
44-8A-9627
44-8A-9628
44-8A-9629
44-8A-9630
44-8A-9631
44-8A-9632
44-8A-9633
44-8A-9634
44-8A-9635
44-8A-9636
44-8A-9637
44-8A-9638
44-8A-9639
44-8A-9640
44-8A-9641
44-8A-9642
44-8A-9643
44-8A-9644
44-8A-9645
44-8A-9646
44-8A-9647
44-8A-9648
44-8A-9649
44-8A-9650
44-8A-9651
44-8A-9652
44-8A-9653
44-8A-9654
44-8A-9655
44-8A-9656
44-8A-9657
44-8A-9658
44-8A-9659
44-8A-9660
44-8A-9661
44-8A-9662
44-8A-9663
44-8A-9664
44-8A-9665
44-8A-9666
44-8A-9667
44-8A-9668
44-8A-9669
44-8A-9670
44-8A-9671
44-8A-9672
44-8A-9673
44-8A-9674
44-8A-9675
44-8A-9676
44-8A-9677
44-8A-9678
44-8A-9679
44-8A-9680
44-8A-9681
44-8A-9682
44-8A-9683
44-8A-9684
44-8A-9685
44-8A-9686
44-8A-9687
44-8A-9688
44-8A-9689
44-8A-9690
44-8A-9691
44-8A-9692
44-8A-9693
44-8A-9694
44-8A-9695
44-8A-9696
44-8A-9697
44-8A-9698
44-8A-9699
44-8A-9700