

PREVENTATIVE MAINTENANCE PROGRAM CHECKLIST LIGHTING, OUTSIDE

SITE AND BLDG #: 24024-356

MECHANIC SIGNATURE: [Signature]

DATE: 3/13/2022

LOCATION/RM #:

WO #

7455 ASSET #

9789

START TIME:

FINISH TIME:

1	In addition to the procedure(s) outlined in this standard, the equipment manufacturer's recommended maintenance procedure(s) and/or instruction(s) shall be strictly adhered to.	<input checked="" type="checkbox"/>			2 Boxes out
2	Schedule and coordinate work with operating personnel.	<input checked="" type="checkbox"/>			They are out
3	Follow lock out/tag out procedures at all times. De-energize or discharge all hydraulic, electrical, mechanical, or thermal energy prior to beginning work.	<input checked="" type="checkbox"/>			
1	Open and tag switch.	<input checked="" type="checkbox"/>			
2	Inspect visual condition of wiring. Look for evidence of overheating.	<input checked="" type="checkbox"/>			
3	Check for proper light operation.	<input checked="" type="checkbox"/>			
4	Test operation of automatic switches/ time clock/ photocells if applicable.	<input checked="" type="checkbox"/>			
5	Inspect light pole and mounting devices for deficiencies.	<input checked="" type="checkbox"/>			
6	For any noted deficiency, takes pictures and open corrective maintenance ticket.	<input checked="" type="checkbox"/>			Change in tower

Note: The technician shall perform any repairs identified during PM up to \$250 (direct labor and direct material cost) per PM occurrence. For any deficiencies found exceeding \$250 open a corrective maintenance (CM) ticket and include the Asset #, WO #, photos, and a detailed description of the deficiency.

To be performed by: General Maintenance Worker

Additional Notes:

4 PC DOUBLE LIGHT POLE - 2 lights out